INCH-POUND


MIL-PRF-83536/6D
25 October 2010
SUPERSEDING
MIL-PRF-83536/6C
01 December 2008

PERFORMANCE SPECIFICATION SHEET

# RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 4PDT, LOW LEVEL TO 5 AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED, ALL WELDED, TRANSIENT SUPPRESSED DC COILS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-83536.




| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | --- | .810 | --- | 20.57 |
| B | --- | .640 | --- | 16.25 |
| C | --- | .810 | --- | 20.57 |
| D | .140 TYP | .160 TYP | 3.55 TYP | 4.06 TYP |
| E | .140 TYP | .160 TYP | 3.55 TYP | 4.06 TYP |

FIGURE 1. Dimensions and configurations.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.





FIGURE 1. Dimensions and configurations - Continued.




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | --- | .810 | --- | 20.57 |
| B | .015 | .035 | 0.38 | 0.89 |
| C | .146 | .166 | 3.71 | 4.22 |
| D | --- | .640 | --- | 16.25 |
| E | 1.068 | 1.088 | 27.13 | 27.63 |
| F | 1.052 | 1.072 | 26.72 | 27.23 |
| G | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| H | .702 | .722 | 17.83 | 18.34 |
| J | .131 TYP | .151 TYP | 3.33 TYP | 3.83 TYP |
| K | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| L | --- | 1.280 | --- | 32.51 |
| M | .240 | .260 | 6.10 | 6.60 |
| N | .490 | .510 | 12.45 | 12.95 |
| P | --- | .810 | --- | 20.57 |
| Q | .123 TYP | .153 TYP | 3.12 TYP | 3.89 TYP |
| R | .840 | .860 | 21.34 | 21.84 |
| S | .100 | .120 | 2.54 | 3.05 |
| T | .415 | .435 | 10.54 | 11.05 |
| U | .021 R | .041 R | 0.53 R | 1.04 R |
| V | 1.060 | 1.080 | 26.92 | 27.43 |
| W | .240 | .260 | 6.10 | 6.60 |
| X | .490 | .510 | 12.45 | 12.95 |
| Y | .840 | .860 | 21.34 | 21.84 |
| Z | .137 | .143 | 3.48 | 3.63 |

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.





| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | 1.068 | 1.088 | 27.13 | 27.63 |
| B | 1.052 | 1.072 | 26.67 | 27.23 |
| C | --- | .810 | --- | 20.57 |
| D | --- | .640 | --- | 16.26 |
| E | .590 | .610 | 14.99 | 15.49 |
| F | .395 | .415 | 10.03 | 10.54 |
| G | .131 TYP | .151 TYP | 3.33 TYP | 3.83 TYP |
| H | .123 TYP | .143 TYP | 3.12 TYP | 3.63 TYP |
| J | --- | .810 | --- | 20.57 |
| K | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| L | .015 | .035 | 0.38 | 0.89 |
| M | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| N | --- | 1.280 | --- | 32.51 |
| P | 1.060 | 1.080 | 26.92 | 27.43 |
| Q | .395 | .415 | 10.03 | 10.54 |
| R | .135 | .145 | 3.43 | 3.68 |

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.




| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | --- | .810 | --- | 20.57 |
| B | .075 | .085 | 1.90 | 2.16 |
| C | .155 | .161 | 3.94 | 4.09 |
| D | .160 | .180 | 4.06 | 4.57 |
| E | .010 R | .020 R | 0.25 R | 0.51 |
| F | --- | .690 | --- | 17.53 |
| G | .050 | .060 | 1.27 | 1.52 |
| H | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| J | .210 | .220 | 5.33 | 5.59 |
| K | .105 | .115 | 2.67 | 2.92 |
| L | .140 TYP | .160 TYP | 3.56 TYP | 4.06 TYP |
| M | .425 | .435 | 10.80 | 11.05 |
| N | --- | .810 | --- | 20.57 |

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.





FIGURE 1. Dimensions and configurations - Continued.




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | 1.02 | 1.08 | 25.9 | 27.4 |
| B | --- | .810 | --- | 20.57 |
| C | .030 | .040 | 0.76 | 1.02 |
| D | .046 | .078 | 1.17 | 1.98 |
| E | .060 | --- | 1.52 | --- |
| F | .090 | .093 | 2.29 | 2.36 |
| G | --- | .704 | --- | 17.88 |
| H | .282 | .302 | 7.16 | 7.67 |
| J | .251 | .271 | 6.37 | 6.88 |
| K | .049 | .051 | 1.24 | 1.29 |
| L | .055 | .085 | 1.40 | 2.16 |
| M | .135 | .145 | 3.43 | 3.68 |
| N | .1.382 | 1.462 | 35.10 | 37.13 |
| P | .070 | .080 | 1.78 | 2.03 |
| Q | .030 | .050 | 0.76 | 1.27 |
| R | .039 | .041 | 0.99 | 1.04 |
| S | .065 | .085 | 1.65 | 2.16 |
| T | .145 TYP | .155 TYP | 3.68 TYP | 3.93 TYP |
| U | .070 | .080 | 1.78 | 2.03 |
| V | .145 TYP | .155 TYP | 3.68 TYP | 3.93 TYP |
| W | .070 | .080 | 1.78 | 2.03 |
| X | --- | .810 | --- | 20.57 |

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.




| Ltr | Inches | | Millimeters | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | .160 | .180 | 4.06 | 4.57 |
| B | .038 | .042 | 0.96 | 1.07 |
| C | .039 | .041 | 0.99 | 1.04 |
| D | .160 | .180 | 4.06 | 4.57 |
| E | ..038 | .042 | 0.96 | 1.07 |
| F | --- | .210 | --- | 5.33 |

FIGURE 1. Dimensions and configurations - Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .010 (0.25 mm).
4. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified.
5. These relays are polarized monostable.
6. This relay shall not operate or be damaged by reverse polarity.
7. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electro-magnet flux.
8. Applicable to horizontal flange mount only. The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side. The remaining portion of the nameplate data shall be marked on the far side.
9. Applicable to horizontal flange mount only. Relays shall be marked with the manufacturer's name or CAGE code, date code and serial number. Marking shall be with the bottom of the print adjacent to the near side.
10. Socket pin terminals shall provide the operational, environmental, and interface characteristics to provide a reliable interconnect to gold-plated contacts. Terminals, track mount B polarizing pin and ground pin, shall be gold plated. One system for gold plating that may be used is ASTM B488, type 3, class 1.25 with a nickel underplate of 50 to 150 microinches thick. The gold plating system shall enable the product to meet the performance requirements of this specification and shall be approved by the qualifying activity.
11. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 15 to 35, thickness .050 ±.005. Gasket material according to AMS 3332 has been considered acceptable.
12. Back EMF (transient voltage): 42 V dc maximum.
13. JANTX or equivalent screened semiconductors or hybrid devices shall be used for internal coil suppression. Relays using suppression devices shall continue to operate should the suppression circuits be in a failure mode. Diodes shall have a peak inverse voltage of 600 V dc minimum and a current rating of one ampere at +25°C. The zener diode shall have a power rating of one watt at +25°C.
14. Track mount B is covered by Deutsch Relays, Incorporated, patent number 4,201,437.
15. Represents minimum travel required to engage locking cutout on mating socket module.
16. Track mount shall be corrosion resistant. One way of ensuring corrosion resistance is to nickel plate 303 stainless steel with 100 microinches minimum thickness. The finish on the top of the knob shall be lusterless black number 37038 in accordance with FED-STD-595 except that the slot shall be white marking color, number 27886 in accordance with FED-STD-595 The post shall be polyamide-imide in accordance with McDonnell Douglas Dwg. ST5M1454 (Deutsch Relays, Inc. Patent number 4,201,437).
17. Direction of 29° rotation to engage locking cutout on mating socket module.
18. Measure from surface of header.
19. Track mount B relay external materials and finishes shall be in accordance with McDonnell Douglas Dwg ST5M1454 (Deutsch Relays, Incorporated, patent number 4,201,437) and applicable specifications. Track mount B relay housing and header shall be corrosion resistant. One way of ensuring corrosion resistance is to nickel plate with 100 microinches minimum thickness.
20. The rotation of the knob mechanism shall be restricted such that the latching pins cannot be placed on the side opposite the McDonnell Douglas ST5M1457 (Deutsch Relays, Incorporated, patent number 3,790,915) bracket cutouts.
21. Indicated terminal shall be identified with a contrasting bead.
22. Plane of critical motion for vibration and shock is Y-axis.
23. Gasket shall provide a reliable seal between the relay and mating socket that will meet the environmental, operational, and interface requirements of the relay with the mating socket. The gasket shall have shore hardness 15 to 35, thickness. 050 ±.005. Gasket material according to AMS 3332 has been considered acceptable.

FIGURE 1. Dimensions and configurations – Continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Load ratings: See table I.

Low level: 10 to 50 μA at 10 to 50 mV dc or peak ac.

Intermediate current: Applicable.

Mixed loads: Applicable.

TABLE I. Rated contact load and cycles (amperes per pole).

| Type of load (high level) | Cycles x $10^3$ | 28 V dc | 115 V ac 1 phase 400Hz | 115/200 V ac 3 phase 400 Hz |
|---|---|---|---|---|
| Resistive | 100 | 5 | 5 | 5 |
| Inductive | 20 | 3 | 5 | 5 |
| Motor | 100 | 2 | 3 | 3 |
| Lamp | 100 | 1 | N/A | N/A |

Life: 100,000 cycles, unless otherwise specified (see table I).

Contact voltage drop or resistance:

Initial contact voltage drop: 0.100 volt maximum. Rated resistive current at 6 V dc or peak ac. Relays shall not make or break this load.

Initial contact resistance: 0.050 ohm maximum. 50 mA max at 6 V dc or peak ac.

High level life (contact voltage drop):

During life: 10 percent open circuit voltage maximum.

After life: 0.125 volt maximum.

Intermediate current (contact resistance):

During intermediate current: 3 ohms maximum.

After intermediate current: 0.150 ohm maximum.

Low level (contact resistance):

During low level: 100 ohms maximum.

After low level: 0.150 ohm maximum at 100 mA and 28 V dc.

Contact bounce: 1.0 millisecond maximum.

Contact stabilization time: 2.5 milliseconds maximum.

Break bounce (normally open contacts): 0.1 millisecond maximum.

Overload current: 20 amperes dc, 30 amperes ac.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

Rupture current: 25 amperes dc, 40 amperes ac.

Time current relay characteristics: See table II.

TABLE II. Time current relay characteristics. 1/

| Successive application | Amperes | Time |
|---|---|---|
| 1 | 10 | 1 hour |
| 2 | 15 | 20 seconds |
| 3 | 37.5 | 2 seconds |
| 4 | 75 | .53 second |

1/ All relays shall withstand overload and fault currents. Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of four different current levels in the sequence listed in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase. Cooling time between successive applications shall be 30 minutes. Tests shall be performed on both normally open and normally closed contacts. There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion.

Coil data 1/: See table III.

Operate time: 6 milliseconds maximum at rated coil voltage at 25°C. 7 milliseconds maximum at rated coil voltage over the temperature range.

Release time: 6 milliseconds maximum from rated coil voltage at 25°C. 7 milliseconds maximum from rated coil voltage over the temperature range.

Duty rating: Continuous.

Coil transient suppression: Applicable (42 V dc maximum).

Neutral screen: Not applicable.

Electrical data:

Insulation resistance:

Initial: 100 megohms at 500 V dc.

After life or environmental tests: 50 megohms at 500 V dc.

1/ CAUTION: Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations:

a. Row to row assisting fields: .125 (3.18 mm).

b. Row to row opposing fields: .1875 (4.763 mm).

c. Side to side alternating fields: .0625 (1.588 mm).

d. Side to side like fields: .125 (3.18 mm).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

TABLE III. Dash numbers and characteristics. 1/

| Dash number 2/ | | | Mount | Coil data | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | At 25°C | | | | | | Over temperature range | | | Maximum pickup voltage | |
| Solder pin | Solder hook | Socket pin | | Coil voltage (V dc) 3/ | | Coil resist-ance (ohms) minimum | Specified pickup voltage (V dc) 4/ | Specified hold voltage (V dc) 4/ | Specified dropout voltage (v dc) 4/ | Specified pickup voltage (V dc) 4/ | Specified hold voltage (V dc) 4/ | Specified dropout voltage (V dc) 4/ | High temper-ature test | Contin-uous current test |
| | | | | Rated | Max | | | | | | | | | |
| 001 | 002 | 003 | No mount | 6 | 7.3 | 15 | 3.3 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 004 | 005 | 006 | RVFM | 6 | 7.3 | 15 | 3.3 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 007 | 008 | --- | HFM | 6 | 7.3 | 15 | 3.3 | 1.6 | 0.4 | 4.5 | 2.3 | 0.25 | 5.0 | 5.7 |
| 009 | 010 | 011 | No mount | 12 | 14.5 | 70 | 6.6 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 012 | 013 | 014 | RVFM | 12 | 14.5 | 70 | 6.6 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 015 | 016 | --- | HFM | 12 | 14.5 | 70 | 6.6 | 3.3 | 0.75 | 9.0 | 4.5 | 0.5 | 9.9 | 11.25 |
| 017 | 018 | 019 | No mount | 28 | 29 5/ | 360 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| 020 | 021 | 022 | RVFM | 28 | 29 5/ | 360 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| 023 | 024 | --- | HFM | 28 | 29 5/ | 360 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| --- | --- | 6/ 7/ 025 | Track A | 28 | 29 | 360 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 | 22.5 |
| --- | --- | 026 | Track B | 28 | 29 | 360 | 13.5 | 5.5 | 2.3 | 18.0 | 7.0 | 1.5 | 19.8 8/ | 22.5 |
| 027 | 028 | 029 | No Mount | 48 | 50 | 1125 | 24.0 | 10.0 | 3.0 | 36.0 | 12.0 | 2.4 | 40.0 | 44.0 |
| 030 | 031 | 032 | RVFM | 48 | 50 | 1125 | 24.0 | 10.0 | 3.0 | 36.0 | 12.0 | 2.4 | 40.0 | 44.0 |
| 033 | 034 | --- | HFM | 48 | 50 | 1125 | 24.0 | 10.0 | 3.0 | 36.0 | 12.0 | 2.4 | 40.0 | 44.0 |

See footnotes on next page.





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

TABLE III. Dash numbers and characteristics – Continued 1/

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications.
2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number. Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0.1; R, 0.01. Example: 001L, 002R.
3/ CAUTION: The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay.
4/ Pickup, hold, and dropout voltages as shown are for test purposes only and are not to be used for design criteria.
5/ When maximum ambient temperature does not exceed +85°C, the maximum coil voltage shall be 32 V dc.
6/ Internal visual: Accomplish on a 100 percent basis prior to final encapsulation of the device to detect and eliminate devices with internal defects or foreign particles that could lead to device failure. The inspection equipment shall include optical equipment of at least 10X magnification and visual standards to permit the inspector to make objective decisions as to the acceptability of the device being examined.
7/ For qualification only, the relay shall meet the test requirements of this specification when installed in relay socket mount MIL-DTL-12883/52 and relay bracket mount MIL-DTL-12883/53 except shock shall be 50 g's for 11 ± 1 milliseconds. No contact opening or closing in excess of 10 microseconds.
8/ Applicable to track mount B only, high temperature test and continuous current shall be performed at +95°C and +125°C. The values for high temperature test and continuous current at +95°C shall be 18 V dc and 19.5 V dc, respectively.




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage 2/:

| | Track mount B | | All others | |
|---|---|---|---|---|
| | Coil to case | All other points | Coil to case | All other points |
| Sea level: | | | | |
| Initial: | 1050 | 1050 | 1000 | 1000 |
| After life: | 1050 | 1050 | 750 | 750 |
| Altitude: | | | | |
| At 80,000 feet: | 500 | 500 | 250 | 250 |
| At 300,000 feet: | --- | --- | 500 | 500 |

Maximum leakage current for track mount B only: 100 microamperes rms.

Environmental characteristics:

Temperature range: -70°C to +125°C.

Maximum altitude rating: 300,000 feet, 80,000 feet for track mount B.

Acceleration: Applicable, except 15 g's.

Shock (specified pulse): Applicable, MIL-STD-202, method 213, test condition C, 200 g's for 6 ±1 ms, except horizontal flange mount peak g value shall be 100 g's for 6 ±1 ms. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts. For track mounting, see table lll, footnote 7.

Vibration (sinusoidal): Applicable, MIL-STD-202, method 204, 30 g's except frequency range shall be 70 to 3,000 Hz. Horizontal flange mount shall be 20 g's, 57 Hz to 3,000 Hz. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (sinusoidal): Applicable to track mount A only. Test in accordance with MIL-STD-202, method 204. .06 inch double amplitude, 10 to 55 Hz. 10 g's, 55 to 500 Hz, 20 g's, 500 to 3,000 Hz. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to qualification and group C inspection. Test in accordance with MIL-STD-202, method 214, test condition IG (0.4 $g^2$/Hz, 50 to 2000 Hz), for horizontal flange mount test condition IE (0.2 $g^2$/Hz). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to track mount A only. Applicable to qualification and group C inspection. Test in accordance with MIL-STD-202, method 214, test condition IF (0.3 $g^2$/Hz, 50 to 2000 Hz). Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Vibration (random): Applicable to track mount B only. Applicable to qualification only. Test in accordance with MIL-STD-202, method 214, test condition IJ, 1.5 hours per axis. Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 10 microseconds maximum closure for open contacts.

2/ Dielectric may be improved by suitable insulation of terminals and wiring after installation.
Physical data:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

Dimensions and configurations: See figure 1.

Weight: For track mount B: 0.072 pound (32.6 grams) maximum. For all others: 0.058 pound (26.4 grams) maximum.

Terminal strength:

Solder hook terminals:

Pull force: 5 pounds ±0.5 pound.

Bend: Applicable.

Twist: Not applicable.

Solder pin terminals:

Pull force:

For .040 diameter terminals: 5 pounds ±0.5 pound.

Bend: Applicable.

Twist: Not applicable.

Socket pin terminals:

Pull force:

For .040 diameter terminals: 5 pounds ±0.5 pound.

For .050 diameter terminals: 10 pounds ±0.5 pound (applicable to track mount B polarizing pin only).

Bend: Applicable.

Twist: Not applicable.

Terminal solderability: Applicable to solder pin and solder hook terminals only.

Seal: Hermetic.

Marking: Applicable.

Part or Identifying Number (PIN): M83536/6 (dash number from table III and suffix letter designating failure rate level).

Qualification inspection:

Qualification inspection and sample size: See table IV.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

TABLE IV. Qualification inspection and sample size. 1/

| Single submission | Group submission | |
|---|---|---|
| 18 units plus 1 open unit for level L at C = 0 2/ | M83536/6-022 | 18 units plus 1 open unit for level L at C = 0 2/ |
| 33 units plus 1 open unit for level M a5t C = 0 2/ | M83536/6-022 | 33 units plus 1 open unit for level M at C = 0 2/ |
| Qualification inspection as applicable | M83536/6-022 | Qualification inspection as applicable |
| | M83536/6-018<br>M83536/6-023<br>M83536/6-026 | 2 units, qualification inspection table, group II, shock, vibration, acceleration, terminal strength, and seal |
| | M83536/6-002<br>M83536/6-014<br>M83536/6-033 | 2 units, qualification inspection table, group II |

1/ For retention of qualification or extension of qualification to lower failure rate levels, all life test data accumulated on MIL-PRF-83536/5 may be used in addition to MIL-PRF-83536/6 data. Prior to performance of retention of qualification testing, the relay manufacturer shall preselect the sampling plan.

2/ The number of units required for qualification testing shall be increased as required in group V, table II of MIL-PRF-83536, if the contractor elects to test the number of units permitting one or more failures. Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.

Supersession data: See table V.

TABLE V. Supersession data.

| Superseded PIN M6106/ | Replacement PIN M83536/6- |
|---|---|
| 22-003 | 025 |
| 28-003 | 017 |
| 28-004 | 017 |
| 28-007 | 018 |
| 28-008 | 018 |
| 28-011 | 019 |
| 28-012 | 019 |
| 28-015 | 020 |
| 28-016 | 020 |
| 28-019 | 021 |
| 28-020 | 021 |
| 28-023 | 022 |
| 28-024 | 022 |
| 28-027 | 023 |
| 28-028 | 023 |
| 28-031 | 024 |
| 28-032 | 024 |
| 28-038 | 012 |
| 28-040 | 013 |
| 28-042 | 014 |
| 28-044 | 015 |
| 28-046 | 016 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-83536, this document references the following:

ASTMB488
AMS3332
FED-STD-595/27886
FED-STD-595/37038
MIL-DTL-12883/52
MIL-DTL-12883/53
MIL-STD-202
MIL-PRF-83536/5
ST5M1454
ST5M1457

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Air Force - 99

Preparing activity:
DLA - CC

(Project 5945-2010-031)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:44Z
Check the source to verify that this is the current version before use.