MILITARY SPECIFICATION SHEET

CHASSIS, TRAILER, SIZE 9, MILITARY DESIGN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the size 9 military design trailer chassis described herein shall consist of this document and the latest issue of specification MIL-C-52437.

REQUIREMENTS:

1. The trailer chassis is the drop axle or trailing arm trailer chassis intended for towing behind the 2-1/2-ton and 5-ton M-series military design truck fleet (see GI trucks per MIL-T-46780 and MIL-T-740).
2. Military design trailer chassis. The size 9 MD trailer chassis shall be constructed in accordance with TA13212E3630 with the additional requirements specified in table I and II.

TABLE I. Military design size 9 chassis.

GVWR per DOT	±8700 – lb.
Payload capacity	Minimum5000- lb.
Trailer curb weight	±3700 – lb.
Tow eye weight	15 – Percent.
OAL	175 – in.
OAH	48 – in.
OAW	96 – in.
Running gear, standar	
No. of axles	1 – ea.
- GAWR, ea. axle at hubs	10,000- lb. Ordnance std.
- No. trailer tires	2 – ea.
No. spare tires	None (using spare from truck)
Tire size	9.00 – 20
Load range	
Tire inf. press.	55 – psi
Running gear options	
Option A:	
No. of axles	
- GAWR, ea. axle at hubs	
- No. trailer tires	
No. spare tires	
Tire size	

FSC 2330

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

TABLE I. Military design size 9 chassis. (Cont'd)

Load range	
Tire inf. press.	
Option B:	
No. of axles	
- GAWR, ea. axle at hubs	
- No, trailer tires	
No. spare tires	
Tire size	
Load range	
Tire inf. press.	
Bed length, A	117 – in.
Bed width, B & C	54 – in.
Bed height, D	21 – in.
Top of fender height,	
Fender length, F	52 – in.

NOTE: The trailer chassis ball be as shown on the drawings and the technical data estimated in this table I is solely for quick reference and identification only.

TABLE II. Components of military design trailer chassis.

a. Intervehicular connections	Military types per drawings. Service on curbside. Emer. on roadside. Lines routed and protected to prevent damage from dropping of military cargo truck tailgate.
b. Suspension	Trailing arm with quarter-elliptic leaf springs per drawings. Contractor's trailer model to include the dash number of the standard various spring dash-l when specified (see 6.2, T-2), optional springs furnished as follows:
Dash - 1.	8700 lb. GVWR chassis, standard. l/
Dash - 2.	7700 lb. GVWR chassis, option.
Dash - 3.	6700 lb. GVWR chassis, option.
Dash - 4.	5700 lb. GVWR chassis, option.
Dash - 5.	4700 lb. GVWR chassis, option.
Dash - 6.	3700 lb. GVWR chassis, option.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

TABLE II. Components of military design trailer chassis. (Cont'd)

c. Fender option	Unless otherwise specified (see 6.2, T-2), fenders and fender supports furnished per drawings. Undercoat fenders and aprons with sandless commercial undercoating compound to min. of 1/16-in. thickness.
d. Splash guards	Per SAE J 682, MS51331, and TTMA RP No. 41, for trailers furnished without fenders.
e. Front platform	When specified (see 6.2, T-2), front platform furnished per drawings.
f. Rear stabilizing jack stands	When specified (see 6.2, T-2), 2 ea. rear commercial jack stands furnished per drawings. Function to support rear and level trailer, when used with front support leg. Provide firm base for operating equipment. Stand heads mate with frame-rail-mounted stand head boxes, underneath rear. Stands stowed and secured on trailer for travel.
g. Brake system	Modified, military air-over-hydraulic brake system per MIL-STD-1180 (FMVSS), as specified herein, and as shown on the drawings. Split system providing shoe-by-shoe protection. Power clusters of either 2 ea., duplicate units or of a single-unit type having any double reservoir and piston master cylinder that is matched and approved by the foundation brake manufacturer. Min. 5 in. of slack provided in each of the relay valve connections to permit interchange of various makes and models. All brake lines installed to facilitate replacement from bulk supply. All metal surfaces of foundation brakes coated with paint or lubricated to resist corrosion. High-temperature silicone compound grease used on lubricated moving parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.

TABLE II. Components of military design trailer chassis. (Cont'd)

h. Vehicle electrical system	Modified military 24-volt electrical system for service and blackout per MIL-STD-1179, only, and with drawing electrical system requirements deleted. For trailers with fenders, install lamps on the trailer. For trailers with bodies, install lamps on both body and trailer with connectors between body and trailer.

l/ See drawing No. D13212E3632, Leaf Spring, in TA13212E3630, for further details.

Custodians:
Army - ME
Air Force - 99

Preparing Activity:
Army - ME

Review activity:
Army - AT

Project 2330-0786-6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:18Z
Check the source to verify that this is the current version before use.