INCH-POUND

MIL-DTL-3943/289B
6 November 2017
SUPERSEDING
MIL-DTL-3943/289A
12 December 2012


DETAIL SPECIFICATION SHEET

DECORATION, COMMISSIONER'S DISTINGUISHED CAREER SERVICE AWARD,


U.S. BORDER PATROL

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE -DEVICE
(see piercing in notes)



OBVERSE -BASE
(see piercing in notes)



REVERSE



ASSEMBLED

MATERIAL:
DEVICE: (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)
OBVERSE BASE AND REVERSE: Gilding Metal

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:55Z
Check the source to verify that this is the current version before use.

FINISH:

DEVICE: 24K Gold Plated, Matte Finished, Polished Highlights and shall match The Institute Heraldry (TIOH) Metal Finish Chip Number 8.

BASE OBVERSE: Enameled or Epoxied, 24K Gold Plated, Matte Finished, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

BASE REVERSE: 24K Gold Plated, Matte Finished, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:

DEVICE:

HEIGTH:

-1: 1-3/32 inches (REF)

-2: 17/32 inch (REF)

WIDTH:

-1: 1-1/32 inches (REF)

-2: 1/2 inch (REF)

THICKNESS:

-1: 0.090 inch ± 0.005 inch

-2: 0.070 ± 0.005 inch

BASE:

DIAMETER Overall excluding lug):

-1: 1-3/8 inches (REF)

-2: 11/16inch (REF)

THICKNESS (At lug):

-1: 0.105 ± 0.005 inch

-2: 0.080 ± 0.005 inch

ASSEMBLED THICKNESS:

-1: 0.175 ± 0.010 inch

-2: 0.130 ± 0.010 inch

PIERCING:

1: DEVICE OBVERSE: between wings, eagle's neck, and top of shield (2 internal piercings).

2: BASE OBVERSE: between annulet and supports (4 internal piercings).

DECORATION SET AND CASE: Decoration set shall consist of a regular size medal, a miniature size medal, and a service ribbon, all packaged in a presentation case conforming to MIL-C-14633, Type XV, Style 6, with a class 1 or 1A pad.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:55Z
Check the source to verify that this is the current version before use.

NOTES:

1: The term (REF) refers to the measurements taken from the Government furnished hub or die.

2: The specification slash sheet for the ribbon for the pendant drape and service ribbon is MIL-DTL-11589/545

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army – IH

Review activity:
DLA - CT

(Project No. 8455-2018-020)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:55Z
Check the source to verify that this is the current version before use.