NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/289D(IH)
26 September 2022
SUPERSEDING
MIL-DTL-3943/289C(IH)
25 March 2019

DETAIL SPECIFICATION SHEET


DECORATION, COMMENDATION MEDAL, U.S. BORDER PATROL

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE -DEVICE
(see piercing in notes)



OBVERSE -BASE
(see piercing in notes)



REVERSE



ASSEMBLED

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: DEVICE: (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:54Z
Check the source to verify that this is the current version before use.

FINISH:

DEVICE (-1 and -2): 24K Gold Plated, Matte Finished, Polished Highlights and shall match The Institute Heraldry (TIOH) Metal Finish Chip Number 8.

BASE OBVERSE (-1 and-2): Enameled or Epoxied, 24K Gold Plated, Matte Finished, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

BASE REVERSE (-1 and -2): 24K Gold Plated, Matte Finished, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:

DEVICE:

HEIGTH:

-1: 1-3/32 inches (REF)

-2: 17/32 inch (REF)

WIDTH:

-1: 1-1/32 inches (REF)

-2: 1/2 inch (REF)

THICKNESS:

-1: 0.090 inch ± 0.005 inch

-2: 0.070 ± 0.005 inch

BASE:

DIAMETER Overall excluding lug):

-1: 1-3/8 inches (REF)

-2: 11/16inch (REF)

THICKNESS (At lug):

-1: 0.105 ± 0.005 inch

-2: 0.080 ± 0.005 inch

ASSEMBLED THICKNESS:

-1: 0.175 ± 0.010 inch

-2: 0.130 ± 0.010 inch

DECORATION SET AND CASE: Decoration set shall consist of a regular size medal, a miniature size medal, and a service ribbon, all packaged in a presentation case conforming to MIL-DTL-14633, Type XV, Style 6, with a class 1 or 1A pad.

EPOXY: epoxied areas shall be as shown. Epoxy resin (stoning epoxy) may be at the option of the manufacturer. When hard enamel is used, the material requirement shall be gilding metal. When epoxy is used, the material requirement shall be either red brass or gilding material. Colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below:

TIOH ENAMEL COLOR CHIP NUMBER	LOCATION
Green #12	Obverse Outer ring

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:54Z
Check the source to verify that this is the current version before use.

NOTES:

1: The term (REF) refers to the measurements taken from the Government furnished hub or die.

2: The specification slash sheet for the ribbon for the pendant drape and service ribbon is MIL-DTL-11589/545.

3: The specification slash sheet for the lapel button is MIL-DTL-11484/427

PIERCING:

1: DEVICE OBVERSE (-1 and -2): between wings, eagle's neck, and top of shield (2 internal piercings).

2: BASE OBVERSE (-1 and -2): between annulet and supports (4 internal piercings).

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2022-279)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:54Z
Check the source to verify that this is the current version before use.