MILITARY SPECIFICATION

BATTERIES, NON-RECHARGEABLE, LITHIUM SULFUR DIOXIDE

This amendment forms a part of MIL-B-49430B(ER), dated 25 April 1988, and is approved for use within the Laboratory Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Para. 3.5.2 C: Delete "30 days" and substitute "45 days".

PAGE 6

Para. 3.5.5.2, delete and substitute:

"3.5.5.2 Diode. Diode(s) shall be inserted in the battery as specified in the applicable specification sheet to prevent significant reverse current (see 3.1). The diode shall meet requirement 30 of MIL-STD-454. The diode shall have the following characteristics:

Forward current, I_F= 3 amperes
Forward voltage drop, V_F = 0.65 volts maximum
Reverse current, I_R = 2 milliamperes
Reverse voltage, V_R = 40 volts

When the battery is tested to assure that the diode is functioning correctly the charging current shall not exceed 2.0 milliamperes maximum (see 4.8.10.3)."

PAGE 11

Para. 3.14.4, delete last paragraph and substitute:

"The card shall be placed on the battery, lettering side out, preferably over the face containing the connector. The word ATTENTION shall be in bold lettering."

AMSC N/A FSC 6135
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:05Z
Check the source to verify that this is the current version before use.

PAGE 29

Para. 4.8.10.3, delete and substitute:

"4.8.10.3 Diode breakdown test. A DC power supply capable of delivering at lease 2.50 ma. shall be used. The voltage to be used shall be 40, +0, -1 volts, plus the voltage obtained by multiplying the number of cells in series by 3.05. It shall be electrically connected with low impedance contacts to the connector terminals of series-connected cell strings of the battery to force reverse current flow (charging) through the individual cell string (i.e. positive to positive and negative to negative). This voltage shall be applied for a minimum of 1.0 second. This test shall be conducted immediately following the battery closed-circuit voltage test. The amount of current flowing shall not exceed the amount specified (see 3.5.5.2)."

Custodian:
Army-ER

Preparing Activity:
Army-ER

(Project 6135-A213)

Source: https://assist.dla.mil - Downloaded: 2026-10-22T20:05Z
Check the source to verify that this is the current version before use.