INCH-POUND
MIL-B-49436/1B(ER)
AMENDMENT 1
8 November 1994

MILITARY SPECIFICATION SHEET

BATTERY, RECHARGEABLE, SEALED NICKEL CADMIUM, BB-590/U

This amendment forms a part of MIL-B-49436/1B(ER), dated 10 December 1993, and is approved for use by the Army Research Laboratory, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Delete the following:

Discharge Rates	5 Second Voltage (V)	Final Voltage (V)	Current (Amps)
$9C_5$	-	20.0	18.0

Replace with the following:

Discharge Rates	5 Second Voltage (V)	Final Voltage (V)	Current (Amps)
$5C_5$ (12V)	-	10.0	20.0

Delete the following:

Test	Discharge Rate	Capacity Requirement (AH)
Pulse Discharge 18 amps, 5 seconds on, 25 seconds off, continuously to 20 volts	9 C_5	1.2

Replace with the following:

Test	Discharge Rate	Capacity Requirement (AH)
Pulse Discharge 20 amps, 5 seconds on, 25 seconds off, continuously to 10 volts in parallel operation	5 C_5	2.8

Custodian:
Army - ER

Preparing Activity:
Army - ER

Review activities:
Army - CR, AV, GL

(Project 6140-A801)

AMSC N/A 1 of 1 FSC 6140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.