METRIC

MIL-PRF-49434A (CR)
AMENDMENT 1
26 JUNE 2000

PERFORMANCE SPECIFICATION

AIMING LIGHT, INFRARED, AN/PAQ-4C

This amendment forms a part of MIL-PRF-49434A, dated 27 August 1997, and is approved for use by the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.2.1: Under STANDARDS: Delete “MIL-STD-461 Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference and MIL-STD-462 Electromagnetic Interference Characteristics” and substitute with “MIL-STD-461 Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems and Equipment”.

.

2.2.2: Under DRAWINGS: Delete list of drawings in its entirety and substitute:

“A3186948	- Optical Baffle Assembly
A3186949	- Bag, Textile
A3186950	- M-16 Mounting Bracket Assembly(M16A1/A2, M16/M203)
A3186951	- Case Assembly, Electronic Communication Equipment
A3186954	- Battery Cap Assembly
A3186958	- M4/M16A2 IAL Bracket Assembly
A3186976	- Thumbscrew Assembly
A3187000	- System, AN/PAQ-4C
A3187001	- Infrared Aiming Light Assembly
A3259265	- M16A2 IAL Bracket Assembly(USMC only)
A3259273	- Strapless Remote Switch Assembly
A3267739	- Training Extender Assembly(MILES)”

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

PAGE 4

3.6.4: Delete and substitute:

"3.6.4 M4/M16A2 Mounting Bracket Assembly. The M4/M16A2 mounting bracket assembly shall be in accordance with drawing A3186958."

Add as new paragraphs:

"3.6.4.1 US Marine Corps (USMC) M16A2 Mounting Bracket Assembly. The USMC M16A2 mounting bracket assembly shall be in accordance with drawing A3259265."

"3.6.4.2 MILES Compatibility. A training extender assembly (in accordance with drawing A3267739) shall provide compatibility with the Multiple Integrated Laser Engagement System (MILES)."

PAGE 7

3.7.11: Delete and substitute:

"3.7.11 Size. The external volume of the IAL with the optical baffle assembly (IAW drawing A3186948), battery cap assembly (IAW drawing A3186954), and thumbscrew assembly (IAW drawing A3186976) installed shall not exceed 7.2 in.."

PAGE 10

4.1b.: Delete and substitute:

"4.1b. Quality conformance inspections (4.2.2)"

4.2.1: Delete and substitute:

"4.2.1: FAT samples. A minimum of fifteen samples shall be selected from the first IAL production lot for FAT. Disposition of FAT samples shall be in accordance with the contract or purchase order (see 6.2.j)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.

PAGE 14

4.3.2.4: Delete and substitute:

"4.3.2.4 Group D inspection. Reliability testing shall be conducted on IALs selected from the units which have passed the tests in 4.3.2.1. Tests shall be conducted in accordance with Table VII and the contract or purchase order."

4.3.2.4.1: Delete and substitute:

"4.3.2.4.1 Sampling for reliability. The sample size shall be a minimum of 3 IALs."

PAGE 20

4.7 Substitute "MIL-STD-462" with "MIL-STD-461".

PAGE 21

6.2k: Delete paragraph 6.2k in its entirety.

6.4: Delete paragraph 6.4 in its entirety.

Custodian:
Army – CR

Preparing activity:
Army – CR
(Project 5855-0225)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:06Z
Check the source to verify that this is the current version before use.