NOT MEASUREMENT SENSITIVE


MIL-L-11484/108B
14 January 1994
SUPERSEDING
MIL-L-11484/108A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN EXECUTIVE RECOGNITION, NAVY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.



MATERIAL:
BASE: Gilding Metal
DEVICE: Red Brass

FINISH:
BASE: Hard Enameled, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

DEVICE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-17T16:44Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

BASE:

DIAMETER: 9/16 inch (1.43 cm) (REF)

THICKNESS (At Edge): 0.055 inch ± 0.005 inch (0.140 cm ± 0.012 cm)

DEVICE:

HEIGHT (Overall): 11/32 inch (0.87 cm) (REF)

WIDTH (Overall): 7/16 inch (1.11 cm) (REF)

THICKNESS (At Edge): 0.050 inch ± 0.005 inch (0.127 cm ± 0.012 cm)

ASSEMBLED THICKNESS (On Eagle's Breast): 0.105 inch ± 0.005 inch (0.267 cm ± 0.012 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The colors shall conform to the TIOH color chip numbers listed below or the standard sample.

COLOR	CHIP NO.
Red	1
Blue	20

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer.

4. The device shall be soft soldered to the base. When Epoxy resin is used, the device shall be attached to the base by rivets.

5. Attaching device shall be prong with pick and flat ball type clutch or pin and catch as specified. When a prong type attaching device is required, the prong shall be centered on the reverse side and fused or soldered to the lapel button. When a pin type attaching device is required, the device shall be located on the vertical center line of the button with the catch on the bottom.

Custodians:
Army - IH
Navy - NU

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:44Z
Check the source to verify that this is the current version before use.