MIL-C-10405/3A(EL)

18 September 1967

SUPERSEDING
MIL-C-10405/3(SigC)
2 April 1954

MILITARY SPECIFICATION

CRYSTAL UNIT DC-34

1. SCOPE

1.1 This specification covers the detail requirements of the crystal unit DC-34. These crystal units have a quartz vibrator pressure mounted in a plastic holder type HC-3/U, and are designed to operate at antiresonance, into a load capacitance of 30 pf, on the fundamental frequency of the vibrator, under noncontrolled temperature conditions, at a specified frequency within the frequency range of 1,690 to 4,440 kilohertz (KHz), Inclusive.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-10405 - Crystal Units, Quartz, Pressure and Spacer Mounted.

STANDARDS

MILITARY

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.

DRAWINGS

MILITARY

SC-D-20035 - Crystal Holder, HC-3/U, Assembly
SC-D-7627 - Crystal Units DC-34 & DC-35, Assembly and Marking Information.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements shall be in accordance with MIL-C-10405, and as specified herein.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Sampling and inspection shall be in accordance with MIL-C-10405, and as specified herein.

Table 1. Detail requirements

Requirement	Specified value or condition
Holder	HC-3/U (Per drawing SC-D-20035)
Dimensions	(Per drawing SC-D-20035)
Frequency range	1690 to 4440 KHz incl.
Frequency tolerance	±0.02 percent
Mode of oscillation	Fundamental
Load capacitance	30 ± 0.5 pf
Temperature range	-40 to + 70°C, incl.
Drive level, rated	See figure 2 of MIL-C-10405
Equivalent resistance	See figure 2 of MIL-C-10405.
Government reference standard test set	TS-330/TSM
Springs	Minimum force, 2 1/2 lbs.
Marking	Per drawing SC-D-7627.
Shock:	
Frequency change permitted	±0.002 percent or 50 cps, whichever is greater.
	The resistance shall not exceed those values shown in figure 2 of MIL-C-10405.
Vibration[1/]	
Frequency change permitted	±0.002 percent or 50 cps, whichever is greater.
	The resistance shall not exceed those values shown in figure 2 of MIL-C-10405.
Cleaning test	250 cps (See 3.13 of MIL-C-10405.

1/ Method 201 of MIL-STD-202, amplitude 0.06 inch total excursion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:01Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-C-10405.

6. NOTES

6.1 The notes specified in MIL-C-10405 are applicable to this specification.

Custodian:
Army - EL

Preparing Activity
Army - EL
Project Nr. 5955-A045

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:01Z
Check the source to verify that this is the current version before use.