MIL-C-10405/4A(EL)

18 September 1967

SUPERSEDING
MIL-C-10405/4(SigC)
2 April 1954

MILITARY SPECIFICATION

CRYSTAL UNIT DC-35

1. SCOPE

1.1 This specification covers the detail requirements of the crystal unit DC-35. These crystal units have a quartz vibrator pressure mounted in a plastic holder type HC-3/U, and are designed to operate at antiresonance, into a load capacitance of 96 pf, on the fundamental frequency of the vibrator, under noncontrolled temperature conditions, at a specified frequency within the frequency range of 2075 to 4055 kilohertz (KHz), inclusive.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-10405 - Crystal Units, Quartz, Pressure and Spacer Mounted.

STANDARDS

MILITARY

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.

DRAWINGS

MILITARY

SC-D-20035 - Crystal Holder, HC-3/U, Assembly
SC-D-7627 - Crystal Units DC-34 & DC-35, Assembly and Marking information.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:02Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Requirements shall be in accordance with MIL-C-10405, and as specified herein.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Sampling and inspection shall be in accordance with MIL-C-10405, and as specified herein.

Table 1. Detail requirements.

Requirements	Specified value or condition
Holder	HC-3/U (Per drawing SC-D-20035)
Dimensions	(Per drawing SC-D-20035)
Frequency range	2075 to 4055 KHz inc.
Frequency tolerance	±0.02 percent
Mode of oscillation	Fundamental
Load capacitance	96 ± 0.5 pf
Temperature range	-40 to + 70°C, incl.
Drive level, rated	See figure 3 of MIL-C-10405
Equivalent resistance	See figure 3 of MIL-C-10405
Government reference standard test set	TS-330/TSM
Springs	Minimum force, 2-1/2 lbs.
Marking	Per drawing SC-D-7627
Shock:	
Frequency change permitted	±0.002 percent or 50 cps, whichever is greater.
	The resistance shall not exceed those values shown in figure 3 of MIL-C-10405
Vibration [1/]	
Frequency change permitted	± 0.002 percent or 50 cps, whichever is greater.
	The resistance shall not exceed those values shown in figure 3 of MIL-C-10405.
Cleaning test	250 cps (See 3.13 of MIL-C-10405

[1/] Method 201 of MIL-STD-202, amplitude 0.06 inch total excursion.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T14:02Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-C-10405.

6. NOTES

6.1 The notes specified in MIL-C-10405 are applicable to this specification.

Custodians:
Army - EL

Preparing Activity
Army - EL
Project No. 5955-A046

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:02Z
Check the source to verify that this is the current version before use.