MIL-C-10405/9A(EL)
18 September 1967

SUPERSEDING
MIL-C-10405/9(SigC)
2 April 1954

MILITARY SPECIFICATION

CRYSTAL UNIT CR-13/U

1. SCOPE

1.1 This specification covers the detail requirements for the crystal unit CR-13/U. This crystal unit has a quartz vibrator spacer mounted in a metal holder, type HC-17/U, and is designed to operate at series resonance, on the fundamental frequency of the vibrator, under noncontrolled temperature conditions, at a specified frequency of 5,250 kilohertz (kHz).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-10405 - Crystal Units, Quartz, Pressure and Spacer Mounted.
MIL-H-10056/8 - Holder, Crystal, HC-17/U.

STANDARDS

MILITARY

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.

DRAWINGS

MILITARY

SC-D-17499 - Marking Instructions for Crystal Units.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:02Z
Check the source to verify that this is the current version before use.

Table 1. Detail requirements

Requirements	Specified values or conditions
Holder	HC-17/U (per MIL-H-10056/8)
Dimensions	(see MIL-H-10056/8)
Frequency range	5,250 kilohertz exclusive
Frequency tolerance	±0.02 percent
Mode of oscillation	Fundamental
Temperature range	-40°C to +70°C
Shunt capacitance	11 ± 1 pf (holder capacitance)
Drive level	30 ma at 5.25 mc with calibration resistance of 100 ohms.
Maximum resonance resistance	50 ohms
Government reference standard test set	TS-573/TSM
Springs	Coil type; minimum force 2½ lbs, (see 3.5.1 of MIL-C-10405)
Marking	Per drawing SC-D-17499; Method 1
Shock:	
Frequency change permitted	0.002 percent.
	The resistance shall not exceed 50 ohms.
Vibration 1/	
Frequench change permitted	0.002 percent.
	The resistance shall not exceed 50 ohms.

1/ Method 201 of MIL-STD-202, amplitude 0.06 inch total excursion.

3. REQUIREMENTS

3.1 Requirements shall be in accordance with MIL-C-10405 and as specified herein.

3.2 The value of C in the series arm of the equivalent network of the crystal unit shall fall between 0.015 to 0.030 pf when computed using the following equation:

$$C = \frac{2f(Co \pm Cl)}{f_s}$$

Where f = the difference in frequency in cps between the series resonance and antiresonance frequency.

f_s = nominal crystal frequency in cps at series resonance

Co = holder capacitance

Cl = capacitance which is put in series with the crystal unit when the series resonance - antiresonance switch is set at S. (See test set

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:02Z
Check the source to verify that this is the current version before use.

instructions for values of C1 to be used with above equation.) C1 and Co to be determined at room temperature.

The value of Co shall be measured at room temperature frequency below the fundamental frequency of the crystal plate ant at which the crystal shows no resonant response. There shall be no spurious responses having a series resonance resistance of less than 1,000 ohms within ±1 percent of the nominal frequency at room temperature.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection shall be in accordance with MIL-C-10405.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with MIL-C-10405.

6. NOTES

6.1 The notes specified in MIL-C-10405 are applicable to this specification.

CUSTODIANS:
Army - EL

PREPARING ACTIVITY
ARMY - EL

(Project 5955-A050)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:02Z
Check the source to verify that this is the current version before use.