MILITARY SPECIFICATION

LIGHTS, INSTRUMENT: FIRE CONTROL EQUIPMENT

This amendment forms a part of Military Specification MIL-L-10470D(MU), dated 24 October 1963.

Paragraph 2.1: Delete J-C-98 and title and substitute the following:

"MIL-STD-202 Test Methods for Electronic and Electrical Component Parts"

Add new paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2 as follows:

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) instrument lights plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as sued in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.5.3: Delete and substitute the following:

"4.5.3 Insulation resistance.- The instrument light shall be subjected to the insulation resistance test in accordance with Method 302 test condition B of MIL-STD-202, using a 500 volt dc megger. All points isolated from ground shall have at least 100 megohms insulation resistance. This test shall be performed on instrument light circuits and cable assembly. The test shall be performed on the instrument light with the lamp and batteries removed."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:05Z
Check the source to verify that this is the current version before use.

Add paragraph as follows:

"6.3 International standardization agreement.- Certain provisions of this specification are the subject of international standardization agreement, ABCA-Army-Std-46B. When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required."

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A231

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:05Z
Check the source to verify that this is the current version before use.