MIL-P-10476C(ER)
12 April 1984
SUPERSEDING
MIL-P-10476B(EL)
8 August 1973

MILITARY SPECIFICATION

PRINT WASHER, PHOTOGRAPHIC EK-1( )

This specification is approved for use within the Electronics Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of motor driven, revolving drum print washer designated as Print Washer, Photographic EK-1( ) (see 6.4).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

CC-M-1807	- Motor, Alternating Current, Fractional And Integral Horsepower (500 Hp And Smaller).
QQ-S-763	- Steel Bar, Wire, Shape, And Forging, Corrosion Resisting.

MILITARY

MIL-T-713	- Twine, Fibrous, Impregnated, Lacing And Tying.
MIL-I-3158	- Insulation Tape, Electrical Glass Fiber (Resin Filled), And Cord, Fibrous Glass.
MIL-P-11268	- Parts, Materials, And Processes Used In Electronic Equipment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Electronics Research and Development Command, ATTN: DELCS-PE, Fort Monmouth, New Jersey 07703 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6740

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

MIL-M-13231 - Marking of Electronic Items.
MIL-F-14072 - Finishes For Ground Electronic Equipment.
MIL-S-23190 - Straps Clamps, And Mounting Hardware, Plastic For Cable Harness Tying And Support.
MIL-E-55585 - Electronics Equipment And Parts, Packaging Of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-252 - Wired Equipment, Classification Of Visual And Mechanical Defects.
MIL-STD-454 - Standard General Requirements For Electronic Equipment.
MIL-STD-461 - Electromagnetic Emission And Susceptibility Requirements For The Control Of Electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement Of.
MIL-STD-726 - Packaging Requirements Code.
MIL-STD-810 - Environmental Test Methods.

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The print washer, photographic EK-1( ) (hereinafter called equipment) shall consist of a tank assembly, drum assembly, drum elevator, transmission, necessary piping and hardware as specified herein.

3.2 First article. When specified, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Parts, materials, and processes; general. In addition to the requirements of this specification, the requirements of MIL-P-11268, including the selection requirement therein, shall apply (see 4.4).

3.3.1 Recycled, virgin and reclaimed materials. It is required that, to the maximum extent possible, recovered or reclaimed materials, in lieu of virgin materials, shall be used without jeopardizing the intended use of the manufactured item.

3.3.2 Cleaning. The equipment shall be cleaned in accordance with MIL-STD-454, requirement 9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

3.4 Design.

3.4.1 Screws, other threaded devices, and related parts. Screws, other threaded devices, and related parts shall be in accordance with MIL-STD-454, requirement 12.

3.4.2 Soldering, welding, and brazing. Soldering, welding, and brazing shall be in accordance with MIL-STD-454, requirements 5, 13 and 59 respectively.

3.4.3 Wiring and cabling. Wiring and cabling shall be neat and sturdy.

3.4.3.1 Cabling. Insulated wires shall be formed into cables except where operation of the equipment would be adversely affected or where it is physically impracticable as in the case where the resulting cables would be excessively large and would interfere with operation or maintenance. The cabling of wires shall be effected by tape or twine conforming to MIL-T-713, or straps for cable harnessing conforming to MIL-S-23190; however, tape conforming to MIL-I-3158 shall be used where resistance to heat or chemicals is essential. Individual conductors thus secured shall lie essentially parallel; however, this does not prohibit the use of twisted pairs.

3.4.3.2 Slack. Wires and cables shall be as short as practical except that sufficient slack shall be provided for the following purposes:

a. To prevent undue stress on cable forms, wires, and connections to resiliently supported parts.
b. To enable parts to be removed and replaced during servicing without disconnecting other parts.
c. To provide for at least two replacements of the part to which the wire or cable is connected, except for certain radio frequency leads which must be as short as possible for electrical reasons.
d. To ensure freedom of motion of lugs or terminals normally intended to have some degree of movement.
e. To facilitate field repair of broken or cut wires.
f. To prevent chafing or breaking of individual wires due to repeated flexing or hinged parts.

3.4.3.3 Protection. Wires and cables shall be so placed and protected as to avoid contact, under specified service conditions, with rough or irregular surfaces or sharp edges. Wires shall not be bent sharply where they enter insulation materials. Where wires run through holes in metal partitions, shields, or similar items less than .125 inch (0.32cm) in thickness, the wires shall be protected by suitable grommets or bushings. Where wires run through holes in metal .125 inch (0.32cm) or greater in thickness, the wires shall be protected by grommets or bushings or shall have the edges in the holes rounded to a minimum radius of .06 inch (.15cm).

3.4.4 Operating power. The equipment shall be capable of operating from 115 volt ±10%, 60 Hertz ±5%, single phase alternating current.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

3.4.5 Electrical connections. Provision shall be included for necessary electrical connections from power supply source to suitable receptacle on washer.

3.5 Construction.

3.5.1 Frame. The metal frame shall rigidly support and position all parts of the equipment. All edges and corners shall be rounded to prevent injury to the operator.

3.5.2 Tank assembly. The tank assembly shall be rectangular in shape when viewed from above and shall have a semi-cylindrical bottom. The overall dimensions of the tank shall not exceed 31 inches (78.7cm) in length, 22 inches (55.9cm) in width, and 20 inches (50.8cm) in depth, and shall hold approximately 36 gallons (136.3 liters) of water. All seams shall be watertight and the upper edges of the tank shall be formed into reinforcing beads.

3.5.3 Piping. The water inlet shall terminate with a female threaded aspirator for attachment to a standard .50 inch (1.3cm) water supply pipe. A discharge pipe shall extend along the bottom of the tank and shall be formed and perforated to provide for an even discharge of water and air bubbles into the washing tank. The aspirator shall introduce a continuous supply of air bubbles into the wash water. A combined drain and overflow valve and fittings, provided with a 1.25 inch (3.2cm) hose connection and clamp for the drain, shall be provided. The inlet and drain shall be on the same side of the tank.

3.5.4 Drum assembly. The drum shall be 18 $\pm$2 inches (45.7 $\pm$5.1cm) in diameter and 27 $\pm$2 inches (68.6 $\pm$5.1cm) in length with its cylindrical and end surfaces perforated with holes .75 inch (1.9cm) in diameter on 1 inch (2.54cm) centers to provide for good water circulation. It shall be supported by stub axles fastened to the ends in such a manner that the drum will not rub on the tank during operation. A hinged locking door, 18 by 13 inches (45.7 by 33cm), shall be provided for loading and unloading the drum. Counterweights, where necessary to balance the weight of the door, shall be provided. The drum shall be capable of being removed from the tank without the use of tools. The drum as well as all parts of the tank assembly which are in continual contact with water shall be constructed of corrosion resisting steel conforming to QQ-S-763, class 304, condition A, or other suitable material of equivalent corrosion resistance, and shall not be painted or otherwise coated.

3.5.5 Drum elevator assembly. Means shall be provided for raising the drum 9 $\pm$2 inches (22.9 $\pm$5.1cm) to permit loading and unloading. It shall be operated by a foot pedal, conveniently located, which has a positive locking device to prevent the drum dropping accidentally during the loading and unloading. While in the raised position, the drum shall also be locked to prevent rotation.

3.5.6 Transmission assembly. The transmission shall consist of a pulley system and shall rotate the drum at a speed of 10 $\pm$2 revolutions per minute.

3.5.6.1 Motor. The motor shall be a constant speed electric motor conforming to CC-M-1807.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

3.6 Interchangeability. Like units, assemblies, subassemblies and replaceable parts shall be in accordance with MIL-STD-454, requirement 7.

3.7 Safety measures. The equipment shall be such that, when set up for operation, accidental contact between personnel and moving part such as belts will be prevented. Projecting and overhanging edges shall be held to a minimum. Edges and corners of inclosures shall be rounded.

3.8 Operational. Fifty each 8 by 10 inch (20.3 by 25.4cm) double weight prints shall be completely processed when tested as specified in 4.6.4. All washer parts shall operate freely and the prints shall not be scratched, corners broken or edges torn. A test for type traces shall be run on the back of the specified processed paper using Heico PW Residual Hypo Indicator (made by Heico Inc., Delaware Water Gap, PA 18327). After testing, the results should read "good" when matched to the tint patches shown in Kodak's Master Darkroom Data guide for black and white work.

3.9 Environmental.

3.9.1 Temperature. The equipment shall show no signs of damage, leakage, or operational degradation when stored in any ambient temperature from -60°F to 100°F (-51.1 to 37.8°C) and tested in accordance with 4.8.1 and 4.8.2.

3.9.2 Humidity. The equipment shall show no signs of damage, leakage or operational degradation when subjected to a relative humidity of 95 percent.

3.10 Breakdown voltage, insulation. The power cable, when connected to the unit, shall show no evidence of visible deterioration when tested in accordance with 4.9. After this test, the equipment shall meet all specified operational performance requirements of 3.8 and 3.11.

3.11 Lubrication. Provisions shall be made for lubricating all parts requiring lubrication. A visual check during operational testing shall be made to ensure no evidence of lubricant seepage in the washing compartment.

3.12 Electromagnetic interference characteristics. The equipment shall meet electromagnetic interference requirements specified in accordance with MIL-STD-461, class C3. If the contractor considers it desirable to modify the equipment proper in order to facilitate conformance to the specified test limits, he shall obtain approval from the contracting officer before proceeding with the modification.

3.13 Dimensions. The overall dimensions of the equipment shall not exceed 36 inches (91.4cm) in length, 36 inches (91.4cm) in height, and 23 inches (58.4cm) in width.

3.14 Weight. The weight of the equipment shall not exceed 155 pounds (70.3 kg).

3.15 Finish. Equipment shall be given protective finish in accordance with MIL-F-14072. This includes finish of hardware, such as handles, hinges, screws, etc., and necessary touchup after mounting. The final paint film on type I surfaces shall be final film E, semigloss, light gray enamel, in accordance with MIL-F-14072, table IA.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

3.16 Marking. Marking shall be in accordance with MIL-M-13231.

3.16.1 Visibility. Whenever practicable, parts shall be so mounted that their identification markings will be readily visible with minimum disassembly of the equipment.

3.16.2 Serial numbers. The equipment shall be serial numbered.

3.17 Workmanship. The equipment shall be manufactured and assembled in accordance with MIL-STD-454, requirement 9.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Inspections covered by subsidiary documents (see 4.4).
c. Quality conformance inspections (see 4.5).
d. Packaging inspection (see 4.12).

4.3 First article.

4.3.1 First article units. When required and as specified in the contract, the contractor shall furnish first article units of the complete equipment.

4.3.2 First article inspection. The first article inspection shall consist of the inspections specified in subsidiary documents covering the items listed in 4.4, and the inspections specified for group A, group B and group C (see tables I, II, III respectively). The inspection shall be performed in the following order: 4.4, group A and group B for al units; and group C as specified in table III. After completion of group C tests, conforming units shall be reinspected and shall pass all group A inspections.

4.4 Inspections covered by subsidiary documents. The following shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification, and the inspection requirement specified in the contract or purchase order.

Item	Where required
Material	3.3
Cabling	3.4.3.1
Motor	3.5.6.1
Finish	3.15
Marking	3.16

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection of equipment before packaging. The contractor shall perform the inspections specified in 4.4 and 4.5.1 through 4.5.4. This does not relieve the contractor of his responsibilites for performing any additional inspection which is necessary to assure compliance with all specification requirements.

4.5.1 Group A inspection. Each unit on contract or purchase order shall be inspected for conformance to the inspections specified in table I. Discrete lots shall be formed from units that pass inspection. Factors of lot composition not defined herein, or in the contract or purchase order, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105, using the general inspection levels, and AQLs indicated in table I.

TABLE I. Group A inspection.

Inspection	Requirement paragraph	Test method paragraph	AQL (percent defective)	
			Major	Minor
Visual and mechanical	3.17	4.11	1.5	6.5
Operational:				
Drum assembly	3.5.4	4.6.1	1.0	1/
Drum elevator assembly	3.5.5	4.6.2		
Transmission assembly	3.5.6	4.6.3		
Electrical:				
Breakdown voltage, insulation	3.10	4.9	1.0	1/

1/ Defects in all characteristics other than visual and mechanical are considered major.

4.5.1.1 Order of inspection. Group A inspection shall be performed in any order that is satisfactory to the Government.

4.5.2 Group B inspection. Group B inspection shall normally be performed on inspection lots that have passed group A inspection and on samples selected from units that have been subjected to and met the group A inspection. This inspection shall conform to table II and to the special inspection levels of MIL-STD-105, table I.

TABLE II. Group B inspection.

Inspection	Requirement paragraph	Test method paragraph	AQL (percent defective)
Interchangeability	3.6	4.7	6.5
Operational	3.8	4.6	6.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

4.5.2.1 Group B sampling plans. Group B AQL shall be 6.5 percent defective and the inspection level shall be S-4 for each inspection.

4.5.2.2 Order of inspection within group B. Group B inspection shall be performed in any order which is satisfactory to the Government.

4.5.3 Group C inspection. Group C inspection shall be performed on units that have passed group A and group B inspection. The inspection shall consist of the inspections specified in table III.

TABLE III. Group C inspection.

Inspection	Requirement paragraph	Test method paragraph
Temperature	3.9.1	4.8.1, 4.8.2
Humidity (moisture-resistance)	3.9.2	4.8.3
EMI characteristics	3.12	4.10

4.5.3.1 Sampling for inspection. Two sample units shall be selected at random for all inspections in table III from every 50 or fraction thereof produced. The first samples selected shall be at the start of the contract from the first quality conformance inspection production lot.

4.5.3.2 Order of inspection within Group C. Group C inspection shall be performed in any order which is satisfactory to the Government.

4.5.3.3 Group C failures. Actions required relative to group C failures shall be as specified (see 6.2).

4.5.4 Reinspection of conforming group B and C sample units. Unless otherwise specified, sample units which have been subject to and passed both group B and C inspection may be accepted on the contract provided all damage is repaired and the sample units are subject to and pass group A inspection.

4.6 Operational.

4.6.1 Drum assembly. The drum shall be removed and examined. Nonconformance to 3.5.4 shall constitute failure of this test.

4.6.2 Drum elevator assembly. The drum elevator assembly shall be tested to determine height of elevation, positive locking device and rotation prevention. Nonconformance to 3.5.5 shall constitute failure of this test.

4.6.3 Transmission assembly. The equipment shall be connected to the specified power source and the speed measured. Nonconformance to 3.4.4 and 3.5.6 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

4.6.4 Washing. The equipment shall be set up for operation; loaded with 50 each, 8 by 10 inch (20.3 by 25.4cm) double weight prints; operated for one hour, then drained, and filled again. The equipment shall be operated for another hour. During the above procedure, the following items shall be inspected:

a. All moving parts for overheating.
b. Tank and piping for leaks.
c. Operation of drain valve.
d. Operation of aspirator. Immediately following this test, the 8 by 10 inch (20.3 by 25.4cm) prints shall be inspected.
e. Lubrication checks.

Nonconformance to 3.5.2, 3.5.3, 3.8 or 3.11 shall constitute failure of this test.

4.7 Inspection for dimensional interchangeability. The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirement of 3.6. When tested dimension is not within specified or design limits, it shall be considered a major defect.

a. External and internal dimension of drum and tank, when such dimensions affect mating of parts.
b. External and internal dimensions of door and opening in drum.
c. Location of hinges and fasteners on separable parts or assemblies which must mate, such as cases, covers, and mountings.
d. Location of connectors, locking pins, fasteners, slides, and mountings which receive mating parts of plug-in assemblies and major units; and locations of the mating parts on the plug-in assembly or major unit.
e. Size and form of special threads.

4.8 Environmental.

4.8.1 Low temperature. The equipment shall be tested in accordance with MIL-STD-810, Method 502.1, Procedure I. The storage temperature shall be -60 (+0, -6)°F (-51.1 (+0,-3.3)°C) not to exceed 24 hours and the operating temperature shall be 40°F (4.4°C). Nonconformance to 3.9.1 shall constitute failure of this test.

4.8.2 High temperature. The equipment shall be tested in accordance with MIL-STD-810, Method 501.1, Procedure II. The storage temperature shall be 100 (+6,-0)°F (37.8(+3.3,-0 °C). Nonconformance to 3.9.1 shall constitute failure of this test.

4.8.3 Humidity (moisture-resistance). The equipment shall be tested in accordance with MIL-STD-810, Method 507.1, Procedure II. Nonconformance to 3.9.2 shall constitute failure of this test.

4.9 Breakdown voltage, insulation. The power cable electrical insulation shall be subjected to a breakdown voltage of 1230 volts rms for a duration of not less than 10 seconds. This voltage shall be applied, in turn, between each conductor and ground. If alternating current, the wave form shall be approximately sinusoidal and the frequency not greater than 100 Hertz. After testing, the equipment shall be subjected to the operational test specified in 4.6.4. Nonconformance to 3.10 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

4.10 Electromagnetic compatibility. The equipment shall be tested in accordance with MIL-STD-462, for electromagnetic compatibility. Nonconformance to 3.12 shall constitute failure of this test.

4.11 Visual and mechanical inspection. Equipment shall be examined for the defects listed in MIL-STD-252 and table IV.

TABLE IV. Classification of visual and mechanical defects.

Classification	Defect
Major	Sharp edges and corners not rounded on equipment proper. Seams not watertight. Drum not balanced to compensate for door. Unsuitability, improper fit, incorrect finish and imperfections of bolts, nuts, screws, washers, rivets, or other fastenings. Imperfections in general construction or improper finish of the washer. Incorrect, improper size, improper position of markings. Any foreign metallic or non-metallic object which could cause the equipment to be mechanically or electrically inoperative or unsafe. Mating parts do not fit or mate causing the equipment to be inoperative or unsafe. Improper soldering, wiring, insulation or terminals that would cause the equipment to be inoperative and unsafe.
Minor	All other defects which do not interfere with operation.

4.12 Packaging inspection. Packaging inspection requirements specified herein are classified as follows:

a. First article inspection of packaging.
b. Quality conformance inspection of packaging.

4.12.1 First article inspection of packaging. Unless otherwise specified in the contract, first article inspection of packaging shall be in accordance with the unit pack design validation requirements of MIL-P-116.

4.12.2 Quality conformance inspection of packaging.

4.12.2.1 Materials inspection. All materials to be used in packaging shall be inspected in accordance with the applicable material specification.

4.12.2.2 Preservation inspection. Inspection of preservation and interior markings shall be in accordance with group A and B quality conformance inspection requirements of MIL-P-116. Lot formation and samplings procedures shall be as specified therein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

4.12.2.3 Packing inspection. Inspection of packing and the marking for shipment and storage shall consist of the examinations specified in table V, "Packing inspection provisions." Lot f[illegible]ation shall consist of all packs made of the same materials during an identifiable period and submitted at one time for acceptance. Sampling procedures shall be in accordance with MIL-STD-105, using a single sampling plan and acceptable quality level of 4.0 percent defective.

TABLE V. Packing inspection provisions.

No.	Characteristic	Method of inspection
101	Intermediate container not as specified.	Visual
102	Improper closure of intermediate container.	Visual
103	Shipping containers not in accordance with specification.	Visual
104	Excessive cube.	Visual
105	Improper blocking and bracing.	Visual
106	Closure not in accordance with specification.	Visual
107	Weight and size exceed container limitations.	Weight & measure
108	Strapping not in accordance with specification, incorrectly applied, or omitted.	Visual
109	Marking omitted, incorrect, or illegible.	Visual

5. PACKAGING.

5.1 Preservation. Preservation shall be as specified in MIL-STD-726, coded as follows:

5.1.1 Level A. JR-1-1-ϕϕ-00-NS-X-ED-ϕ-00-A.

5.1.2 Level B. JR-1-1-ϕϕ-00-NS-X-ED-ϕ-00-B.

5.2 Packing and marking. Packing and marking shall be in accordance with MIL-E-55585.

6. NOTES

6.1 Intended use. Print Washer, Photographic EK-1( ) is motor driven and of the revolving perforated cylinder type for washing prints measuring not larger than 11 by 14 inches (27.9 by 35.6cm).

6.2 Ordering data. Acquisition documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

a. Title, number, and date of this specification.
b. When a first article is required for inspection and approval (see 3.2,4.3 and 6.3).
c. Action required relative to group C failures (see 4.5.3.3).
d. Level A or B preservation and packing (see section 5).
e. When first article inspection rough handling tests are not required.
f. When first article packaging inspection test reports require acquisition activity approval prior to production unit packing.

6.3 First article. When a first article inspection is required, the item will be tested and should be a first article sample. The first article should consist of units as specified in the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Nomenclature. The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example: EK-1W. The contractor should apply for nomenclature in accordance with the applicable clause in the contract (see 1.1).

6.5 Level B preservation. When level B preservation is specified, this level of protection will only be used under known favorable conditions during transportation, storage and handling.

6.6 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the change.

Custodian:
Army - ER

Preparing activity:
Army - ER

(Project 6740-A134)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND
COMBAT SURVEILLANCE AND TARGET ACQUISITION LABORATORY
ATTN: DELCS-PE
FORT MONMOUTH, NEW JERSEY 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-10476C(ER)	PRINT WASHER, PHOTOGRAPHIC EK-1( )

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR EDITION OF 1 OCT 76 IS OBSOLETE

Source: https://assist.dla.mil - Downloaded: 2026-10-17T14:06Z
Check the source to verify that this is the current version before use.