
METRIC

DOD-B-15072/14(SH)
2 September 1981
SUPERSEDING
DOD-B-15072/7B(SH) and
DOD-B-15072/8B(SH)
26 April 1976


MILITARY SPECIFICATION SHEET
BATTERY, STORAGE, LEAD-ACID, PORTABLE, TYPES
6V - 300 AH - L/D - A OR B AND 8V - 300 AH - L/D - A OR B (METRIC)

This specification sheet is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.


The complete requirements for acquiring the battery described herein shall consist of this document and the latest issue of DOD-B-15072.



6 VOLT



8 VOLT



TYPE ARRANGEMENT

SH11985

Military part number	Volts	Ah	Rate/discharge	Type	Dimensions			Final cut-off volts		
					L	W	H	10 Hour	2 Hour	5 Minute
M15072/14-001	6	300	Low/deep	A	515	252	248	5.25	4.8	3.6
M15072/14-002	8	300	Low/deep	A	683	254	273	7	6.4	4.8
M15072/14-003	6	300	Low/deep	B	515	254	248	5.25	4.8	3.6
M15072/14-004	8	300	Low/deep	B	683	252	273	7	6.4	4.8

Notes:

1. Dimensions are in millimeters (mm).
2. Unless otherwise specified, tolerances are plus or minus 3 mm.
3. Terminals shall be capable of receiving a round end lug accepting a 77 mm^2 or 100 mm^2 cable.

FSC 6140

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:29Z
Check the source to verify that this is the current version before use.

Requirements:

Electrolyte at 27°C: 1.265 specific gravity
Design and construction: See figure
Mass (filled): 55 kilograms (kg) maximum for 6 volts (V)
Mass (filled): 85 kg maximum for 8 V
Terminals: Posts with lugs
Rated capacities (at 1.220 specific gravity):
10-hour rate: 300 ampere-hours (Ah)
2-hour rate: 195 Ah
5-minute rate: 60 Ah
Discharge rates:
10-hour rate: 30 amperes (A)
2-hour rate: 97.5 A
5 minute rate: 720 A
Performance (at 1.265 specific gravity):
Cranking performance amps at minus 18°C: 1900 A
Reserve capacity minutes at 27°C: 590 minutes
Life test:

Requirements for completed batteries	
Over 80 percent rated capacity at rates	Minimum test value
97.5 A 720 A	500 cycles

Unit package: 1 battery
Shipping container: 2 unit packages
Arrangement: 1-2-1

Preparing activity:
Navy - SH
(Project 6140-N538)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:29Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATION

METRIC
DOD-B-15072/14(SH)
NOTICE 1
20 April 1989

MILITARY SPECIFICATION

BATTERIES, STORAGE, LEAD-ACID, PORTABLE, TYPES
6V - 300 AH - L/D - A OR B AND 8V - 300 AH - L/D - A OR B (METRIC)

DOD-B-15072/14(SH), dated 2 September 1981, has been reviewed and determined to be valid for use in acquisition.

Preparing activity:
Navy - SH

AMSC N/A
FSC 6140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:29Z
Check the source to verify that this is the current version before use.