MIL-C-40126F
29 July 1988
SUPERSEDING
MIL-C-40126E
7 December 1982

MILITARY SPECIFICATION

CUP, WATER CANTEEN (FOR INSULATED CANTEEN)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a corrosion-resisting steel canteen cup with folding handle (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-P-35	- Passivation Treatments for Corrosion-Resisting Steel
QQ-S-766	- Steel Plates, Sheets, and Strip - Corrosion Resisting
PPP-B-26	- Bag, Plastic, (General Purpose)
PPP-B-636	- Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-W-12332 - Welding, Resistance, Spot, Seam, and Projection; for Fabricating Assemblies of Low-Carbon Steel
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-9-160 - Cup, Water Canteen (For Insulated Canteen) Assembly, Complete
2-9-161 - Cup, Water Canteen (For Insulated Canteen) Details

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 580 - Stainless and Heat Resisting Steel Wire
D 3951 - Standard Practice for Commercial Packaging
E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Copies should be obtained from American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials. Materials and components shall be as specified herein and on Drawings 2-9-160 and 2-9-161, as applicable. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this document (see 6.4).

3.2.1 Steel, corrosion-resisting.

3.2.1.1 Sheet or strip. Corrosion-resisting steel sheet or strip shall conform to the requirements for any condition or temper of class 302 or 304 of QQ-S-766.

3.2.1.2 Sheet or strip, 1/4 hard. Corrosion-resisting steel sheet or strip, 1/4 hard, shall conform to the requirements for class 302, 1/4 hard of QQ-S-766.

* 3.2.2 Wire, steel, corrosion-resisting. The wire shall be stainless, furnished in straight lengths, condition A, round, type 302, 304, or 305 of ASTM A 580.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

* 3.3 Design and construction. The cup shall consist of a body, a folding handle with a sliding lock, and a hinge with a hinge pin. Spot or projection welds shall be used for attaching the hinge to the body. The cup shall be fabricated and assembled as shown on Drawings 2-9-160 and 2-9-161 and as specified herein. The sliding lock shall engage and disengage with the use of moderate force and shall hold the handle in an open position when tested as specified in 4.5.1.

* 3.3.1 Body, hinge, and sliding lock. The body, the hinge, and the sliding lock shall be fabricated from any of the corrosion-resisting steel sheet or strip specified in 3.2.1.1. After forming, the vertical walls of the body shall have a minimum hardness of 85 on the 15T Rockwell scale when tested as specified in 4.5.4.

3.3.2 Handle. The handle shall be fabricated from the corrosion-resisting steel sheet or strip specified in 3.2.1.2. The finished handle shall have a hardness of not less than C25 on the Rockwell scale when tested as specified in 4.5.2.

3.3.3 Hinge pin. The hinge pin shall be fabricated from any of the corrosion-resisting wire specified in 3.2.2.

* 3.3.4 Welds. The spot or projection weld for attaching the hinge shall be in accordance with MIL-W-12332. The welds shall be free of splatter, burn, holes, cracks or fractures, and discoloration and shall be tightly joined when tested as specified in 4.5.5 or 4.5.6. The indentation of the welds on the inside of the cup due to the welding of the hinge shall not exceed 0.005 inch in depth.

* 3.4 Finish. All components of the canteen cup shall be given a uniform lusterless finish approximating a commercial 2D sheet finish and passivated in accordance with QQ-P-35. There shall be no evidence of rust, staining, or spotting (slight water spotting, easily removed by washing, shall not be considered a defect) when tested as specified in 4.5.3.

* 3.5 Marking for identification. In addition to the US marking required by Drawing 2-9-161, the manufacturer shall permanently and legibly indent his name or trademark on the handle of each cup.

3.6 Workmanship. The finished cup shall be clean and free of stains, die marks, dents, burrs, sharp edges, scratches, slivers, pits, and deformities. Welding indentations on the inside of the cup due to welding of the hinge are acceptable providing the indentation is smooth and free from sharp edges, weld splatter, burrs, cracks, and burn through areas.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4 and tested for the characteristics specified in 4.5.1 through 4.5.6. The presence of any defect or failure to pass any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Inspection shall be made to determine that spot or projection welds are in compliance with 3.3.4. The spot or projection weld sample test shall be conducted on two test specimens per welding machine rather than sample cups. The spot or projection weld shall be performed as specified in 4.5.7 at the start of each day's shifts production. Failure of the test shall require correction of the welding process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of cups. The sample unit shall be one completely fabricated and assembled cup. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total major and minor combined defects.

TABLE I. End item visual examination

Examine	Defect	Classification	
		Major	Minor
Finish	Not a uniform, frosted, lusterless finish approximating a commercial 2D sheet finish		201
	Evidence of rust, staining, or spotting (slight water spotting, easily removed by washing shall not be considered a defect)		202
Design, construction, and workmanship	Not as specified (not in accordance with Drawings 2-9-160 and 2-9-161)	101	
	Component missing, broken, deformed, or not in proper alignment	102	
	Burr, draw mark, die mark, sharp edge, dent, scratch, sliver or pit		203
	Hinge pin loose (can be removed by hand)	103	
	Hinge not bent to fit contour of cup body		204
Welding (when applicable)	Contains crack or fracture	104	
	Not number specified	105	
	Not in proper location		205
	Contains burn hole, splatter, or discoloration	106	
	Evidence of poor fusion	107	
	Not smooth	108	
Marking	Missing, incomplete, illegible, misspelled, not indented, not in location specified		206

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions annotated with an asterisk on the drawings and as specified in 3.3.4. Any annotated dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of cups. The sample unit shall be one completely fabricated cup. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing . The end item shall be tested as specified in 4.5.1 through 4.5.6. Any test failure shall be classified as a defect. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number of intermediate containers is more or less than specified Number of cups per intermediate container is more or less than specified 1/

1/ For this defect one intermediate container shall be examined.

* 4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Lock operation test. Engage and disengage the sliding lock in the locking lugs. Then fill the cup, with the handle locked in the open position, with water to within 1/2 inch of the top. Then, raise by the handle not less than 6 inches and lower to the original starting position not less than 20 times in a period not exceeding 1 minute. Lock engaging or disengaging without the use of moderate force or any slippage of the lock shall constitute a test failure.

4.5.2 Hardness test. Test the handle in accordance with ASTM E 18 to determine compliance with hardness requirement of 3.3.2. Inability of the handle to meet the hardness requirements of 3.3.2 shall constitute a test failure.

4.5.3 Finish test. Expose the completely assembled cup to 95 to 100 percent relative humidity at 72° ± 2°F for not less than 16 hours to determine compliance with rust, staining, pitting, and spotting requirements of 3.4. Inability of the cup to withstand the requirements of 3.4 shall constitute a test failure.

* 4.5.4 Rockwell hardness. Test the Rockwell hardness of the vertical walls of the body of the cup in accordance with ASTM E 18. Take four Rockwell hardness readings on the vertical walls each 90 degrees apart around the cup and approximately half way between the top and the bottom of the cup. Any sample cup having one or more readings less than 85 on the Rockwell 15T scale as specified in 3.3.1 shall constitute a test failure.

4.5.5 Spot weld cup peel test. Place the cup in a jig or vise and peel the hinge from the cup. Inability of each weld to leave a 5/32 inch (minimum) hole in either the cup or hinge shall constitute a test failure.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:18Z
Check the source to verify that this is the currentversion before use.

4.5.6 Projection weld cup peel test. Separate the weldment of the cup and hinge by driving a chisel between welded components in an unwelded area or by peeling the hinge back against the weld until failure occurs. Failure outside the periphery of the weld area shall be considered evidence that the welds are satisfactory. Lack of fusion under the projection weld shall constitute a test failure. It is not necessary to pull buttons in this test provided that at least 3/4 of the area of each projection weld shows positive fusion.

4.5.7 Spot or projection weld peel test. Each spot or projection weld test specimen shall be of the type and thickness of the material in the cup body or hinge. Each specimen shall be spot or projection welded as specified in 3.3.4 in the locations shown on Drawing 2-9-161 and then placed in a jig or vise. Bend the parent metal piece and peel the hinge piece with pliers or other suitable tool. Inability of any spot weld to pull a 5/32 inch (minimum) hole in either piece of material shall constitute failure of this test. For projection welds, failure outside of the periphery of the weld area shall be considered evidence that the welds are satisfactory. Lack of fusion under the projection weld shall constitute failure of this test. It is not necessary to pull a button in this test, provided at least 3/4 of the area of each projection weld shows positive fusion.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

* 5.1.1 Level A. Five cups, each with handle in the closed position and the sliding lock positioned at the bottom of the cup, shall be nested one within another and then be intermediately packed in a flat (or square) style polyethylene bag conforming to type I or II of PPP-B-26. The minimum thickness of the polyethylene film shall be 0.003 inch. Each bag shall be closed in accordance with style 2 of PPP-B-26.

* 5.1.2 Commercial. The cups shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commerical as specified (see 6.2).

* 5.2.1 Level A packing. Fifty cups, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside dimensions of each shipping container shall be approximately 18-1/2 inches in length, 10-1/2 inches in width, and 14-1/2 inches in depth. Approximate dimensions are furnished as a guide only. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A intermediate packs shall be placed on their side with the cups on end, five in width and two in depth with a fiberboard pad between

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

the layers. The fiberboard pad shall extend the full length and width of the shipping container, minus one inch. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. Fifty cups, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. The inside dimensions of each shipping container shall be approximately 18-1/2 inches in length, 10-1/2 inches in width, and 14-1/2 inches in depth. Approximate dimensions are furnished as a guide only. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A intermediate packs shall be placed on their side with the cups on end, five in width and two in depth with a fiberboard pad between the layers. The pad shall extend the full length and width of the shipping container, minus one inch. Closure shall be in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

* 5.2.3 Commercial. Cups, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

* 5.3 Palletization. When specified (see 6.2), cups, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 26 in accordance with MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, intermediate packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable. Polyethylene bagged intermediate packs shall have the required information printed or stamped directly on the bag or on a paper label inserted within the bag so as to permit ready identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The cup is intended for use with the insulated steel canteen covered by MIL-C-40124.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.5 Subject term (key word) listing.

Canteen
Corrosion-resisting steel
Cup
Insulated
Water

6.6 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT

User activities:

Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0981

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY LEFT BLANK

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-40126F	Cup, Water Canteen (For Insulated Canteen)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATIONAL STOCK NO. 7540-01-317-9744

Source: https://assist.dla.mil -- Downloaded: 2020-10-21T19:18Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:18Z
Check the source to verify that this is the current version before use.