MIL-C-40131C
15 September 1986
SUPERSEDING
MIL-C-40131B
11 June 1968

MILITARY SPECIFICATION

COVER, WATER CANTEEN, INSULATED, COTTON DUCK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of canteen cover fabricated of Olive Drab cotton duck, tape, and webbing and attached hardware.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203	- Paper, Kraft, Untreated
V-T-285	- Thread, Polyester

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-Yarns Army and Numbered
CCC-D-950	- Dyeing and Aftertreating Processes for Cotton Cloths
DDD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-H-9890	- Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-F-10884	- Fasteners, Snap
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-C-40124	- Canteen, Water, Insulated, Corrosion-Resisting Steel Without Cup and Cover
MIL-C-40126	- Cup, Water Canteen (for Insulated Canteen)
MIL-T-43566	- Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-2-211	- Cover, Water Canteen, Insulated, Cotton Duck

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Standard sample. The cotton duck cloth shall match the standard sample for shade and shall be equal to or better than the standard sample with respect to all characteristics for which the standard sample is referenced (see 6.3).

3.1.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

* 3.2 Materials. Recycled material may be used (see 6.5).

3.2.1 Cloth, duck, cotton. The cloth, before finishing, shall be No. 6, hard texture, conforming to type I of CCC-C-419.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

3.2.1.1 Color and treatment. The cloth shall be dyed Olive Drab 7 to match the standard sample (see 6.3) and shall conform to type I, class B of CCC-D-950.

3.2.2 Tape, cotton. The tape shall be dyed Olive Drab 7 to match the standard sample (see 6.3) and shall conform to type I, class 4, 3/4 inch width of MIL-T-43566.

3.2.3 Webbing, cotton. The webbing shall be dyed Olive Drab 7 to match the standard sample (see 6.3) and shall conform to type IIb, class 4, 2 1/4 inch width of MIL-W-530.

3.2.4 Thread, polyester. The polyester thread shall be type I, class 1, subclass B of V-T-285. The thread sizes shall be as follows:

a. For all stitching, except binding and overedge stitching, use size FF.
b. For binding and overedge stitching, use size E.

3.2.4.1 Color. The thread shall be dyed shade S-1 (Cable No. 66022) and shall show fastness to chlorine bleaching equal to or better than the standard sample (see 6.3). If no standard sample is available, the thread shall show "good" fastness to chlorine bleaching.

3.2.5 Fasteners, snap. The snap fasteners shall conform to style 2, finish 2 of MIL-F-10884. The female components shall be socket and size 1 or 2, 24-line button, and the male components shall be stud and size 1 or 2 eyelet.

3.2.6 Keepers, with slide. The keepers shall be steel, black in color, and shall conform to type X of MIL-H-9890.

3.3 Construction. The construction shall conform in all respects to Drawing 2-2-211 and as specified herein.

3.3.1 Stitches, seams, and stitchings.

3.3.1.1 Type of stitching. All stitching shall conform to FED-STD-751, as follows:

a. For all stitching except overedge stitching on reinforcement - Type 301, 6 to 8 stitches per inch.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:19Z
Check the source to verify that this is the currentversion before use.

b. For overedge stitching on reinforcement - Type 304, 10 to 14 stitches per inch; or type 502 or 503, 6 to 10 stitches per inch.

3.3.1.1.1 Automatic stitching. Any of the stitching operations cited in this document may be performed with an automatic machine provided that the requirements for stitch pattern, stitches per inch, size and types of thread are met, and that at least three tying, overlapping, or back stitches are used to secure the ends of stitching.

3.3.1.1.2 Lubrication of thread. There shall be no lubrication of the thread prior to or during sewing (see 4.4.1.1).

3.3.1.1.3 Type 301 stitching. Thread breaks in stitching shall be overstitched not less than 1 inch back of the break. Ends of all stitching shall be backstitched or backtacked not less than 1 inch except where ends are caught in other seams and stitching. Thread tensions shall be maintained so that there will be no loose or tight stitching and the lock will be embedded in the sewn materials.

3.3.1.1.4 Overedge stitching. Thread breaks and overedge stitching shall be overstitched not less than 3/4 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.3.1.2 Trimming. All thread ends shall be trimmed.

3.3.2 Setting of the metallic snap fasteners. Holes punched before inserting the male or female part of the fasteners shall be smaller than the outside diameter of the fastener tubes so that the tubes must be forced through the holes. The fasteners shall be securely clinched without cutting the material.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 2-2-211 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size of characters and in the location indicated on Drawing 2-2-211 and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.5 Workmanship. The covers shall conform to the quality of product established by this document, and the occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in table I and table II. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirement specified in 3.3.1.1.2.

4.4.2 In-process inspection. Inspection shall be made at any phase of the manufacturing process to determine whether cut lengths, cut parts, fabricated parts before assembly, and marking for location of components are in accordance with specified requirements for dimensions and that operations and assemblies are accomplished as specified. In addition, inspection shall be made during the manufacturing process to ensure that holes for receiving hardware are prepunched smaller than the outside diameter of the tube. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of water canteen covers. The sample unit shall be one completely fabricated cover. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects, 6.5 for combined major and minor A defects, and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification	
		Major	Minor A B
Cloth, duck	Any hole, cut or tear, smash, broken or missing yarns, or open place clearly visible at normal inspection distance (approximately 3 feet)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Webbing and tape	Any hole, cut, tear, smash, broken end, or pick	X		
	Not firmly and tightly woven; edge frayed or scalloped	X		
	Abrasion mark		X	
Hardware	Broken or malformed, failing to serve intended purpose; corroded area, burr, or sharp edge	X		
	Finish omitted or not as specified	X		
	Finish defects (i.e., objectionable orange peel, wrinkle, drop, streak, thin film, or no film)	X		
	Not attached or assembled as specified	X		
	Misplaced, failing to serve intended purpose	X		
Snap fastener	Not functioning properly, failing to effect a secure closure or to open freely	X		
Keeper	Slide portion of keeper jams, failing to effect a secure closure	X		
Seams and stitching				
Open seams	More than 1 inch	X		
	More than 1/2 inch, but not more than 1 inch		X	
	1/2 inch or less			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued				
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more skipped stitches or run-offs occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.			
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching		X	
NOTE:	Raw edges not securely caught in stitching shall be classified as open seams.			
Run-off (see open seams)				
Seam and stitch type	Wrong seam or stitch type	X		
Stitch tension	Loose, resulting in a loosely exposed bobbin or top thread; tight, resulting in excessive puckering of fabric on seam			X
Stitches per inch	One stitch less than minimum specified			X
	Two or more stitches less than minimum specified		X	
	One or more stitches in excess of maximum specified			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued				
NOTE:	Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy places or heavy seams, or in turning corners shall be classified as follows: a. Within the minor B defect classification - no defect. b. Within the minor A defect classification - minor B defect.			
Stitching margins or stitching gage	Not as specified		X	
End of stitching (not held down by other stitching or turned under in a hem)	Not backstitched or secured	X		
	Backstitched less than 1 inch		X	
Thread breaks	Backstitched less than 1 inch (type 301)			X
	Overstitched less than 3/4 inch (overedge stitching)			X
NOTE:	Thread break not backstitched or overstitched shall be classified as an open seam.			
Stitching	One or more rows of required stitching omitted (except on box stitching)	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects - Continued

Examine	Defect	Classification		
		Major	Minor A	Minor B
Seams and stitching - continued				
Box stitching	Two or more rows of stitching omitted	X		
	One row of stitching omitted			X
Components and assembly	Any component part or required operation omitted or not as specified (unless otherwise classified herein)	X		
	Needle chews	X		
	Mend or darn	X		
Binding	Improperly or loosely applied, badly puckered			X
Reinforcements "B" and "C"	Exposed edge of reinforcements not selvage edge or not turned under		X	
Reinforcement "D"	Cut ends of webbing not overedge stitched	X		
Cleanness	Grease or oil stains clearly noticeable, thread ends not trimmed throughout			X
Marking	Omitted, illegible, incorrect, or misplaced		X	

* 4.4.4 End item dimensional examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of water canteen covers. The sample unit shall be one completely fabricated

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

cover. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.0 for major defects and 10.0 for total (major and minor combined) defects.

TABLE II. End item dimensional defects

Examine	Defect	Classification	
		Major	Minor
Location and component dimensions	Not within specified tolerance		X
Finished dimensions			
Height (back)	Less than 7 1/8 inches	X	
	Less than 7 3/8 inches, but not less than 7 1/8 inches		X
	More than 7 7/8 inches		X
Bottom (length)	Less than 5 inches	X	
	Less than 5 1/4 inches, but not less than 5 inches		X
	More than 5 3/4 inches		X
Bottom (width)	Less than 2 inches	X	
	Less than 2 1/8 inches, but not less than 2 inches		X
	More than 2 3/8 inches		X
Fit of canteen and cup in cover	NOTE: Fit examination shall be performed with a standard insulated canteen manufactured in accordance with MIL-C-40124 and with a standard cup manufactured in accordance with MIL-C-40126 (see 6.3). The assembled canteen and cup shall be inserted into the cover. To determine whether canteen and cup fit in cover, ease canteen into cover without effort and close flaps by snapping fasteners in a closed position.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects - Continued

Examine	Defect	Classification	
		Major	Minor
Fit of canteen and cup in cover-continued	Cover too small (i.e., assembled canteen and cup fail to fit in cover)	X	
	Flaps too short, causing failure of snap fastener to effect a smooth and secure closure	X	
	Flap wrinkled or puckered, does not hug body of canteen cover when snapped closed		X

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling
	Bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

Examine	Defect
Content	Number of covers per bundle is more or less than specified 1/ Number of bundles per shipping container is more or less than specified

1/ For this defect, three bundles from each shipping container in the sample shall be examined.

* 4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each canteen cover, with flaps snap fastened in place and keepers closed, shall be folded down flat so that the cover measures approximately 8 by 7 1/2 inches. Five canteen covers shall be stacked in a bundle with "US" facing up and alternated top to bottom. Each bundle shall then be securely cross-tied with cotton tape or twine.

* 5.1.2 Commercial. Canteen covers shall be preserved in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. One hundred and fifty canteen covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Level A unit packs shall be packed on edge, alternated top to bottom, three in length, five in width, and two in depth within a shipping container. Inside dimensions of the shipping container shall be approximately 24 1/2 inches in length, 17 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.2.2 Level B packing. One hundred and fifty canteen covers, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed on edge, alternated top to bottom, three in length, five in width, and two in depth within a shipping container. Inside dimensions of the shipping container shall be approximately 24 1/2 inches in length, 17 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.5.

* 5.2.3 Commercial packing. Canteen covers, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

* 5.3 Palletization. When specified (see 6.2), covers, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 3 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The canteen cover is designed to serve as a suitable carrier for the steel insulated water canteen and cup.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1.2, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

* 6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

* 6.6 Subject term (key word) listing.

Carrier, water canteen
Cover, water canteen

6.7 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8465-0927

Review activities:

Army - MD
Air Force - 82
DLA-CT

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:19Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T19:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-40131C	Cover, Water Canteen, Insulated, Cotton Duck

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OF 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 20261O-21T19:19Z
Check the source to verify that this is the current version before use.