INCH-POUND

MIL-C-40153L
AMENDMENT
31 March 1994

MILITARY SPECIFICATION

CLOTHING REPAIR SHOP, TRAILER MOUNTED

This amendment forms a part of mL-c-40153L, dated 30 September 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under "SPECIFICATIONS, FEDERAL": Delete "A-A-50470", "RR-I-660", and "PPP-C-843" and their titles.

Under "SPECIFICATIONS, FEDERAL": Add the following:

" A-A-297 - Ironing Board, Household
A-A-1805 - cover, Ironing Board
A-A-1806 - Pad, Ironing Board
A-A-1898 - Cushioning Material, Cellulosic, Packaging
A-A-50473 - Oilers , Hard, Push-Button
PPP-B-26 - Bag, Plastic (General Purpose)
PPP-F-320 - Fiberboard: Corrugated and Solid, sheet Stock (container Grade), and Cut Shapes"

Under "SPECIFICATIONS , MILITARY" : Delete "MIL-B-117" and it's title.

Add the following: "MXL-T-10579 - Trailers, Cargo: 2 wheel, 1/4 Ton to 1-1/2 Ton"

PAGE 9

3.4.6: Delete and substitute:

"3.4.6 Ironing board, pad, and cover. The ironing board shall conform to A-A-297 , except the top dimensions shall be 27 f 1/4 by 7 ~ 1/4 inches overall, and the stand shall not be adjustable and shall be suitable for mount ing on a folding table, per Drawing 6-1-1117. The pad shall conform to A-A-1806 and be suitable for mounting on the ironing board. The cover shall conf orm to class B of A-A-1805 and be suitable for covering the ironing board with the pad mounted. "

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:21Z
Check the source to verify that this is the current version before use.

PAGE 10

3.4.9, TABLE III:

Item 1: After "1/4-inch", Add: “or V-belt, rubber, 3L"

Item 3: Delete “Description” and substitute:

“Oiler, hand, push bottom, steel, 4-inch straight spout, polished copy clear lacquer or varnish, 1/2 pint, class A per A-A-50473'

Item 8: Delete “Description” and subtitute:

“Screwdriver, Flat Tip, Plastic Handle, 9/64 by 2-inch blade, type I, class 8, style 1 or 2 of GGG-D-121'

Item 11 and Item 12: Delete “brass, chrome plated, closed, ” and substitute “solid nickle silver, closed, ”

PAGE 13

4.4.1.1: Delete and substitute:

“4.4.1.1 component testing. The electrical and mechani“cal components of each product end item shall be tested for proper operation. The operational test is a test of the equipment and electric distribution system. It may be done independently of the cabinet f abdication. Upon successful compliance, each equipment group and electrical distribution system shall be tagged inspected, and may be preservation packaged. Failure to pass these tests shall be cause for rejection of the equipment and distribution system. ”

Add the f ollowing new paragraphs:

4.4.1 .1.1 Power and disribution box assenblies. Each conductor of the power box and distribution box assemblies shall be checked for proper continuity. In addition each conductor in the cable will be checked for insulation resistance from that conductor to every other conductor. The insulation resistance shall not be less than 1 mega ohm when tested at a voltage of not less than 500 volts direct current (VDC).

4.4.1 .1.2 Electrical extension light. Each light shall be checked for operation by plugging in the light to a standard 110 volt (V) socket.

4.4.1 .1.3 Clothing sewing machine assembly Each clothing sewing machine shall be subjected to the examination and test paragraphs as specified in 00-S-256 /GEN. Conformance to the requirements of stitch type 301, class 3 machine of 00-S-256/1 shall be verified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

4.4.1.1.4 DARNING SEWING machine assembly. Each darning sewing machine shall be subjected to the examination and test paragraphs as specified in 00-S-256/GEN. Conformance to the requirements of class 3 machine of 00-S-256/3 shall be verified.

4 .4.1.1.5 Button sewing machine assemblies. Each button sewing machine shall be subjected to the examination and test paragraphs as specified in 00-S-256/GEN, except that the operational test shall be as described in the "test" paragraph of 00-S-256/8. Conformance to the requirements of class 1 button machine shall be verified "

PAGE 14

4.4.5, last sentence: Delete and substitute:

"The inspection level shall be S-2. The finding of any defect shall be cause for the rejection of the lot."

PAGE 15

4.5.3, e.: Delete and substitute:

"e. The generator shall be started and adjusted for 120/208 volts, 60 cycles, 3 phase electrical output. "

1.: Delete and substitute:

"l. Using the data recorded above, the electrical load on each phase shall be in compliance witht the requirement in 3.5.3. "

PAGE 16

5.1.1.2, lines 8 and 9: Delete "type 1, class B of PPP-C-843' and substitute "grade II, class B of A-A-1898, or type CF, class domestic, variety SW, grade 175 of PPP-F-320'.

Line 10: Delete "cord or twine" and substitute "cord, twine or tape" l

Line 13: Delete "type 1, class E of MIL-B- 117" and substitute "style 1 or 3 of PPP-B-26".

5.1.1.3, line 7: Delete "IA-14 of MIL-P-116' and substitute "IA-15 of MIL-P-116' .

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T19:21Z
Check the source to verify that this is the currentversion before use.

MILITARY INTERESTS:

Custodians :

Army - GL
Air **Force - 99**

Review activities:

Army - TR
Air Force - 84
DLA - GS

User activity:

Navy - MC

Preparing activity:

Army - GL

(Project 3530-0097)

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:21Z
Check the source to verify that this is the current version before use.