MILITARY SPECIFICATION

LOADING STANDARDS, LIQUID TRANSFER, BULK: PORTABLE, 2-INCH

This specification is approved for use by the USA Belvoir Research and Development Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of portable loading standards for bulk liquid transfer.

1.2 Classification. The loading standards shall be the following types, as specified (see 6.2 and 6.7):

Type II	- Loading Standard, Liquid Transfer, Bulk: Fuels Portable, 2-inch.
Type III	- Loading Standards, Liquid Transfer, Bulk: Potable Water Portable, 2-inch.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

W-C-440	- Clips, Electrical, General Specification for.
QQ-S-781	- Strapping, Steel and Seals.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research and Development Center, ATTN: STRBE-DS, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3990

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-T-97 - Tape, Pressure-Sensitive Adhesive, Filament Reinforced.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.
MIL-T-704 - Treatment and Painting of Materiel.
MIL-F-3541 - Fittings, Lubrication.
MIL-G-3859 - Grease Guns, Hand Operated, Lever, Push and Screw Type.
MIL-A-3962 - Anchor Ground, Arrowhead with Driving Equipment.
MIL-A-8625 - Anodic Coatings, for Aluminum and Aluminum Alloys.
MIL-G-10924 - Grease, Automotive and Artillery.
MIL-P-15024/6 - Plates, Identification, Equipment.
MIL-G-20241 - Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-A-22895 - Adhesive, Metal Identification Plate.
MIL-G-23827 - Grease, Aircraft and Instrument, Gear, and Actuator Screw.
MIL-S-81733 - Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

TA13226E2190 - Loading Standard, Liquid Transfer, Bulk: Fuels, Portable, 2-Inch, Type II.
TA13225E9160 - Loading Standard, Liquid Transfer, Bulk: Potable Water, Portable 2-Inch, Type III.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/ASME - Boiler and Pressure Vessel Code, Section IX, Welding and Brazing Qualification.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

AMERICAN WELDING SOCIETY (AWS)

B3.0 - Standard Qualification Procedure.

(Application for copies should be addressed to the American Welding Society, United Engineering Center, 345 East 47th Street, New York, NY 10017).

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The loading standards shall be as shown in accordance with TA13226E2190 for type II and TA13225E9160 for type III and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the loading standard. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Materials. Materials shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The loading standards shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the loading standards may be newly fabricated from recovered materials to the maximum extent practicable, provided the loading standards produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the loading standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

3.4 Safety.

3.4.1 Static electricity protection. With the loading standard fully erected and ready for operation, and the cable from the grounding reel extended to its full length, there shall be not more than 3 ohms resistance between the tip of the drop tube and the grounding cable attachment clip.

3.4.2 Electric conductivity. Where electric conductivity for static grounding is required, protective coatings and any materials with insulating properties shall be removed from between contacting parts. The flange type coupling, swing joint, and loading arm assembly shall be provided with graphitized packing and gaskets, sliding brushes, or other positive means of insuring the electrical conductivity required.

3.4.2.1 Support bracket. The area of the support bracket which comes in contact with the grounding reel shall not be painted or anodized to insure a positive ground.

3.5 Working pressure. Each loading standard shall dispense fuel at a working pressure of 100 pounds per square inch gage (psig). The portion of the loading standards between the fuel inlet and the loading valve shall withstand a hydrostatic proof pressure of 150 psig, for not less than 2 minutes, without leakage or permanent deformation or other defects that could harmfully affect the performance and serviceability of the loading standards.

3.6 Components.

3.6.1 Loading arm assembly. The loading arm assembly shall be a commercial type equipped with O-ring seals having the following operational characteristics:

a. Swing freely through 360 degrees in a horizontal plane.
b. Swing freely through a vertical arc from not less than 30 degrees below to 70 degrees above the horizontal plane.
c. When manually lowered to the loading position, the loading arm shall automatically remain in that position during loading. When released from loading position, the loading arm shall return to its original position by mechanical means other than counterweight.
d. When swung through its vertical arc, the drop tube shall hang in a vertical position by its own weight.

3.6.2 Loading valve. The loading valve shall be a lever operated, self-closing type, of such construction as to assure a smooth shockproof closure. A vacuum breaker shall be mounted on the discharge end of the valve. The valve shall not leak or show any indication of failure when subjected to a hydrostatic proof pressure of 150 psig, for not less than 2 minutes.

3.6.3 Sliding tube assembly. The sliding tube assembly shall be as shown on the applicable drawing. The outer tube shall be fabricated from aluminum. The inner tube shall be aluminum or stainless steel, and shall be fully guided from the closed to the maximum extended position. The outer tube shall have a

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

stuffing box with a packing compatible with petroleum fuels. The stuffing box shall be equipped with a packing gland and a lugged and threaded take-up ring for adjustment. The sliding tube assembly including the drop tube, single swing joint, and the outside tube stuffing box, shall not leak when subjected to a 25 psig hydrostatic pressure for 5 minutes.

3.6.4 Double swing joint. The double swing joint shall be equipped with double rows of ball bearings for each rotative direction. The bearings shall be sealed to prevent leakage and entry of fuels into the bearing cavities, and shall be provided with lubrication fittings specified in 3.7.1.

3.6.5 Drop tube. The drop tube shall be as shown on the applicable drawing. The drop tube, when specified (see 6.2), shall be 6 feet in length and provided with a tee deflector fitting equal to Dover Corporation part number OPW 464 Deflector.

3.6.6 Grounding reel. The grounding reel shall be a commercial enclosed type as shown on the applicable drawing and shall have the following characteristics and component parts:

a. Steel cable 3/32-inch galvanized. The cable shall terminate in an electrical power clip with lug conforming to W-C-440, type PCL, nominal current rating 100 amperes.
b. Automatic rewind for cable.
c. Provisions for vertical mounting on the support bracket.
d. Ratchet device to latch the cable at intervals.
e. Instruction plate specified in 3.8.1.

3.6.7 Component weight. Any component of the loading standard that weighs in excess of 37 pounds shall be labelled "_____ person lift", depending on the number of personnel necessary to lift the component, using 37 pounds per person as the determining factor.

3.6.8 Threaded fasteners. Threaded fasteners shall conform to FED-STD-H28. Captive fasteners shall be used wherever practicable.

3.7 Lubrication. All surfaces requiring lubrication shall be provided with means for lubrication.

3.7.1 Lubrication fittings. Lubrication fittings shall conform to MIL-F-3541, type I or III as applicable. Fittings shall be located in a protected position and shall be accessible to a grease gun conforming to MIL-G-3859 without removal or adjustment of accessories or parts. Fittings shall incorporate provisions for release of excess lubricant to the atmosphere.

3.7.2 Lubricant. Grease lubrication, including lubrication of sealed bearings, shall be with standard military thermally stable grease conforming to MIL-G-10924 or MIL-G-23827 as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

3.8 Identification marking. The loading standards shall be identified in accordance with MIL-STD-130. The marking shall be applied to the loading standards on plates conforming to MIL-P-15024/6. Plates shall be attached by screws, bolts, or rivets to the riser support and located approximately 24 inches up from the support base assembly.

3.8.1 Instruction plates. The loading standards shall be equipped with instruction plates suitably located, describing any special or important procedure to be followed in operating and servicing the loading standards. Instruction plates shall conform to MIL-P-514, type III, composition C, of type I, grade A, class 1, material thickness .008 to .012; black background with aluminum lettering. Adhesive for bonding the plates to the equipment shall be in accordance with MIL-A-22895, class B. One plate shall be located at the grounding reel in a conspicuous location. This plate shall give the following warning: "Copper grounding clip must be attached to the truck prior to starting loading operations".

3.9 Treatment and painting. The portions of the loading standards normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type A.

3.9.1 Anodic coating. The loading standards and component parts, fabricated from aluminum alloy, when not painted, shall be anodized in accordance with MIL-A-8625, type II, class 2, thickness 0.0007 inch. Color shall be specified (see 6.2).

3.10 Interchangeability. All identical components of each type loading standard, except support assemblies, shall be interchangeable.

3.11 Types.

3.11.1 Type III. The type III loading standard shall be in accordance with top assembly TA13225E9160, and as specified herein.

3.11.2 Type II. The type II loading standard shall be in accordance with top assembly TA13226E2190, and as specified herein. The loading standard shall be equipped with four cable supports, with the two short cables for forward support and the two longer cables for rearward support.

3.11.2.1 Government-furnished property. The following anchors and driving equipment, in the quantities indicated, shall be furnished for each type II loading standard, and shall be inclusive of anchors and driving equipment specified on the drawings; and unless otherwise specified (see 6.2), will be Government-furnished property (see 6.4).

Item No.	Description	Specification	Qty of each
1	Anchors, ground, arrowhead	MIL-A-3962, size 4 inch (102 mm), grade B, style 5	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

Item No.	Description	Specification	Qty of each
2	Driving equipment consisting of rod, head and handle	MIL-A-3962, size 4 inch (102 mm)	2

3.12 Workmanship. The loading standards shall be free from defects such as misaligned components, incomplete welds, cracks, burns, leaks, and other defects that could impair the operation and serviceability of the loading standards. All parts shall be clean and free from dirt, sand, grease, oil, and metal chips.

3.12.1 Welders and welding.

3.12.1.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

AWS B3.0 - Standard Qualification Procedure.
ANSI/ASME - Boiler and Pressure Vessel Code, Section IX, Welding and Brazing Qualifications.

Certification shall be made available upon request of the contracting officer or designated representative.

3.12.1.2 Welding (aluminum). Welding performed in the fabrication of the loading standards shall be in accordance with drawing D13214E8326. The surface of parts to be welded shall be free from grit, scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading.

3.12.1.3 Castings. Castings shall be sound and free from patching, misplaced coring, warping, or any other defect which might render the casting unsound for its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Parts and components. Parts and components shall be inspected in accordance with the quality assurance provisions (QAP) shown on the applicable drawings (see 6.5 and 6.6).

4.1.3 Disassembly inspection. The first article loading standard failing a performance test shall be disassembled in the presence of a Government representative. Each disassembled part shall be inspected in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, and tolerances. Parts not complying with such requirements shall be rejected.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. Prior to assembling, the loading standards shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The fully assembled loading standards shall be tested as specified in 4.5.2. Failure of any test shall be cause for performance of the inspection specified in 4.1.3.

4.4 Quality conformance inspection.

4.4.1 Unit of product. For the purpose of inspection a unit of product shall be all individual parts and components required for assembling one complete loading standard.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2.2 For tests. Sampling for tests shall be in accordance with MIL-STD-105, level S-2, for both the sliding tube assembly and the complete loading standard.

4.4.3 Examination. Samples selected in accordance with 4.4.2.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective for major and 6.5 percent defective for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

4.4.4 Tests.

4.4.4.1 Sliding tube assembly. Samples selected in accordance with 4.4.2.2 shall be tested as specified in 4.5.2.2.2. AQL shall be 4.0 percent defective.

4.4.4.2 Loading standard (complete). Samples selected in accordance with 4.4.2.2 shall be tested as specified in 4.5.2.1, 4.5.2.2.1, and 4.5.2.3. AQL shall be 4.0 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The loading standard shall be examined as specified herein for the following major and minor defects:

Major

101. Any part or component not in accordance with the QAP requirements as shown on the drawing.
102. Materials not as specified.
103. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operating environments.
104. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
105. Contractor does not have documentation available for identification of material, material finishes, or treatment.
106. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the loading standards.
107. Components missing or not as specified.
108. Sliding tube assembly not as specified.
109. Adjustable assemblies that cannot be adjusted or do not perform the function intended.
110. Grounding reel and component parts not as specified.
111. Component lift markings omitted.
112. Threaded fasteners not as specified.
113. Positive means for electric conductivity not provided for.
114. Identical components not interchangeable.
115. Workmanship not as specified.
116. Welding not as specified on drawing D13214E8326.
117. Castings not as specified.

Minor

201. Lubrication fittings missing or not as specified.
202. Identification marking missing, incomplete, or illegible.
203. Instruction plates missing, incomplete, or illegible.
204. Treatment and painting not as specified.
205. Anchor kit incomplete.
206. Dimensions, other than those identified by QAP data, not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

4.5.2 Tests.

4.5.2.1 Static electrical. Measure the electrical resistance between the tip of the drop tube and the grounding cable attachment clip. Nonconformance to 3.4.1 shall constitute failure of this test.

4.5.2.2 Hydrostatic tests.

4.5.2.2.1 Loading standard. Subject the portion of the loading standard, from the fuel inlet to the loading valve, to a hydrostatic proof pressure of 150 psi, with the loading valve in the closed position. Retain the pressure for a minimum period of 2 minutes, rotate the loading arm 360 degrees and check the loading valve, riser pipe, double swing joint, and O-ring seals for leaks. Nonconformance to 3.5 and 3.6.2 shall constitute failure of this test.

4.5.2.2.2 Sliding tube assembly. Subject the sliding tube assembly to a hydrostatic pressure of 25 psi and hold for a period of 5 minutes. Nonconformance to 3.6.3 shall constitute failure of this test.

4.5.2.3 Loading arm assembly. Manually turn the loading arm 360 degrees in a horizontal plane, then vertically move the arm from not less than 30 degrees below, to not less than 70 degrees above the horizontal plane, the drop tube remaining in vertical position during testing. Manually lower the loading arm assembly into its loading position and leave for 2 minutes, then release the loading arm assembly and check its return to original position. Nonconformance to 3.6.1 a., b., c., or d. shall constitute failure of these tests.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

118.	Disassembly not as specified for level A.
119.	Removed bolts, nuts, pins, and washers not preserved and secured as specified for level A.
120.	Unprotected surfaces not preserved as specified for level A.
121.	Components not lubricated as specified for level A.
122.	Tent pins and ground anchors not secured as specified for level A.
123.	Technical publications not preserved and secured as specified for level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

124. Preservation and packing not in accordance with referenced document as specified for commercial.
125. Boxes not as specified for level A or B.
126. Components not blocked or braced within the box as specified for level A or B.
127. Strapping not as specified for level A or B.
128. Marking missing, illegible, incorrect, or incomplete for level A, B, or commercial.

5. PREPARATION FOR DELIVERY

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The riser assembly shall be disconnected from the loading arm assembly. The drop tube shall be folded and secured to the loading arm assembly. The support legs for type I and the cables for type II shall be secured to the riser assembly. Securing shall be with tape conforming to PPP-T-97, type I, size 3/4 inch. Removed bolts, nuts, pins, or washers shall be replaced in one of the mating parts and secured to prevent loss or preserved together in accordance with MIL-P-116, method IC-1 or IC-3, and secured to one of the assemblies with the tape specified herein.

5.1.1.2 Unprotected surfaces. Unprotected exterior metal surfaces of components of the loading standard requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.1.3 Lubrication. Components for which lubrication fittings have been provided shall be lubricated to capacity with the lubricant recommended by the manufacturer.

5.1.1.4 Tent pins and ground anchors. The tent pins and ground anchors as required shall be secured together with tape specified herein.

5.1.1.5 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, method IC-1, and secured to one of the assemblies with the tape specified herein.

5.1.2 Commercial. Each complete disassembled loading standard shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A. Components comprising a complete loading standard, preserved as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional. The contents shall be blocked and braced within the box in a manner to prevent movement or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

damage. Box closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.2.2 Level B. Packing shall be as specified in 5.2.1 except boxes shall be domestic type or class as applicable and strapping shall be finish A.

5.2.3 Commercial. Components comprising a complete loading standard, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951. In addition, weight and cube data shall be marked on the shipping container.

6. NOTES

6.1 Intended use. The portable loading standards are intended for use with fuel supply points for transferring bulk, combat liquid fuels from the supply point storage tanks to mobile tank trucks, and tank trailer truck.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Type loading standards required (see 1.2).
c. When a first article is required for inspection and approval, and number of units required (see 3.2).
d. When 6 foot drop tube with tee deflector fitting is required (see 3.6.5).
e. Color of class 2 anodic coating (see 3.9.1).
f. When anchors and driving equipment will not be Government furnished (see 3.11.2.1).
g. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the item will be tested and should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Government-furnished property. The contracting officer should arrange to furnish the property specified in 3.11.2.1, when applicable.

6.5 Quality assurance provisions (QAP). The contracting officer should require the contractor to maintain records of all QAP inspections. A suggested paragraph is as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

"The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirements, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.6 Definition of QAP. A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.7 Classification change. Type I loading standard has been discontinued since it is no longer required.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3990-A176

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 22060- 5606

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY
Commander
USA Belvoir R&D Center
STRBE-DS
Fort Belvoir, VA 220 -5606

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-L-40101D(ME)	Loading Standards, Liquid Transfer, Bulk: Petroleum Fuels, Portable, 2-Inch

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:15Z
Check the source to verify that this is the current version before use.