MILITARY SPECIFICATION

OPENERS, CAN, ELECTRIC, HEAVY DUTY

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope.- This specification covers two types of electric, heavy-duty can openers.

* 1.2 Classification.- Can openers shall be of the following types as specified (see 6.2).

Type I - Portable
Type II - Table

2. APPLICABLE DOCUMENTS

* 2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-393	-	Plastic Molding Material, Polycarbonate, Injection and Extrusion.
CC-M-636	-	Motors, Alternating-Current (Fractional Horsepower)
QQ-I-652	-	Iron Castings, Gray
QQ-Z-363	-	Zinc-Base Alloy; Die Castings
PPP-B-636	-	Box, Fiberboard
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

MILITARY

MIL-P-116	-	Preservation, Methods Of

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-66 - Steel: Chemical Composition and Hardenability

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized and Containerized Unit Loads 40" x 48" 4-Way (Partial) Pallet Skids, Runners, or Pallet-Type Base.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Society for Testing and Materials (ASTM)

Specification A167-70 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.

Standard E18-67 - Rockwell Hardness and Rockwell Superficial Hardness of Metalic Materials, Test for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

Underwriters' Laboratories, Inc. (UL)

Standard No. 73-1967 - Motor-Operated Appliances.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, New York 11749; 207 East Ohio Street, Chicago, Illinois, 60611; or 1655 Scott Boulevard, Santa Clara, California, 95050.)

National Sanitation Foundation (NSF)

Standard No. C-2 - Basic Criteria for the Evaluation of Special Equipment and/or Devices.

(Application for copies should be addressed to National Sanitation Foundation, P.O. Box 1468, Ann Arbor, Michigan 48106.)

(Technical society and technical associations specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

3. REQUIREMENTS

3.1 Standard product.- The can openers delivered under this specification shall be the manufacturer's standard commercial product, except for any changes necessary to meet specification requirements. All can openers of one type furnished under this specification, and any one contract, including parts and assemblies thereof, shall be identical.

3.2 Standards compliance.- The can openers shall conform to the applicable requirements of UL Standard No. 73.

* 3.2.1 U. L. certification.- Prior to approval of the first shipment, the supplier shall submit satisfactory evidence to the contracting officer or his authorized representative, that the can openers he proposes to supply meet the applicable requirements of UL Standard No. 73. Acceptable evidence of meeting applicable requirements of UL Standard No. 73 shall be the UL Label, UL Listing Mark, or a certified test report from a recognized independent testing Laboratory, acceptable to the Government indicating the can opener conforms to applicable requirements of UL Standard No. 73.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

3.3 Materials.- Materials not definitely specified shall be of the quality normally used by the manufacturer for can openers provided the completed items comply with all provisions of this specification. Commercial tolerances are applicable to all metal thicknesses and diameters.

3.3.1 Tube, steel, carbon.- Steel tube shall be square, seamless or mechanically welded seam tube, cold finished, conforming to the chemical composition of any AISI steel between 1010 and 1020 of FED-STD-66.

3.3.2 Rod, steel, carbon.- Steel rods shall conform to the chemical composition of any AISI steel between 1010 and 1020 of FED-STD-66.

3.3.3 Castings, iron.- Gray iron castings shall conform to class 30 of QQ-I-652.

3.3.4 Castings, zinc.- Zinc castings shall conform to alloy AG40A or AC41A of QQ-Z-363.

3.3.5 Steel, corrosion-resisting.- Corrosion-resisting steel shall conform to any type of the 300 series listed in ASTM A167-70.

* 3.3.6 Plastic.- Plastic material shall conform to L-P-393.

* 3.4 Design.- The can openers shall be electrically operated and designed to cut tops from circular, elliptical, or rectangular cans of all sizes up to and including No. 10 cans. The openers shall be equipped with a magnetic lid lifter(s) which shall hold the can top after it has been cut off. Openers shall include provisions for lubricating bearings, and other moving parts that require lubrication. Opener design shall allow opening of No. 12 and 4 1/4 x 4 1/4 inch square cans by placing over edge of table or counter when tested as specified in 4.4.2(c).

3.5 Construction.- For Navy procurements (see 6.2), the type I and type II can openers shall conform to the requirements of National Sanitation Foundation Standard No. C-2 - Basic Criteria for the Evaluation of Special Equipment and/or Devices.

3.5.1 Body.- The body on the type I and type II can openers shall be fabricated from cast iron specified in 3.3.3, zinc casting specified in 3.3.4 or corrosion-resisting steel specified in 3.3.5. In addition, the body of type I can opener may be fabricated from plastic material specified in 3.3.6. The type I can opener shall have a handle as an integral part of the body.

3.5.1.1 Feed wheel.- The feed wheel on the type I and type II can openers shall be fabricated of tool steel or other alloy steel, heat treated to a through hardness of 50 to 58 on the Rockwell C scale (see 4.4.1). The diameter of the feed wheel shall be not less than 7/8 inch. The wheel shall be secured to the feed mechanism so as to be removable for replacement. Maximum permissible radius on the sharp edge of each tooth shall not exceed 0.002 inch except when

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

feed and cutting wheels are geared together, the maximum permissible radius on the sharp edge of each tooth shall not exceed 0.005 inch. A stamped or rolled gripping surface will not be permitted except where the feed and cutting wheel shafts are geared together.

3.5.1.2 Cutting wheel.- The cutting wheel on the type I and type II can openers shall be fabricated of tool steel or other alloy steel, heat treated to a through hardness of 50 to 58 on the Rockwell C scale (see 4.4.1). The cutting edge shall be sharp and without burrs. The diameter of the cutting wheel shall not be less than 3/4 inch and the wheel shall be removable for replacement. The cutting wheel shall be mounted on a floating shaft secured to the body of the can opener and shall penetrate the top of the can adjacent to the inside bead by pressure applied by an eccentric lever. The cutting wheel shall not leave a sharp edge or any protrusion in the can. When tested as specified in 4.4.2 the cutting wheel shall make a clean cut without any deformation to metal not already deformed; and the top of the cans shall be completely severed.

3.5.1.3 Can holding device.- An eccentric or spring loaded or cam action can holding device shall be provided on the type I and type II can openers. The can holding device shall show no signs of failure when tested as specified in 4.4.3.

3.5.1.4 Can guide.- All type I and type II can openers shall have a can guide located on the body of the opener so that the guide will ride the top of the chime on the can and shall prevent the can from tipping while the can top is being cut.

* 3.5.1.5 Mounting, type II.- The type II opener shall be furnished with either a vertical shaft and a table clamp which mounts to the table or shall have 4 composition rubber supports permanently attached to the bottom of the body which stands on the table. When the can opener is furnished with a shaft it shall be tube conforming to 3.3.1, a cast iron shaft (H form) conforming to 3.3.3, or a round carbon steel shaft conforming to 3.3.2. When a round shaft is provided, a positive locking device shall be furnished which does not allow the shaft to turn when the can opener is operated. A set-screw alone is not considered a positive locking device. The diameter of the shaft shall be 1-inch, plus or minus 1/32 inch, and a minimum of 14 inches in length. The bracket to accommodate the shaft shall be constructed of cast iron specified in 3.3.3 and shall incorporate a clamping device to enable that bracket to be securely attached to table edges up to and including 3 inches thick. The table clamping bracket shall incorporate a clamping device to hold the vertical shaft of the opener at any desired height. The base plate of the table clamping bracket shall not crack, bend, chip, or break when tested as specified in 4.4.4. When composition rubber supports are furnished, the opener shall not tilt or slide when tested as specified in 4.4.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

* 3.5.1.6 Assembly.- The body of the openers shall be so constructed that the feed wheel, cutting wheel, can holding device and the can guide are readily removable with the use of simple tools such as a screwdriver and pliers.

3.5.2 Lid lifter(s).- Magnetic lid lifter(s) shall be provided on the body assembly of the type I and type II can openers. After the lid has been cut from the top of the can, the lid lifter(s) shall hold the lid (see 4.4.2).

3.5.3 Electrical characteristics.- Unless otherwise specified (see 6.2), all electric equipment shall be designed for operation on a nominal 120-volt, alternating current (a.c.), 60-hertz (hz) circuit. The motor shall conform to CC-M-636. A 3-wire neoprene cord, 5 to 8-1/2 feet long, shall be provided. The can openers shall be grounded. One end of the cord shall have a grounding plug with the grounding wire at the other end, connected to the motor frame.

* 3.5.4 Electromagnetic compatibility.- When specified (see 6.2), equipment procured for Army shall be designed and equipped for electromagnetic compatibility in accordance with class IIB of MIL-STD-461 (see 4.4.5).

* 3.6 User's instruction plate.- Each can opener shall bear instructions stamped on a corrosion-resistant plate riveted to thee exterior, or indented in a conspicuous place on an exterior surface of the opener. When the type I can opener is fabricated of plastic, a decalcomania containing operating and maintenance instructions as specified herein shall be placed on an exterior surface of the can opener. The instructions shall include:

(a) Instruction for replacing cutting and feed wheels.
(b) Method of accomplishing clearance between cutting and feed wheels (if applicable).
(c) Method and location for lubricating all moving parts.

3.7 Operational parts.- Three additional sets of cutting wheels and feed wheels shall be furnished with each opener. Where cutting wheel studs are used, three of these studs shall be furnished with each can opener. All parts shall be attached securely to the base of type I can openers, or to the clamping bracket of type II openers, when applicable.

3.8 Marking.- Each can opener shall be marked with the manufacturer's name, trade name, or trademark readily identifiable with said manufacturer.

* 3.9 Finish.- The can opener shall be smooth on all surfaces and edges, free from discoloration and stains, and shall be finished in accordance with the manufacturer's standard practice.

3.10 Workmanship.- Metallic surfaces shall be clean and not contain any rough or sharp edges, burrs, slivers, scratches, rough die marks, gouges, pits,

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

rust or scale. All surfaces to be welded shall be clean. Welding shall be accomplished in a manner that will prevent pits and flashes. All scale or flux deposits shall be removed from finished welds. The molded surfaces shall be free from blisters, cracks, dirt, and flash, and all gates shall be trimmed flush. Bolt holes and rivet holes shall be accurately punched or drilled and any obstruction that prevents proper seating shall be removed. All threaded fasteners shall be drawn tight. Rivets shall be tightly driven, fully peened, and shall completely fill the holes. The finished item shall not be fractured, buckled, bent, punctured, malformed, or damaged.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Components and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.2.2 Process inspection.-

* 4.2.2.1 In process testing.- The feed and cutting wheel hardness tests shall be performed in accordance with 4.4.1. The sample unit shall be one feed wheel and one cutting wheel. The lot shall be the number of feed and cutting wheels offered for inspection at one time. The inspection level shall be S-3 with an acceptable quality level (AQL) of 4.0 defects, expressed in terms of defects per hundred units.

4.2.3 End item inspection.- The inspection lot shall consist of all can openers of one type offered for inspection at one time. The sample unit for this inspection shall be one completely fabricated can opener.

4.2.3.1 Visual examination.- The end item shall be examined for defects in table I. The inspection level shall be II with an AQL of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

TABLE I. - Classification of defects

Examine	Defect	Classification Major	Classification Minor
Finish (Metallic and molded surfaces, as applicable)	Not manufacturer's standard		X
	Evidence of discoloration, or stains	X	
	Not smooth on all surfaces	X	
Construction and workmanship (applicable to all components and assemblies)	Any rough or sharp edges, burrs, slivers, scratches, rough die marks, gouges, pits, rust, or scale	X	
	Any component missing	X	
	Any component not securely attached	X	
	Any component fractured, buckled, punctured, distorted, or malformed	X	
	Moving parts bind, or are loose	X	
	Removable components i.e. feed wheel, cutting wheel, can holding device, and can guide cannot be accomplished by use of simple tools (pliers and screwdriver)	X	
	Adjustable assembly that cannot be adjusted	X	
	Component not accessible, where required	X	
	Functioning component that requires abnormal force to operate	X	
Rivets (when applicable)	Missing, loose, broken, or inadequately peened	X	
	Does not fill hole completely	X	
	Rivet heads not in full contact with riveted members		X
Threaded components	Missing, stripped, or fractured	X	
	Loose		X
Identification marking	Missing, incomplete, not legible		X
Electrical cord	No grounding plug	X	
	Grounding wire not connected as specified	X	
Instruction plate	Missing, incomplete, not legible	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

4.2.3.2 Dimensional examination.- Examination shall be made of the end items to determine conformance with dimensions specified herein. Any nonconformance shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.2.3.3 Testing of the end product.- One can opener from each production lot shall be tested as specified in 4.4.2 through 4.4.3 and when applicable 4.4.4 and 4.4.5.

4.3 Examination of preparation for delivery.- An examination shall be made to determine that preservation, packaging, packing, and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table II. The lot shall be the number of shipping containers offered for inspection at one time. The sample unit shall be one container fully prepared for delivery. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

TABLE II. - Examination of preparation for delivery

Examine	Defect
Marking	Missing; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Content	Contents per container are more or less than required. Additional operational parts missing.
Preservation	Preservative improperly applied or missing.

4.3.1 Examination of shipping containers.- When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing and strapping shall be in accordance with PPP-B-636.

* 4.3.2 Examination of palletization.- An examination shall be made to determine that palletization is in compliance with section 5 of this specification. Defects shall be as indicated in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

TABLE III.- Examination of palletization

Examination	Defect
Finished dimension	Length, width or height exceeds specified maximum requirements.
Palletization	Not as specified. Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

4.3.3 Standard compliance.- The supplier shall submit to the Government representative, proof of compliance with UL Standard 73 as required in 3.2.1.

4.4 Tests.-

4.4.1 Rockwell hardness.- The feed wheels and cutting wheels shall be tested for hardness in accordance with ASTM E18-67 to determine compliance with 3.5.1.1 and 3.5.1.2. Testing shall be performed on the Rockwell C scale. Testing on the superficial scale is not permissible. Any noncompliance with specified requirements shall constitute failure of the test.

4.4.2 Performance.- The type I and type II can openers shall be tested to determine compliance with 3.5.1.2 and 3.5.2. The test shall be performed as follows:

(a) The can opener shall cut the tops from circular, elliptical, and rectangular cans referenced in 3.4. Three sizes of circular, three sizes of elliptical, and three sizes of rectangular cans shall be used for this test.

(b) The can openers shall cut the tops from cans dented as follows: No. 10 cans, commercially packed, four to a case and weighing a minimum of 6 pounds each, shall be dropped on the six sides and four diagonal corners of the case from a height of 2 feet onto a flat concrete surface. During the above test, the lid lifter(s) shall come in contact with the can lid and after the lid is completely cut off from the can, the lid lifter(s) shall hold the can lid away from the can. Any noncompliance with specified requirements shall constitute failure of this test.

(c) Type II openers furnished with rubber supports shall open one each No. 12 and 4-1/4 x 4-1/4 inches square cans by positioning the opener so that the can is over the edge of the table. Inability to meet can opening requirements of paragraph 3.4 shall constitute failure of test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

4.4.2.1 Stability.- Type II can openers furnished with rubber supports shall be tested as follows: The lids of six No. 10 cans having a minimum gross weight of 10 pounds per can shall be cut open. The position of the opener shall be noted prior to, and after, operation to determine conformance to 3.5.1.5. Any noncompliance with specified requirements shall constitute failure of this test.

4.4.3 Can holding device load capacity.- The can holding device shall hold the can while a force of not less than 25 pounds is applied in a vertical downward direction to the can held in position for opening to determine compliance with 3.5.1.3. When the operation of the opener and the clamping action are accomplished by the same handles, the handles shall be held closed during the test and the power shall be off. Inability of the can holding device to hold the specified load capacity shall constitute failure of the test.

4.4.4 Base plate impact.- A 3-pound, plus or minus 1/4 pound, spherical metal weight shall be dropped vertically from a point approximately 1 foot above the center of the plate of the type II opener with vertical shaft and table clamp and the plate shall be checked for compliance with 3.5.1.5. Any noncompliance with the requirements specified shall constitute failure of this test.

* 4.4.5 Electromagnetic compatibility test.- When electromagnetic compatibility is required, the initial unit of production shall be tested by the supplier in accordance with test method CE03, and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the supplier or an independent testing agency. The supplier shall furnish the Contracting Officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic compatibility test report, and the requirements meet MIL-STD-461.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.- Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.-

5.1.1.1 Disassembly.- Components of each can opener such as the table clamping bracket, shall be disassembled from each can opener to reduce cubage of the pack. Disassembly shall be limited to those components which are secured to the can opener by hand-operated fasteners, such as thumb screws and wing nuts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

5.1.1.2 Preservation.- All exposed, uncoated ferrous metal surfaces of each can opener and operational parts shall be cleaned process C-1, thoroughly dried, and coated with type P-14 preservative in accordance with MIL-P-116.

5.1.1.3 Packaging.- Each disassembled and preserved can opener with electric cord coiled and secured to the motor unit shall be packaged in the most compact manner in a snug-fitting fiberboard box conforming to style RSC (end opening), type CF, variety SW, or type SF, class domestic of PPP-B-636. Fiberboard inserts or other suitable cushioning material shall be used if necessary to immobilize and isolate the contents within the box to prevent movement or damage during transit. Each box shall be closed in accordance with the appendix of PPP-B-636.

5.1.2 Level C.- The can openers shall be preserved and packaged to afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.- Four can openers, preserved and packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, V2s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat strapping or tape banding in accordance with the appendix of PPP-B-636.

* 5.2.2 Level B.- Four can openers, preserved and packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

* 5.2.2.1 When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636.

5.2.3 Level C.- Can openers, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification rules or National Motor Freight Classification rules, as applicable.

5.3 Palletization.- Unless otherwise specified (see 6.2) can openers packed as specified shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

5.4 Marking.- In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The electric can openers covered by this specification are intended for use in cutting the tops from circular, elliptical, and rectangular cans. The openers are primarily used in food preparation areas.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type required (see 1.2).
(c) When procurement is for Navy (see 3.5).
(d) Electrical characteristics if other than specified (see 3.5.3).
(e) When electromagnetic compatibility is required (see 3.5.4).
(f) Selection of the applicable levels of preservation and packaging, and packing (see 5.1 and 5.2).
(g) When weather-resistant fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(h) When palletization is not required (see 5.3).

* 6.3 Manuals.- Any requirements for instruction manuals for the items covered by this specification should be included in DD Form 1423 Contract Data Requirements List and cited in the contract.

6.4 The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 84

Review activities:

Army - MD
Navy - MC, MS, YD

Preparing activity:

Army - GL

Project No. 7330-0374

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commander
US Army Mobility Equipment Research and
Development Center
Attn: STSNL-TD
Fort Belvoir, Virginia 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION
'Openers, Can, Electric, Heavy Duty MIL-O-40155C

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:21Z
Check the source to verify that this is the current version before use.