MILITARY SPECIFICATION

PADDLE, PARACHUTE PACKING, ALUMINUM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of parachute packing paddle for use as a parachute packing aid.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-566	- Boxes, Folding, Paperboard
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-665	- Boxes: Paperboard, Metal Edged and Components
PPP-B-676	- Boxes, Setup
PPP-T-45	- Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1670

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:18Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

11-1-152 - Paddle, Parachute Packing, Aluminum

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA. 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

* 3.2 Materials and components. Materials and components shall be as specified herein and on Drawing 11-1-152. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial products, provided that the completed item complies with all provisions of this document. Recycled material may be used (see 6.4).

3.3 Construction. The construction of the parachute packing paddle shall conform to the requirements of Drawing 11-1-152 and as specified herein. The end item shall not be bent, split, twisted, or otherwise damaged.

3.4 Identification marking. Marking for identification shall include part number and the manufacturer's name or trademark, as specified on Drawing 11-1-152.

3.5 Workmanship. The parachute packing paddle shall be clean and free from sharp edges, burrs, or metal slivers. There shall be no surface evidence of blowholes, sponginess, or shrinkage. The anodized coating shall be continuous and adherent, not powdery, and free from any evidence of corrosion, dirt, grease, oil, or foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:18Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When a first article is required, a completely fabricated end item shall be examined for the defects listed in table I. The presence of any visual defect or dimension not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the paddle at appropriate stages of fabrication to determine conformance to the requirements of this document and the applicable drawing. The Government reserves the right to exclude from consideration for acceptance components for which in-process inspection has indicated nonconformance.

4.4.3. End item inspection. The parachute packing paddles shall be examined for visual defects and proper dimensions. The lot size shall be all the completed parachute packing paddles offered for inspection at one time. The sample unit shall be one paddle.

4.4.3.1 Visual examination. The parachute packing paddle shall be examined for the defects listed in table I. The inspection level shall be II, and the acceptable quality level (AQL) shall be 2.5 for major defects and 10.0 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish, protective	Omitted or not type specified	101	
	Coating powdery, discontinuous, not adherent, or any evidence of corrosion	102	
	Color not as specified		201

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects - Continued

Examine	Defect	Classification	
		Major	Minor
Material	Any surface evidence of blow-holes, sponginess, or shrinkage defects	103	
Construction and workmanship	Item bent, split, twisted, or otherwise damaged	104	
	Any surface roughness in excess of maximum specified		202
	Dirt, grease, oil or foreign matter		203
	Any sharp edges, burrs, or metal slivers	105	
Identification marking	Incorrect, incomplete, missing, not legible; improper location, or improper method of application		204

4.4.3.2 Dimensional examination. An examination shall be made of the end item for compliance with dimensions as specified on Drawing 11-1-152. Any nonconformance shall constitute a defect. The inspection level shall be S-3, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

4.4.4 Packaging inspection. An examination shall be made to determine that preservation, packing, and marking comply with the section 5 requirements. Defects shall be as listed in table II. The lot shall be the number of containers offered for inspection at one time. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2, and the AQL shall be 2.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:18Z
Check the source to verify that this is the currentversion before use.

TABLE II. Packaging inspection

Examine	Defect
Marking (interior package and exterior container)	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application (i.e., not on shipping tag or paper label when applicable)
Materials	Component missing, damaged, defective, or not as specified
Workmanship	Improper packaging, contents loose or not snug fit; incomplete or improper closure of containers; inadequate or improper application of components such as cleats, nails, strapping; bulged or distorted container
Contents (unit pack and exterior container)	Number per unit pack or exterior container not as specified

4.4.5 Examination for palletization. An examination shall be made to determine that palletization complies with the section 5 requirements. Defects shall be scored in accordance with table III. The lot size shall be the number of palletized unit loads in the inspection lot. The sample unit shall be one palletized unit load fully packaged. The inspection level shall be S-1, and the AQL shall be 6.5, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of palletization

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Not as specified Pallet pattern not as specified Interlocking of loads not as specified Loads not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted, incorrect, illegible, or of improper size, location, sequence, or method of application

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A, or Commercial, as specified (see 6.2).

5.1.1 Level A. Twenty paddles shall be unit packed in a snug-fitting, folding setup or metal stayed paperboard box conforming to variety I, style III or VIII, type B, class a of PPP-B-566; type I, variety 1, class A, style 3 or 4 of PPP-B-676; or style A of PPP-B-665, respectively. The paddles shall be positioned on edges and alternated end for end within each box. Inside dimensions of each paperboard box shall be 12 inches in length, 3 1/2 inches in width, and 1 5/8 inches in depth. Box closure shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade B, of PPP-T-45, applied at the center of the length opening and extending along the bottom and up each side at least 1 inch.

5.1.2 Commercial. Paddles shall be preserved in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. One hundred and sixty paddles, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, V2s of PPP-B-636; or class 2, style optional, type 2 load of PPP-B-621, as specified (see 6.2). Level A unit packs shall be packed flat one in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 12 1/4 inches in length, 7 1/2 inches in width, and 7 inches in depth. Approximate dimensions are furnished as a guide only. Each fiberboard container shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636. Each wood container shall be waterproofed with a sealed case liner conforming to type I or II, grade C of MIL-L-10547, and closed and reinforced in accordance with the appendix of PPP-B-621.

5.2.2 Level B packing. One hundred and sixty paddles, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to type CF or SF, class domestic, variety SW, grade 275, style RSC of PPP-B-636. Level A unit packs shall be packed flat one in length, two in width, and four in depth within a shipping container. Inside dimensions of each shipping container shall approximate 12 1/4 inches in length, 7 1/2 inches in width, and 7 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification.

5.2.3 Commercial packing. Paddles, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), paddles, packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type I or Ia, as applicable, of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the patterns of each course. If the container is of a size that does not conform to any of the container patterns specified in MIL-STD-147, the container pattern used shall first be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The parachute packing paddle is used for dressing parachute packs and for stowing webbing or flaps in retainers on parachute assemblies.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required and, if required, number of samples (see 3.1, 4.3, and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type of shipping container desired for Level A packing (see 5.2.1).
e. Whether weather-resistant fiberboard shall be required for Level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, the item shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

* 6.4 Recycled material. The contractor is encouraged to use recycled material when practical, provided that it meets the requirements of this document (see 3.2).

6.5 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:18Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - AS
Air Force - 99

Review activities:

Army - AV
Navy - MC
Air Force - 82

Preparing activity:

Army - GL

Project No. 1670-0706

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-40130D	Paddle, Parachute Packing, Aluminum

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 82 MAR — PREVIOUS EDITION IS OBSOLETE.

NATICK OPT, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:18Z
Check the source to verify that this is the current version before use.