23 February 1966
SUPERSEDING
MIL-T-40112A(GL)
16 December 1963

MILITARY SPECIFICATION

TABLE, KITCHEN, DROP-LEAF, PLASTIC TOP

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type and size drop-leaf, kitchen table having a laminated, thermosetting, decorative top and metal tubular legs.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
MMM-A-188	-	Adhesive, Urea-Resin-Type (Liquid and Powder).
PPP-B-636	-	Box, Fiberboard.
PPP-C-650	-	Crates, Wood, Open and Covered.

MILITARY

MIL-W-6110	-	Wood, Determination of Moisture Content Of.
MIL-L-10547	-	Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

STANDARDS

FEDERAL

Fed. Test Method Std. No. 141	-	Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling, and Testing.

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

STANDARDS (cont'd)

MILITARY

MIL-STD-105 - Sampling procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions, should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal, shall apply.

UNITED STATES DEPARTMENT OF COMMERCE

Commercial Standard CS 35 - Hardwood Plywood.
Commercial Standard CS 45 - Douglas Fir Plywood.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION

Publication LD1-1964-Laminated Thermosetting Decorative Sheets.

(Application for copies should be addressed to National Electrical Manufacturers' Association, 155 E. 44th Street, New York, N.Y. 10017.)

3. REQUIREMENTS

3.1 Preproduction sample.- Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished table covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production tables.

3.2 Materials.- The materials shall conform to the applicable referenced specifications and requirements specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

Where materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice.

3.2.1 Adhesive.- Adhesive shall conform to any type of MMM-A-188.

3.2.2 Plywood panels.- Plywood panels shall be constructed of hardwood veneers, a combination of hardwood veneers and softwood, or a combination of hardwood veneers and lumber core, as specified in 3.2.2.1, 3.2.2.2 and 3.2.2.3, respectively. Face and back veneers for all constructions shall be close-grained hardwood conforming to grade 1 or 2 veneers of Commercial Standard CS 35. The veneers shall be of such thickness as required to produce the finished top thickness specified in 3.3.1, and to produce a balanced panel to prevent warping.

3.2.2.1 Hardwood veneer plywood panels.- Hardwood veneer plywood panels shall be 5 or 7 ply, fabricated of all hardwood veneers. The panels shall be constructed in accordance with type II, grade 1 or 2 of Commercial Standard CS 35.

3.2.2.2 Combination of hardwood veneers and softwood panels.- Combination hardwood veneers and softwood panels shall be 5 or 7 ply. The face and back veneers shall conform to 3.2.2 and shall have an interior type bond. The interior plies shall be of softwood conforming to interior type, grade A-B of Commercial Standard CS 45.

3.2.2.3 Combination of hardwood veneers and lumber-core plywood panels.- Combination hardwood veneers and lumber core plywood panels shall be 3-ply minimum. The face and back veneers shall conform to 3.2.2, and crossbands, when used, shall be hardwood veneers conforming to grade 1 or 2 of Commercial Standard CS 35. Hardwood veneers shall have an interior type bond. The interior of the panel shall have a lumber core of medium or low density hardwood, or Idaho or Ponderosa Pine, Spruce or similar low density softwood. Construction of the lumber core shall conform to "regular" grade of Commercial Standard CS 35, and shall be glued in accordance with the manufacturers' standard practice. After the lumber core has been glued, and prior to surfacing, the moisture content shall be stabilized to not less that 5 percent and not more than 9 percent when tested as specified in 4.3.2.2.

3.2.3 Laminated, thermosetting, decorative sheet.- The laminated, thermosetting, decorative sheet shall conform to type I (general purpose) of National Electrical Manufacturers' Association Publication No. LD1-1964. The sheet shall be not less than 1/16 inch thick and the surface of the sheet shall have a satin finish. Unless otherwise specified (see 6.2), the color and grain shall approximate frosted walnut and shall be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

3.2.4 Steel tubing.- Steel tubing shall be either the welded or the seamless type, and shall have a minimum wall thickness of 0.049 inch.

3.2.5 Hinges, continuous.- The continuous hinges shall be not less than 1-1/2 inches wide when opened, and shall be fabricated from brass, bronze, corrosion-resisting steel or chrome-plated wrought steel. The fastening screws shall be of the same material and finish.

3.2.6 Glides, self-leveling.- The self-leveling glides shall have floor contact surfaces of stainless steel, molded polyethelene, polyvinyl chloride acetate, or cellulose acetate butyrate. The glides shall fit securely to the table leg ends.

3.3 Construction.- Except for any modification required by this specification, the table shall be the standard product of the manufacturer. The overall design dimensions of the table shall be within the following limits. However, all tables furnished on a single contract shall be within ± 1/8-inch of the dimensions established by the preproduction sample or initial production model:

(a) Length with leaves down, 25-1/4 inches maximum, 22-3/4 inches minimum.
(b) Length with leaves up, 60-1/4 inches maximum, 57-3/4 inches minimum.
(c) Width, 36-1/4 inches maximum, 34-3/4 inches minimum.
(d) Height, 30 inches maximum, 29 inches minimum.

3.3.1 Table top and drop leaves.- The table top and drop leaves shall be fabricated from material specified in 3.2.2, and shall not be warped greater than 1/8 inch in width, and 1/16 inch in length. The overall thickness of the table top and drop leaves, including decorative sheets, shall be not less than 13/16 inch.

3.3.1.1 Fastening of table top and drop leaves.- The table top and drop leaves shall be joined by a continuous hinge conforming to 3.2.5. The hinge shall end 1/2 to 1 inch from the edge of the table top. There shall be no binding in the operation of the hinge. When the drop leaves are raised to the horizontal position, the gap between the table top and drop leaves shall not exceed 1/32 inch. The maximum misalignment, in any plane, between the table top and drop leaves, shall be 1/16 inch.

3.3.1.2 Laminated, decorative surface sheets and strips.- A laminated, thermosetting decorative sheet conforming to 3.2.3 shall be bonded to the table top and to the top and bottom surfaces of the drop leaves.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

A phenolic, laminated, kraft backing sheet, not less than 0.062 inches thick, or a decorative sheet conforming to 3.2.3 shall be bonded to the bottom surface of the table top. Seams or joints shall not appear on the face surfaces of the laminated, thermosetting, decorative sheets, and there shall be no evidence of patched, blistered, or rough areas; mars, pinholes, chips, cracks, or scratches. All the edges of the table top and drop leaf plywood panels shall be self-edged with plastic strips of the same color and grain of the laminated thermosetting, decorative sheet. All bonding shall conform to 3.3.1.3. All edges shall be beveled or chamfered. There shall be no delamination between the plywood and the laminated, thermosetting, decorative sheets, or self-edged strips. The joints between the decorative sheets and the plastic edge strips shall be tight with no opening. When viewed at a distance of 5 feet, discoloration, spotting, streaking, staining, surface contour, swells, lapping of printed layer, depression, mold marks and grain shall not be visible in the laminated, thermosetting, decorative sheets or edge strips.

3.3.1.3 Gluing.- The laminated, thermosetting, decorative sheets and phenolic backing sheet (when used) shall be bonded with adhesive specified in 3.2.1. The adhesive shall be applied in an adequate and uniform manner with pressure, pressing time, and open and closed assembly time conforming to recommendations of the adhesive manufacturer.

3.3.2 Drop leaf support.- The drop leaf support shall be designed to rigidly support the drop leaves and table top when the leaves are in the horizontal position. When wooden extension slides are used, they shall be of the heavy duty type, with the combined thickness of the sliding components a minimum of 3-1/8 inches. The table shall not tip, and the separation of the table top and drop leaf shall not exceed 3/32 inch when a 100 pound force is applied to the outside edge of the leaf when tested as specified in 4.4.1.

3.3.3 Legs.- The legs shall be fabricated from tubing specified in 3.2.4. The legs shall be tapered or swaged from 1-1/2 inches plus or minus 1/4 inch to a smaller diameter as design requires, and fitted with a brass or aluminum ferrule and a self-leveling glide conforming to 3.2.6. The legs and braces (when required) shall be fabricated and attached in a manner to permit them to be easily removed from the table top for shipping and storage, without the need for special tools. The legs shall not be visibly out of vertical alignment.

3.3.3.1 Leg braces.- When leg braces are required by the manufacturer's design, they shall be fabricated from tubing specified in 3.2.4. The diameter shall be not less than 1/2 inch. The braces shall be crimped

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

and prepared as necessary to receive screws or bolts at the underside of top or support. When gate-leg type tables are supplied, the legs shall be braced and secured to a pivoting mechanism at the underside of the top in a manner that will insure efficient operation of the gateleg, and will provide a rigid construction without sway or wobble.

3.3.4 Hardware, miscellaneous.- All miscellaneous hardware, such as bolts, screws (except screws used with hinges, see 3.2.5) and slides, shall be fabricated from steel and given a zinc or cadmium plating or painted in accordance with commercial practice.

3.3.5 Stability.- When placed on a flat, level surface, the assembled table shall not rock more than 1/16 inch. The table top and raised drop leaves shall not slope more than 3/16 inch over the length of the table or more than 1/8 inch over the width of the table.

3.4 Finish.-

3.4.1 Surface preparation.- Steel legs and braces shall be given a surface preparation conforming to any method, type I or II of TT-C-490.

3.4.2 Enameling.- After surface preparation, the legs and braces shall be coated with a commercial bronze enamel.

3.4.2.1 Adhesion and toughness of film.- It shall be difficult to cut through the film with a sharp knife blade as specified in test of 4.4.2. The cut edge shall not have the jagged appearance indicative of brittleness of the coating.

3.4.2.2 Resistance to alkali solution.- There shall be no blistering, wrinkling, or other visible failure of the film when immersed in an alkali solution as specified in test of 4.4.3. After air drying for 24 hours, there shall be no more than a slight difference in color when compared to the portion of film not immersed.

3.4.2.3 Resistance to salt spray.- There shall be no blistering, wrinkling, or other visible failure of the film when subjected to a salt spray as specified in test of 4.4.4. Twenty-four hours after the test, the film shall be no softer than the film of an unexposed panel when tested with the thumbnail.

3.5 Identification marking.- Identification marking shall be in accordance with MIL-STD-130. The letters "U.S.", in characters 1 inch high minimum, and the manufacturer's identification in characters 1/4 inch high minimum, shall be stamped or legibly stenciled on the underside of the table top.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

3.6 Assembly instructions.- Comprehensive, legible assembly instructions shall be securely attached to the underside of the table top.

3.7 Workmanship.- All surfaces shall be free of burrs, slivers, and rough or sharp edges. Components shall not be broken, twisted or cracked. The enamel coating shall level out to a continuous, smooth, dry film thickness, without runs, drops, streaks or areas of no film. The coating shall be free from imbedded foreign matter, and shall show no evidence of peeling, flaking or blistering.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection.- When a preproduction sample is required, it shall be examined for defects in table II, dimensions specified, and tested as specified in 4.4.1.

4.3 Sampling for inspection.- Sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3.1 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.1.1 Certificate of compliance.- The supplier shall furnish a certificate of compliance stating that material for self-leveling glides is in compliance with 3.2.6.

4.3.2 In-process inspection.-

4.3.2.1 In-process examination.- Examination shall be made during the manufacturing process for surface preparation specified in 3.4.1 to establish that no deviation is made from indicated requirements. Whenever nonconformance is noted, correction shall be made to affected items and process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

4.3.2.2 Intermediate testing.- Testing shall be performed for moisture content in accordance with MIL-W-6110, for compliance with 3.2.2.3. Three determinations shall be taken on each sample unit and the results for the unit shall be the average of the three determinations. The sample unit shall be one lumber core after gluing and prior to surfacing. The lot shall be all lumber cores submitted for inspection at one time. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5, expressed in terms of defects per hundred units.

4.3.2.3 Enamel durability.- Testing shall be performed for the characteristics in table I. The tests shall be performed on three specimens, 3 inches by 6 inches, representative of a production run. Failure of any test shall be cause for rejection of components processed, during the production run.

TABLE I.- Enamel tests

Characteristic	Requirement paragraph	Test method
Adhesion	3.4.2.1	4.4.2
Resistance to alkali solution	3.4.2.2	4.4.3
Resistance to salt spray	3.4.2.3	4.4.4

4.3.3 End item inspection.- The lot shall be all the tables offered for inspection at one time. The sample unit for this inspection shall be one assembled table.

4.3.3.1 Visual examination.- Examination shall be made of the end item for defects in table II. The inspection level shall be level II with an AQL of 2.5 for major defects and 10.0 for total defects expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

TABLE II.- Classification of defects

Examine	Defect	Classification Major	Minor
Components			
Tubing	Not as specified.		X
Hinges	Not continuous type.		X
Glides	Not self-leveling type.		X
	Not secure fit to table leg ends.	X	
Finish			
Enameled surfaces	Not color specified.		X
	Not continuous and smooth.		X
	Has runs, drops or streaks.		X
	Area of no film.	X	
	Dirt, grit, or other foreign matter imbedded in finish.	X	
	Evidence of peeling, flaking or blistering.	X	
Plated surfaces	Not as specified.	X	
Quality of table top			
Decorative sheet and edge strips	Color not as specified.		X
	Not satin finish.		X
	Seams or joints appear on face surfaces.	X	
	Patched, blistered or rough areas.	X	
	Mars, pinholes, chips, cracks, or scratches.	X	
	Edges not beveled or chamfered.	X	
	Delamination between plywood and decorative sheet or edge strip.	X	
	Openings between decorative sheet and edge strips.	X	
	Discoloration, spotting, streaking, staining, surface contour, swells, lapping, depression, mold marks, and grain, visible at a distance of 5 feet.	X	
	Any portion of backing sheet unbonded, when applicable.	X	
Construction and workmanship	Table top and drop leaves warped more than 1/8-inch in width.	X	
	Table top and drop leaves warped more than 1/16-inch in length.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

TABLE II.- Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (cont'd)	End of hinge more than 1 inch or less than 1/2-inch from edge of table top.		X
	Operation of hinge causes binding.	X	
	Gap between table top and drop leaves greater than 1/32-inch when leaves are in horizontal position.		X
	Misalignment between table top and drop leaves greater than 1/16-inch.		X
	Drop leaves supports do not hold leaves rigid to table top when leaves are in raised position.	X	
	Legs not detachable without use of special tools.	X	
	Legs visibly out of vertical alignment.	X	
	Gate legs, when applicable, not properly braced or secured to pivoting mechanism to provide efficient operation and rigid support.		X
	Burrs, slivers, rough or sharp edges.	X	
	Component missing, broken, twisted or cracked.	X	
	Functional component loose.		X
	Functional component requires excessive force to operate.	X	
Identification marking	Missing, illegible, incorrect, incomplete or wrong size.		X
Assembly instructions	Missing, illegible, not comprehensive or not securely attached to table.		X

4.3.3.2 Dimensional inspection.- Inspection shall be made of tables for compliance with dimensions specified. Any noncompliance shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

4.3.4 Testing of the end item.- The tables shall be tested in accordance with 4.4.1 to determine compliance with 3.3.2. The drop

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

leaf support test shall be performed on one table from each lot offered for inspection. Any failure shall be cause for rejection of the lot.

4.3.5 Examination of preparation for delivery.- An examination shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table III. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0, expressed in terms of defects per hundred units.

TABLE III.- Examination of preparation for delivery

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strappings, or tape banding, and inadequate stapling. Bulging or distortion of containers.
Contents	Number per package is more or less than required.

4.4 Tests.-

4.4.1 Drop leaf support test.- The drop leaves shall be raised to the horizontal position and supported as in normal use. Weights totaling not less than 100 pounds shall be placed on an area not to exceed one square foot. The area shall be centered on the longitudinal centerline of the table, and shall extend from the outside edge of the leaf inward to a distance not greater than one foot. With the weights in position, the table shall be examined to determine compliance with 3.3.2.

4.4.2 Adhesion (knife test).- The test panel shall be tested in accordance with Method 6304 of Fed. Test Method Std. No. 141 to determine compliance with 3.4.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

4.4.3 Alkali test.- A portion of the test panel shall be immersed in a 5 percent solution of sodium hydroxide for 30 minutes at room temperature to determine compliance with 3.4.2.2.

4.4.4 Salt spray test.- The test panel shall be exposed to a 20 percent salt spray for 200 hours in accordance with Method 6061 of Fed. Test Method Std. No. 141, to determine compliance with 3.4.2.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A (see 6.3).-

5.1.1.1 Disassembly.- Each table shall be shipped with the legs detached (K.D.).

5.1.1.2 Packaging.-

5.1.1.2.1 Legs.- Each leg shall be sleeved wrapped in one sheet of 30-pound basis weight (24 by 36-500) machine-glazed kraft paper, highly calendered kraft paper, or waxed paper. Each wrap shall be secured with tape. Legs required for one table shall then be packaged in a snug-fitting, low-height, one-piece folder conforming to style OPF, type CF, class domestic, grade 200 of PPP-B-636. The contents of each folder shall be immobilized so as to preclude movement or damage to the legs while in transit. Each box shall be securely closed in accordance with the appendix of the box specification.

5.1.1.2.2 Hardware.- Detached hardware shall be placed in a cotton cloth drawstring or kraft paper bag and the bag secured to the underside of the table top.

5.1.1.2.3 Table top and drop leaves.- Each table shall be packaged with two drop leaves in the normal open position, except when one of the drop leaves may be folded flat against the bottom without straining the hinges. In this event, one of the drop leaves shall be in the open position and the other folded against the underside of the table top. When slides are used for drop-leaf support, they shall be secured in the closed position. The top surface and edges of the table top and drop leaves shall be completely covered in one sheet of paper specified in 5.1.1.2.1, and then cushioned with a pad or blanket made from any one of the following materials or combination of materials to provide built-up cushioning of not less than 3/4 inch thick:

Macerated paper, plain.
Macerated paper, cellulose-faced.
Shredded paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

Wood wool.
Wood fiber felt.
Excelsior (sealed ends).
Cellulose wadding.
Cotton wadding.
Moulded pulpboard.
Laminated cellulose wadding backed with corrugated fiberboard.

When cellulose-faced mascerated paper, cellulose wadding, cotton wadding, or laminated cellulose wadding backed with corrugated fiberboard are used, the initial sheet of machine-glazed kraft paper, highly calendered kraft paper, or waxed paper may be omitted. The cushioning material and paper wrap shall be secured tightly to the bottom surfaces of the table top and drop leaves.

5.1.1.2.4 Other components.- Other detached components of each table shall be packaged in a snug-fitting fiberboard box conforming to type CF, class domestic of PPP-B-636, or they may be secured to the underside of the table top in such a manner as to prevent damage while in transit. Each box shall be securely closed in accordance with the appendix of the box specification.

5.1.1.2.5 Placement.- Each complete table, prepared as specified, shall be packaged in a snug-fitting, double-wall, fiberboard box conforming to style FTC, type CF, class domestic of PPP-B-636. Each box shall be provided with a snug-fitting full-height tray made of the same material as the box. The flaps shall be glued to the inside surface of the sides of the tray. Placement of components of each table shall be as follows: Each table top, with either one or both drop leaves extended, shall be placed top surface down within the tray. The packaged legs, erection instructions, and other components shall be placed on top of the inverted table top and drop leaves and secured in place. The fiberboard tray containing each complete table shall then be placed within the bottom of the box. The contents of each box shall be immobilized by means of air cells, die-cut pads, et cetera, so as to preclude movement or damage to the table while in transit. Each box shall be securely closed in accordance with the appendix of the box specification.

5.1.2 Level C.- Tables shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

5.2 Packing.- Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A.- Two tables, packaged as specified in 5.1, shall be packed in a snug-fitting crate conforming to type II, style A of PPP-C-650. Care shall be exercised to assure that the packaged tables are placed within the crate with the top surface of the table top down. Each crate shall be provided with a type I or II, grade C case liner conforming to MIL-L-10547. Each shipping container shall be closed and strapped in accordance with the appendix of the crate specification.

5.2.2 Level B.- Unless otherwise specified (see 5.2.2.1), each table, packaged as specified in 5.1.1, shall be reinforced with flat steel strapping or tape banding in accordance with the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the fiberboard box specified in 5.1.1.2.5 shall conform to style FTC, V3c of PPP-B-636.

5.2.3 Level C.- Tables, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.- In addition to any special marking required by the contract or order, each box containing one table and each shipping container shall be marked in accordance with MIL-STD-129.

5.3.1 Additional marking.- In addition to marking specified in 5.3, the top panel of each box containing one table and each shipping container shall be marked in letters not less than 2 inches high, as follows:

FURNITURE

FRAGILE, HANDLE WITH CARE

TOP

THIS SIDE UP

One front panel of each shipping container shall be marked in letters not less than 2 inches high, as follows:

UP FURNITURE UP

FRAGILE, HANDLE WITH CARE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.- The table covered by this specification is intended for use in kitchens or dinettes of living quarters of Military personnel.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a preproduction sample is not required (see 3.1).
(c) Color and grain of laminated, thermosetting, decorative sheet, if other than specified (see 3.2.3).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant fiberboard is required for level B pack (see 5.2.2.1).

6.3 Packaging.- The method of packaging referred to in 5.1.1, is similar to method III of MIL-P-116.

Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - YD
Air Force - 69

Preparing activity:

Army - GL

Project No. 7105-0105

Review activities:

Army - MD
Navy - YD
Air Force - 69

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing Of DOD Documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

TABLE, KITCHEN, DROP-LEAF, PLASTIC TOP - MIL-T-40112B

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01762

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRE-SS
Natick, Massachusetts 01762

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.