30 September 1968

MILITARY SPECIFICATION

TABLE, KITCHEN, DROP-LEAF, PLASTIC TOP

This amendment forms a part of Military Specification MIL-T-40112B, dated 23 February 1966, and is mandatory for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under listing of Military Specifications.- Delete "MIL-W-6110 - Wood, Determination of Moisture Content Of."

PAGE 2

2.1, under listing of Military Standards.- Delete "MIL-STD-130 - Identification Marking of US Military Property."

2.2, under listing of United States Department of Commerce.- Delete "Commercial Standard CS 45 - Douglas Fir Plywood" and substitute "Product Standard, PS 1-66 Softwood Plywood/Construction and Industrial."

Add the following in proper sequence:

"AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 2016-62 - Standard Methods of Test for Moisture Content of Wood

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)."

PAGE 3

3.2.2.2, line 5.- Delete "Commercial Standard CS 45" and substitute "Product Standard PS 1-66".

PAGE 4

3.2.6, line 2.- Delete "stainless" and substitute "corrosion-resisting".

PAGE 5

3.3.3, line 4, after "or".- Insert "brass colored anodized."

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

PAGE 6

3.5 Delete and substitute:

"3.5 Marking for identification.- The manufacturer shall permanently and legibly mark his name or trademark of such known character easily identifiable with said manufacturer on the underside of the tabletop."

PAGE 8

4.3.2.2 Delete and substitute:

"4.3.2.2 Intermediate testing.- Testing shall be performed for the moisture content of wood requirement in 3.2.2.3, and shall be determined in accordance with ASTM D2016-62. The lot shall be all lumber cores prepared under the same conditions, stored as a group, and offered for inspection at one time. The sample unit shall be one lumber core after gluing and prior to surfacing. The inspection level shall be S-1 with an AQL of 4.0, expressed in terms of defects per hundred units. When testing is performed by the electric moisture meter method, three determinations shall be made on each sample unit. The average of the three determinations shall be the moisture content of the sample unit."

PAGE 9

Table II, under examination of finish.- Add in proper sequence "Legs, ferrule not brass colored - Minor".

PAGE 11

4.3.5, lines 5 and 6.- Delete "with the exception that it need not be sealed."

Table III Delete entries in "Defect" column applicable to "Workmanship" and substitute "Inadequate application of components, such as components not immobilized or secured, and interior boxes not securely closed."

Add the following new paragraph in proper sequence:

"4.3.5.1 Examination of shipping containers.- Examination for defects in closure and strapping of shipping containers shall be in accordance with the appendix of the applicable container specification."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

PAGE 12

5.1.1.2.1, line 1, after "sleeved".- Insert "or".

PAGE 13

5.1.1.2.3, continued, line 9.- Delete "mascerated" and substitute "macerated".

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - YD
Air Force - 84, 85

Preparing activity:

Army - GL

Project No. 7105-0138

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.