MILITARY SPECIFICATION

WAFFLE IRON, ELECTRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one size of double unit, electrically heated, counter-type waffle iron with automatic controls.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing
PPP-B-636	-	Boxes, Shipping, Fiberboard

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:16Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel, Plate, Sheet and Strip

A 176 - Stainless and Heat-Resisting Chromium-Steel Plate, Sheet, and Strip

B 26 - Aluminum-Alloy Sand Castings

B 108 - Aluminum-Alloy Permanent Mold Castings

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

UNDERWRITERS' LABORATORIES, INC. (UL)

UL No. 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, LI, NY 11746; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 Standard product. The waffle irons shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Modification to add features shall not incorporate different parts unless such parts are used on other current commercial models. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturers or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:16Z
Check the source to verify that this is the currentversion before use.

* 3.2 Codes and standards. The waffle iron shall comply with the applicable requirements of NSF Standard No. 4, and UL No. 197.

* 3.2.1 Compliance. Prior to commencing production, the contractor shall submit to the contracting officer, or his authorized representative, satisfactory evidence that the waffle iron he proposes to furnish under this specification meets the applicable requirements of NSF and UL as follows:

* 3.2.1.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished waffle iron, or

(2) A certification for the waffle iron issued by NSF under their special one-time contract evaluation/certification service, or

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the waffle irons are being procured, indicating that the waffle irons have been tested and conform to NSF.

* 3.2.1.2 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the waffle irons have been tested and conform to UL No. 197.

3.3 Materials and components. The materials and components shall conform to the requirements specified hereinafter. When materials are not definitely specified, they shall be of the quality normally used by the manufacturer. Unless otherwise specified herein, commercial tolerances are applicable to all material thicknesses.

* 3.3.1 Stainless steel sheet and strip. Stainless steel sheet and strip shall conform to any type in the 300 or 400 series of ASTM A 167 and ASTM A 176, respectively.

3.3.2 Aluminum castings. Aluminum castings shall conform to alloy 319 or 443 of ASTM B 26 or ASTM B 108.

3.4 Design and construction. The waffle iron shall be of the double unit, electrically heated, counter-type design. The waffle iron shall have two separate baking units with each baking unit capable of being operated independent of the other. Each baking unit shall consist of its own upper and lower grid, "ON" - "OFF" switch, control, spillage receptacle, and indicating device. Each baking unit shall be capable of producing not less than 15 waffles per hour when tested as specified in 4.4.2. The waffle iron overall dimensions shall be not more than 20 inches wide, 20-1/2 inches deep and 12 inches high (closed position).

Source: https://assist.dla.mil -- Downloaded: 202640-21T19:16Z
Check the source to verify that this is the currentversion before use.

3.4.1 Body. The body shall be fabricated of stainless steel specified in 3.3.1. Finish shall be as specified in 3.8.

3.4.2 Grids. Grids shall be cast aluminum as specified in 3.3.2. Each baking unit shall be of a size to produce a waffle having an area of not less than 38 square inches. When the upper grid is in the closed position it shall mesh with the lower grid. The upper grid shall have a floating hinge so that the upper grid, when closed, will remain parallel within 1/32 of an inch to the batter-filled lower grid (see 4.4.4).

* 3.4.3 Handle. A handle shall be provided on each upper grid section of each baking unit. The handle shall be securely fastened to the upper grid(s) and shall be used for raising and lowering the upper grid from its normal down position to the raised and lock position and return.

* 3.4.4 Spillage receptacle. A spillage receptacle shall be provided under each lower grid section and shall be removable. Spillage receptacles shall be fabricated from stainless steel (see 3.3.1) and shall be formed to catch and retain overflow baking unit spillage.

3.4.5 Electrical characteristics.

3.4.5.1 Voltages. The waffle iron assembly shall be rated for one of the following nominal system voltages, as specified (see 6.2):

(a) 120-volt, 1-phase, 60 Hertz (hz)
(b) 240-volt, 1-phase, 60 Hertz (hz)

* 3.4.5.2 Electrical input. The waffle iron assembly shall have an input rating of not less than 1650 watts at the specified voltage rating (see 4.4.3).

* 3.4.5.3 Cable and plug assembly. The waffle iron assembly shall be electrically grounded by a three wire grounding type cord and an attachment plug cap with a grounding prong. One end of the cord shall be connected to a terminal block within the waffle iron assembly. The external length of the cord shall be not less than 5-1/2 feet nor more than 6 feet.

3.4.5.4 Heating elements. Heating elements shall be provided in each upper and lower grid section of each baking unit. Heating elements shall be of the enclosed type and like heating elements shall be interchangeable. Heating elements shall be removable with the use of simple tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

* 3.4.5.5 Controls. Controls shall be located at the front of the body or on the stationary part of each baking unit. Controls shall consist of "ON" - "OFF" switch and mechanical timer. Each baking unit shall be provided with an "ON" and "OFF" switch to control the heating element circuit in both the upper and lower grid section. Each baking unit shall have a mechanical timer graduated in minutes from 0 to not less than 3 minutes. Controls shall be operated through one complete cycle i.e., first, center, and third positions and whenever the preset time has been reached on the timer, the indicating device shall operate, that is, either an audible alarm or an indicating light goes off (see 4.4.1). Position settings shall be clearly marked on the timer knob. When the "ON" - "OFF" switch is placed in the "OFF" position, all ungrounded lines shall be broken. At all positions, the switches and controls shall not be loose and shall operate without binding when tested as specified in 4.4.1.

* 3.4.5.6 Indicating light. Unless otherwise specified (see 6.2), each baking unit shall be provided with an indicating light. The indicating light shall glow whenever the heating elements system(s) are energized and go out whenever the heating element circuits are deenergized (see 4.4.2.).

3.5 Performance. The waffle iron assembly shall be given the performance tests specified in 4.4.1 and 4.4.2. All parts, including mechanical timers, switches, indicating lights, and movable grids shall operate satisfactorily without failure and baking shall continue during this cycle. Each baking unit shall be capable of baking waffles at a rate of 15 waffles per hour. Waffles produced during the performance test shall be evenly baked and similar in appearance to each other when compared visually.

* 3.6 Marking. Identification markings shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate thickness shall be not less than 0.012 inch.

3.6.1 Identification marking. Each waffle iron assembly shall be permanently marked with the manufacturer's name, trade name or trademark of such known character as to be readily identifiable with said manufacturer.

3.7 Repair and maintentance. Provisions shall be made to allow access to permit adjustment, repair or replacement of electrical and other components.

3.8 Finish. All surfaces shall comply to NSF Standard No. 4. The waffle iron assembly shall be smooth on all surfaces and edges and shall be free from discoloration or stains.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

* 3.9 Workmanship. All components and assemblies of the waffle iron assembly shall be free from dirt and other harmful extraneous material; burrs; slivers; rough die, tool and grind marks; dents, and cracks. Castings, molded parts and stampings, if used, shall be free of sand, fins, pits, blow holes and sprues. External surfaces shall be free from sharp edges and sharp corners.

3.9.1 Metal fabrication. Metal used in the fabrication of the waffle iron assembly shall be free from kinks. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and like bends shall be of uniform size and shape.

3.9.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free of cracks, burn holes, undercuts or incomplete fusion. All scale shall be removed from the finish weld area.

3.9.3 Fastening devices. Threaded fasteners and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked, or stripped and shall be drawn tight. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all waffle iron assemblies offered for inspection at one time. The sample unit shall be one completely fabricated waffle iron assembly.

* 4.2.2.1 Visual examination. Examination shall be made of the completely fabricated waffle iron for the defects listed in table I. The inspection level shall be II, and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product, except for changes necessary to comply with specification requirements	X	
Finish	Not in accordance with NSF	X	
	Edges and surfaces not smooth	X	
	Not free of discoloration or stains		X
Construction and workmanship (general)	Component missing	X	
	Any wearing part not accessible for adjustment or replacement	X	
	Any component fractured or malformed	X	
	Any component misplaced or not in alignment	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed	X	
	Functioning component that is inoperative or will not operate as intended	X	
	Component that requires abnormal force to operate		X
	Any adjustable assembly not properly adjusted to perform the intended function		X
	Not fabricated of material specified	X	
Detail construction			
Body	Controls not on front	X	
Grid	Upper and lower grid do not mesh	X	
	Loose		X
Handle	Loose		X
	Not type specified (keep cool type)	X	
Spillage receptacle	Not formed to catch spillage	X	
	Not removable	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Electrical switch and other components (as applicable)	Missing, not type specified, or does not function as intended	X	
	Not accessible to operator	X	
Welding	Missing	X	
	Not free from rust, scale, paint, grease and other foreign matter	X	
	Scale and flux deposits not removed		X
	Weld not smooth and free of cracks, burnholes, undercuts or incomplete fusion		X
Fastening devices	Missing, cracked or stripped		X
	Fastener, loose		X
	Rivet holes not accurately punched	X	
	Rivet not peened properly		X
Marking identification	Missing, incomplete, not legible, not corrosion-resistant metal (when not marked directly on the item)	X	

4.2.2.2 Dimensional examination. The waffle iron shall be examined for compliance with dimensions specified. Any dimension not within the specification tolerance shall be a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.2.2.3 End item testing. Each waffle iron shall be tested as specified in 4.4.1. Failure of this test shall be cause for rejection of the unit. One representative production unit shall be tested as specified in 4.4.2, 4.4.3, and 4.4.4. Failure of any test shall be cause for rejection of the inspection lot.

* 4.2.3 Packaging inspection. An inspection shall be made to determine that preservation, packaging, packing, and marking comply with the section 5 requirements. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery except that it need not be closed. The lot shall be the number of shipping containers in the end item lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

TABLE II. Packaging inspection

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Bulged or distorted container
Contents, exterior and interior	Number of packages per shipping container is more or less than required

* 4.2.4 Examination of shipping container. When shipping containers are required to comply with PPP-B-636, examination of defects in the closure, waterproofing and reinforcing shall be in accordance with the appendix of PPP-B-636.

4.3 Certificate examination. Certificates of compliance, certified test reports, approved labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Tests.

* 4.4.1 Operational test. Connect the waffle iron assembly to an electrical power source having the same characteristics specified in the contract and check that all moving components function as intended for compliance with 3.4.5.5. Observe that indicator lights glow whenever the heating electrical systems are activated and go out when power is turned "OFF". Operate mechanical timer through one complete cycle for compliance with 3.4.5.5. One complete cycle shall be defined as operation from each of the settings to "OFF", i.e., first position to "OFF"; center position to "OFF" and third position to "OFF". Check upper grid for compliance with the requirements of 3.4.2. Any noncompliance with specified requirements shall constitute failure of the test.

* 4.4.2 Performance test. Using same electrical power source in 4.4.1, turn switch to "ON" position, set mechanical timer to medium setting, allow waffle iron assembly to preheat in accordance with the manufacturer's standard procedure. When waffle iron assembly has reached proper preheat temperature, (when indicator light goes out) pour waffle batter mix on grid, close upper grid and bake until steam stops, remove waffle and check for compliance with the requirement of 3.5. Batter mix temperature for this test shall be 70°F. Repeat this procedure on each baking unit for a period of 30 minutes. During this test, hourly rate shall be checked to determine compliance with 3.4. Any noncompliance with specified requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

4.4.3 Wattage. When connected to a power source of known voltage, measure the power input to the waffle iron to determine compliance with 3.4.5.2. Any noncompliance with specified requirements shall constitute failure of this test.

4.4.4 Parallelism of upper grid. With the upper grid in the open position, place a 1/4 inch flat board on the lower grid. Check the upper grid for parallelism to determine compliance with 3.4.2. The waffle iron shall not be connected to an electric power source for this test. Any noncompliance with specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

* 5.1.1 Level A. Two thicknesses of minimum 30-pound basis weight (24 by 36-500) machine glazed kraft paper, highly calendered kraft paper or wax paper shall be placed between the upper and lower grid of each waffle iron, extending a minimum of 1 inch beyond the grids. The upper-hinged lid of each waffle iron shall be secured to the lower half or base of the waffle iron with cotton tape, cord, or twine. The extension cord shall be coiled and secured to the waffle iron with cotton tape, cord, or twine. Each waffle iron shall then be packaged in a fiberboard box conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Corrugated fiberboard inserts shall be used to provide a minimum of 1/2-inch clearance between the inner surfaces of the box and projecting parts of the waffle iron, such as handles and switches to secure the upper-hinged lid of the waffle iron in the closed position and to further immobilize the waffle iron in the box. One thickness of the paper specified herein shall be used to prevent contact between the fiberboard inserts and polished surfaces of the waffle iron. Waffle irons equipped with loose spillage receptacles shall have the trays removed from the waffle iron, wrapped in paper specified herein, and secured within the box by means of fiberboard inserts. Box closure shall be secured with a 2-1/2 inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45.

* 5.1.2 Level C. Waffle irons shall be packaged to afford adequate protection against physical damage during shipment from the contractor to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

* 5.2.1 Level A packing. Two waffle irons, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of the container specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

* 5.2.2 Level B packing. Two waffle irons, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF (variety SW) of SF, class domestic, grade 275 of PPP-B-636. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification.

* 5.2.2.1 Weather-resistant fiberboard shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with PPP-B-636, and closed in accordance with method III as specified in the appendix of the box specification.

* 5.2.3 Level C packing. Waffle irons, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The waffle irons are intended for use in Military kitchens and galleys.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Voltage required (see 3.4.5.1).
(c) When an indicating light is not required (see 3.4.5.6).
(d) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(e) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Contract data requirements. Any requirements for equipment manuals and drawings for the item covered by this specification should be included in DD Form 1423, Contract Data Requirements List, and cited in the contract.

6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:16Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activities:

Army - MD
Navy - SA

Preparing activity:

Army - GL

Project No. 7310-0547

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-W-40110C - Waffle Iron, Electric

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T19:16Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 Apr 76

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-21T19:16Z
Check the source to verify that this is the current version before use.