INCH-POUND
MIL-M-38510/319B
AMENDMENT 3
4 October 1999
SUPERSEDING
AMENDMENT 2
11 August 1986

MILITARY SPECIFICATION

Inactive for new design as of 18 April 1997

MICROCIRCUITS, DIGITAL, LOW POWER SCHOTTKY TTL, 4-BY-4 REGISTER FILE, CASCADABLE, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/319B, dated 4 March 1985, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Following 3.5, add 3.6 and 3.7 as follows:

"3.6 Marking. Marking shall be in accordance with MIL-M-38510.

"3.7 Microcircuit group assignment. The devices covered by this specification shall be in microcircuit group number 12 (see MIL-M-38510, appendix E)."

PAGE 14

TABLE III, tests 62 through 69 and 71 through 78, pin GW, delete "C" and substitute "B".

PAGE 16

* TABLE III, device type 01, delete footnote 1/ as changed in Amendment 1, delete previous change and substitute new footnote 1/ as follows:

"1/ Min/Max limits (µA) for circuits, unless otherwise specified.

Test	A	B	C	E	F
I_{IL1}	-120/-360	-30/-300	-160/-400 except -120/-360 for test 24	-120/-360 except -0.5/-360 for tests 22 and 24	-135/-370 except -150/-380 for test 23; -135/-380 for tests 24, 25, and 26
I_{IL2}	-.36 mA/ -1.08 mA	-30/-900	-305/-760	-.36 mA/ -1.08 mA	-.48 mA/ -1.20 mA
I_{IL3}	-240/-720	-60/-600	-305/-760	-240/-720	-320/-800

TABLE III, device 01, footnote 4/, delete in its entirety and substitute new footnote 4/ as follows:

"4/

A = 3.0 V min
B = 0.0 V or GND



PAGE 18

TABLE III, tests 50 through 56 and 59 through 66, pin GW delete "C" and substitute "B".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:09Z
Check the source to verify that this is the current version before use.

PAGE 19

TABLE III, device type 02, footnote 1/, delete in its entirety and substitute new footnote 1/ as follows:

"1/ Min/Max limits (µA) for circuits, unless otherwise specified.

Test	A	B	C	E	F
I_{IL1}	-120/-360	-30/-300	-160/-400 except -120/-360 for test 24	-120/-360 except -0.5/-360 for tests 22 and 24	-135/-370 except -150/-380 for test 23
I_{IL2}	-240/-720	-90/-900	-305/-760	-240/-720	-320/-800
I_{IL3}	-240/-720	-60/-600	-305/-760	-240/-720	-320/-800

PAGE 19

TABLE III, device type 02, footnote 3/, delete in its entirety and substitute new footnote 3/ as follows:

"3/

A = 3.0 V min
B = 0.0 V or GND

C = pulse 3.0 V ___ ___ 3.0 V"
0.0 V |___|

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI
Navy - OS, SH, AS, CG, MC
Air Force - 19, 99

Preparing activity:
DLA-CC

(Project 5962-1860)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:09Z
Check the source to verify that this is the current version before use.