MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, LOW-POWER SCHOTTKY TTL, QUADRUPLE BUS BUFFER GATES WITH THREE-STATE OUTPUTS, MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/323C, dated 7 August 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Low level input current at data input (control high) (circuits A and B only) test: Delete "(circuits A and B only)" from test title and substitute "(circuit A only)".

PAGE 16

TABLE III, device type 01, test numbers 45 through 48, symbol column: Delete "I_{IL2}, CKT A,B" and substitute "I_{IL2}, CKT A".

PAGE 18

TABLE III, device type 01, footnote 3/, I_{IL3} test, circuit D: Delete "-160/-400" and substitute "0/-100".

TABLE III, device type 01, footnote 4/, delete and substitute as follows:

"4/ Circuit E, tests 54 through 57, I_{OS}, min -30/max -130 mA."

PAGE 21

TABLE III, device type 02, footnote 3/, I_{IL3} test, circuit D: Delete "-160/-400" and substitute "0/-100".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH, TD
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1257)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T14:11Z
Check the source to verify that this is the current version before use.