MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, BIPOLAR, LOW POWER SCHOTTKY TTL,
OCTAL BUFFER GATES WITH THREE-STATE OUTPUTS,
MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/324C, dated 15 October 1987 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

1.4, maximum low-level input voltage: Delete and substitute as follows:

"Maximum low-level input voltage (V_{IL}):
All device types - - - - - - - - - - - - 0.7 V
Device types 04 and 05 at +125°C - - - 0.6 V"

PAGE 4

TABLE I, V_{OH1}, V_{OL1}, V_{OL2}, I_{OZH}, and I_{OZL}, conditions column: Add "V_{IL} = 0.6 V at +125°C for device types 04 and 05".

TABLE I, I_{OS}, conditions column: Delete "ALL". Device type column: Delete "-40" and substitute "ALL". Minimum limits column: Delete "-225" and substitute "-40". Maximum limits column: Delete "mA" and substitute "-225". Units column: Add "mA".

PAGE 5

TABLE II, group A test requirements, class S devices: Add "9, 10, 11".

PAGE 14

TABLE III, I_{IL}, pin $\overline{1G}$, test numbers 50, 51, 52, and 53: Add "GND".

TABLE III, I_{IL}, pin $\overline{2G}$, test numbers 54, 55, 56, and 57: Add "GND".

PAGE 18

TABLE III, footnote 1/, I_{IL}, circuit A: Delete "-5/-200" and substitute "0/-200".

PAGE 20

TABLE III, I_{IH1}, test numbers 59 and 60, minimum limits column: Delete "μ".

PAGE 24

TABLE III, footnote 5/, I_{IL}, circuit A: Delete "-5/-200" and substitute "0/-200".

AMSC N/A FSC 5962

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:11Z
Check the source to verify that this is the current version before use.

PAGE 28

TABLE III, subgroup 2: Delete "Same tests, terminal conditions, and limits as for subgroup 1, except T_C = +125°C and V_{IC} tests are omitted" and substitute "Same tests, terminal conditions, and limits as for subgroup 1, except T_C = +125°C, V_{IC} tests are omitted and V_{IL} = 0.6 V."

PAGE 31

TABLE III, footnote 1/: Delete "For device type 04; 0.7 V" and substitute "For device type 04; 0.7 V (0.6 V at 125°C)".

TABLE III, footnote 3/: Delete "For device type 05; 0.7 V" and substitute "For device type 05; 0.7 V (0.6 V at 125°C)".

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - SH, OS
Air Force - 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1309)

Source: https://assist.dla.mil -- Downloaded: 202610-21T14:11Z
Check the source to verify that this is the current version before use.