MIL-R-11534C
21 May 1969
SUPERSEDING
MIL-R-0011534B(MU)
18 March 1969
MIL-R-11534A
22 May 1952

MILITARY SPECIFICATION

REGULATOR, PRESSURE

This specification is mandatory for use by all Departments anc Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of pressure regulator.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attribtues.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

C81-1-778 - Regulator, Pressure.
IDL81-1-778 - Regulator, Pressure - Inspection Data List.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1040

Source: https://assist.dla.mil -- Downloaded: 20261O-17T18:18Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing C81-1-778 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the regulator shall conform to the specifications and drawings listed on Drawing C81-1-778 and subsidiary drawings.

3.2 Assembly. The regulator shall be assembled as specified on Drawing C81-1-778.

3.3 Pressure delivery. The regulator shall deliver air at 40 ± 10 pounds per square inch gage (psig) and 350 ± 10 psig with no pressure creep above 390 psig when tested as specified in 4.3 (see 6.3).

3.4 Workmanship. The regulator shall be free from foreign matter (oil, grease or dirt) and damage such as dents, cracks or deformation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspec-

Source: https://assist.dla.mil -- Downloaded: 202610-17T18:18Z
Check the source to verify that this is the current version before use.

tion requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspection are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the regulators of one interfix number, produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 For examination. The sample regulators shall be examined in accordance with the classification of defects and MIL-STD-105.

4.2.3.2 For critical defects. Each item in the lot shall be tested for the critical characteristics listed in the classification of defects.

4.2.3.3 Classification of defects. (See inspection data list IDL81-1-778 for inspection equipment required to perform the examinations specified in this section.)

(a) Regulator, pressure (Drawing C81-1-778)

Categories	Defects	Acceptance standards
Critical:		
1	Pressure delivery	4.3
Major:	AQL 1.0 percent defective	
101	Shipping tag missing or incorrectly marked	
102	Thread (5/8 - 18UNF-2A) incorrect	
103	Thread (1/4-18NPT) incorrect	
104	Angle inlet fitting incorrect	
105	Workmanship (3.4)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:18Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects (continued).

(a) Regulator, pressure (Drawing C81-1-778)(continued).

Categories	Defects	Acceptance standards
Minor:	AQL 4.0 percent defective	
201	Protective finish missing or incorrect	
202	Marking missing or incorrect	
203	Openings not capped or taped	

4.3 Pressure delivery test. (See inspection data list IDL81-1-778 for inspection equipment required to perform the test specified in this section.) The inlet of the regulator shall be connected to a source of compressed air at 2000 ± 100 psig. The outlet shall be connected to a pressure gage, a valve and a discharge orifice in the form of a No. 35 (0.110 inch) drilled hole in a standard 1/4 inch pipe cap. With the valve between the gage and orifice wide open, permitting full flow of air through the orifice, the regulator shall be adjusted to deliver air at 40 ± 10 psig. It shall then be adjusted to deliver air at 350 ± 10 psig. Finally the valve between the gage and orifice shall be closed, and the delivery pressure shall not rise above 390 psig when observed for a minimum period of 5 minutes (see 6.3).

5. PREPARATION FOR DELIVERY

5.1 Packaging, level C. Each regulator shall be individually packaged in a box conforming to type I, variety 2, grade A, class A, style 4, of PPP-B-676. Dimensions of the box shall be 5 inches length by 4 inches width by 3 1/2 inches depth. The open appendages of each regulator shall be taped and/or closed in accordance with drawing C81-1-778. Cushioning material, measuring 1/2 inch thick and conforming to type 2, class B of PPP-C-843, shall be used to completely cushion the item in the box, and shall be secured in place with tape conforming to PPP-T-76. The box shall be closed and secured with tape conforming to PPP-T-76.

5.2 Packing, level C. Twenty-five regulators, packaged as specified in 5.1, shall be packed together, in one layer, in a fiberboard shipping container conforming to style RSC, class CF, grade W5c of PPP-B-636. Inside dimensions of the shipping container shall be approximately 26 inches length by 21 inches width by 4 inches depth. Filler pads, conforming to grade W5c of PPP-F-320 shall be used, when necessary, to insure a tight pack. Closure of the shipping container shall be in accordance with the appendix to PPP-B-636 using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:18Z
Check the source to verify that this is the current version before use.

5.3 Marking. Unless otherwise specified in the contract or order the unit and shipping containers shall be marked in accordance with MIL-STD-129.

5.4 When this itme is procured for storage and issue as a repair part, preservation, packaging, packing and marking shall be as specified on the packaging data sheet which is identified by Federal Stock No. 1040-160-8050.

6. NOTES

6.1 Intended use. The regulator is intended for use with the M3 disperser for the regulation and control of high pressure air from the air cylinder to the fuel tanks.

6.2 Ordering data. Procurement documents should specify the title, number and date of this specification.

6.3 Caution. Due to the hazards inherent in testing with high pressure air, suppliers are hereby notified that every precaution possible should be taken to prevent injury to personnel engaged in testing.

Custodians:

Army - MU
Navy - MC
Air Force - 84

Preparing activity:

Army - MU(EA)

Project No. 1040-0046

Review activities:

Army - SM
Navy - MC
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:18Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 54 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:18Z
Check the source to verify that this is the current version before use.