INCH-POUND

MIL-R-11534C
AMENDMENT 1
19 July 1989

MILITARY SPECIFICATION

REGULATOR, PRESSURE

This amendment forms a part of MIL-R-11534C, dated 21 May 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, DRAWINGS: Delete "IDL81-1-778 - Regulator, Pressure - Inspection Data List."

PAGE 2

3.3: Delete paragraph in its entirety and substitute the following:

"**3.3 Pressure delivery.** The regulator shall deliver air at 40 ± 10 pounds per square inch gage (psig) with no pressure creep above 90 psig and 350 ± 10 psig with no pressure creep above 390 psig when tested as specified in 4.3 (see 6.3)."

PAGE 3

4.2.3.3, lines 1 through 3: Delete "(See inspection data list IDL81-1-778 for inspection equipment required to perform the examinations specified in this section.)"

4.2.3.3(a), defect 104: Delete defect 104 in its entirety.

4.2.3.3(a), defect 105: Delete "105" and substitute "104".

AMSC N/A FSC 1040

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T18:18Z
Check the source to verify that this is the currentversion before use.

PAGE 4

4.2.3.3(a), defect 201: Delete "or incorrect".

4.3: Delete paragraph in its entirety and substitute the following:

"**4.3 Pressure delivery test.** The inlet of the regulator shall be connected to a source of compressed air at 2,000 ± 100 psig. The outlet shall be connected to a pressure gage, a valve, and a discharge orifice in the form of a No. 35 (0.110 inch) drilled hole in a standard 1/4 inch pipe cap. With the valve between the gage and orifice wide open, permitting a full flow of air through the orifice, the regulator shall be adjusted to deliver air at 40 ± 10 psig. Close the valve between the gage and orifice and the delivery pressure shall not rise above 90 psig when observed for a minimum period of 5 minutes. Adjust the regulator to deliver air at 350 ± 10 psig. Close the valve between the gage and orifice and the delivery pressure shall not rise above 390 psig when observed for a minimum period of 5 minutes (see 6.3)."

PAGE 5

6.1: Delete paragraph in its entirety and substitute the following:

"**6.1 Intended use.** The regulator is intended for use with the M3 disperser, M2A1 flamethrower, and M2A1-7 flamethrower for the regulation and control of high pressure air."

Custodians:

Army - EA
Navy - MC
Air Force - 99

Review activity:

Air Force - 84

Preparing activity:

Army - EA

Project No. 1040-0120

Source: https://assist.dla.mil -- Downloaded: 202610-17T18:18Z
Check the source to verify that this is the current version before use.