A-A-1931A
March 31, 1988
SUPERCEDING
A-A-1931
April 9, 1982

COMMERCIAL ITEM DESCRIPTION

LOCK SET, BORED

The General Services Administration, Office has authorized the use of this commercial item description in preference to Federal Specification FF-H-106.

This description covers bored type locks for residential and industrial applications.

Salient characteristics:

Design. Product design including knobs, roses, fronts, latch bolts, strikes and other components shall conform to the requirements of ANSI/BHMA A156.2 'American National Standard For Bored And Preassembled Locks & Latches', for series 4000 lock sets. Lock sets furnished shall be compatible with door preparations conforming with ANSI A115.2. In the event of a conflict between this commercial item description and the standards referenced herein, this document shall take precedence.

Function and grade. Function and grade shall be in accordance with the identifying numbers shown in ANSI/BHMA A156.2.

Cylinders. When removable core or interchangeable cylinders are specified, the cylinders shall be removable by use of a control key which permits installation of a new core.

Keys. Keys shall be nickel-silver, brass or aluminum as specified. A set of two (2) keys shall be furnished with each lock set unless master keying is specified.

Master keying. Groups of lock sets shall be master keyed when specified. Three (3) master keys shall be furnished with each lock group when master keying is specified.

Finish. Unless otherwise specified, finishes shall be in accordance with BHMA/ANSI A156.18 'American National Standard For Materials And Finishes'.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:18Z
Check the source to verify that this is the current version before use.

Workmanship. The locks sets shall be free from imperfections and defects which affect appearance, durability, and serviceability. All finished parts of the hardware that are set flush shall have accurately machined, true edges. Edges of unfinished steel and iron and unpolished work, do not need to be machine finished, but shall be smooth and reasonably true.

Quality Assurance Provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Sampling.

Lot. All lock sets of the same type presented for acceptance at one time shall be considered a lot for purposes of inspection.

Sampling for quality conformance examination and testing. A random sample of lock sets shall be selected from each lot in accordance with Military Standard MIL-STD-105 'Sampling Procedures And Tables For Inspection By Attributes'.

Visual and inspection. Samples shall be selected in accordance with MIL-STD-105, general inspection level II, AQL 4.0 expressed in terms of percent defective. The sample lock sets shall be visually and dimensionally examined to verify compliance with this specification.

Tests per ANSI/BHMA A156.2. One lock set shall be randomly selected for each test specified and tested for conformance with the requirements specified in ANSI/BHMA A156.2. Failure of any lock set to conform with stated requirements shall be cause for rejection of the entire lot.

Certification. Listing in the current Builders Hardware Manufacturers Association, Inc., Directory Of Certified Locks & Latches or other listing service which provides equivalent testing and follow-up service shall be considered proof of conformance with ANSI/BHMA A156.2 test requirements. Labeling, listing and follow-up service procedures are specified in the BHMA directory. The Government may refuse to accept such listing as evidence of conformance if lock sets furnished are subsequently found not to conform with requirements.

Source: https://assist.dla.mil -- Downloaded: 20260-26T08:18Z
Check the source to verify that this is the current version before use.

Examination for preparation for delivery. A random sample of unit, intermediate and shipping containers (as applicable) shall be selected from each lot and examined for conformance with the preservation, packaging, packing, labeling and marking required in the contract or order. Samples shall be selected in accordance with MIL-STD-105, Inspection level II, AQL 6.5 expressed in terms of defects per hundred unit.

Preservation,packaging,packing,labeling,and marking (Civil Agencies). The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Packaging (DOD). The packaging shall be in accordance with ASTM Standard D3951 `Commercial Packaging, Practice for'.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.

Notes:

The issues or revisions of standards or directories referenced herein in effect on the date of solicitation shall be used to determine compliance with these requirements.

Copies of ANSI/BHMA Standards and BHMA directories are available from the Builders Hardware Manufacturers Association (BHMA), 60 East 42nd Street. New York, NY 10017. ANSI/BHMA Standards are also available from the American National Standards Institute, 1430 Broadway, New York, NY 10018.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Copies of military standards may be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:18Z
Check the source to verify that this is the current version before use.

Purchaser should specify:

1) This commercial item description, including revision and date.
2) Function number and grade in accordance BHMA/ANSI A156.2.
3) Nickel-silver, brass or aluminum keys (aluminum keys are more subject to wear and breakage).
4) If master keying is required (group lock sets only).
5) If removable core or interchangeable cylinders are required.
6) Finish required, see Appendix B, BHMA/ANSI A156.2 and BHMA/ANSI A156.18. BHMA Directory Of Certified Locks & Latches provides a list of models and finishes available from listed manufacturers.
7) Packaging, packing and marking requirements.

MILITARY INTERESTS:

Military Coordinating Activity

Navy - YD

Custodians

Army - AR
Navy - YD
Air Force - 99

Review Activity

DLA - IS
Air Force - 82

User Activity

Army - ME

CIVIL AGENCY COORDINATING ACTIVITIES

VA - OSS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:18Z
Check the source to verify that this is the current version before use.