A-A-50726
25 February 1988

COMMERCIAL ITEM DESCRIPTION

TEST SET, TELEPHONE

The General Services Administration has authorized the use of this Commercial Item Description.

Scope. This Commercial Item Description (CID), describes a telephone cable test set (TCTS). This CID is meant as a minimum requirement for the TCTS in which only those manufacturers that meet or surpass the following requirements are qualified per this CID.

Classification. Equipment covered by this CID may be commercially available equipment modified to the extent necessary to meet the following description. The equipment shall be type III, class 3, style P and color R in accordance with MIL-T-28800.

Applicable documents.

Specifications and standards. The following specifications and standards form a part of this CID to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-T-28800	Test Equipment for use with Electrical and Electronic Equipment, General Specification for

STANDARDS

MILITARY

MIL-STD-461	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.

(Copies of specifications, standards, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Other publications. The following document forms a part of this CID to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of the DODISS

AMSC N/A FSC 6625

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI-C62.41-1980

(Application for copies of ANSI publications should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

Order of precedence. In the event of a conflict between the text of this CID and the references cited herein (except for associated detail specifications, specification sheets or MS standards) the text of this CID shall take precedence. Nothing in this CID, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Salient characteristics. The equipment shall be capable of operation and be bid sample tested within the accuracies, limits, and specifications herein.

1. Safety. The equipment shall be UL (Underwriters Laboratories) listed and approved and/or shall comply with the Type III safety requirements of MIL-T-28800.

a. Leakage current protection. Protection shall be provided from leakage current in excess of 3.5 milliamperes (ma) rms (AC and DC) from any accessible conductive parts of equipment (including control shafts with knobs broken or removed and recessed calibration or adjustment controls) to either pole of the power source for any position of the power switch(es).

b. Radio frequency interference (RFI) capacitors. Any capacitor used in RFI filters shall be rated for at least four (4) times the operating voltage.

c. Type III ventilation openings.

(1) Ventilation openings shall be designed to prevent accidental contact with live electrical circuits and mechanical moving parts.

(2) Top ventilation openings shall incorporate small mesh screening or similar design to prevent the expulsion of hot electronic particles due to failure of electronic devices such as capacitors.

2. Parts, materials, and processes. Except for marking, the TCTS shall comply with the Type III parts, materials, and process requirements of MIL-T-28800. Nonstandard parts approval requests shall be in accordance with MIL-T-28800. Front panel marking shall be in accordance with MIL-T28800.

a. Restricted material. The equipment shall comply with the restricted material requirements of MIL-T-28800, including the requirement for mercury and radioactive materials, and shall contain no combination of materials which cause deterioration of any material contained in the equipment due to the effects of outgassing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

3. Design and construction. Unless otherwise specified herein, the equipment shall comply with the Type III design and construction requirements of MIL-T-28800. The equipment shall be of solid-state construction. Encapsulation and embedment (potting) of subassemblies may be used only for high voltage circuits where construction is susceptible to leakage or corona, indicators and associated controls shall be in close proximity to each other, all potentiometer controls shall have at least a 270 degree rotation range (4.71 radians).

a. Type of construction. Construction of the TCTS shall be of a monolithic or a separate component design.

b. Signal input and output connectors. Unless otherwise specified, all signal input and output connectors shall be Type BNC 310 connectors.

c. Internal cooling. The equipment shall be capable of operating continuously for twenty four (24) hours at 55°C. If forced air is used, it shall be as specified in MIL-T-28800.

(1) Forced air cooling motor. DC brushless motors shall be utilized for the forced air cooling motor in the equipment.

(2) Air filter. Equipment utilizing a cooling scheme which exhausts air from the equipment through the cooling fan shall not require an externally accessible air filter.

(3) Thermal switch. A thermal switch shall be provided which will interrupt circuit power to the TCTS when the internal temperature rises to the degree of possible damage to the electronic components. A minimum of 10°C hysteresis drop from this tripping temperature must occur before circuit power is again applied.

4. Electrical power sources. The equipment shall operate from internal batteries.

5. Dimensions and weight. The size and weight of individual components shall be consistent with current commercial capabilities, refer to paragraph 5.a of this CID.

a. Equipment weight. The weight including all accessories (excluding manual) per component, shall not exceed 12 lbs.

6. Enclosure requirements. Unless otherwise specified herein, the equipment shall comply with the Style P enclosure requirements of MIL-T-28800.

7. Marking and identification.

a. MARKING. The visible surface adjacent to panel facilities such as variable controls, indicators, jacks, connectors and fuse holder(s), shall be marked with a suitable word, phrase, or abbreviation thereof, indicating the purpose or use of the part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

(1) Panel marking. The front panel marking shall comply with the Type III parts, materials and processes panel marking requirements of MIL-T-28800; however, marking identification processes other than the Type III requirements specified in MIL-T-28800 may be used, provided the marking and identification processes are capable of passing the front panel marking test when tested in accordance with this CID.

8. Environmental requirements.

a. Temperature requirements. Unless otherwise specified herein, the equipment shall meet its specified performance characteristics and other requirements when subjected to the class 3 temperature requirements specified in MIL-T-28800 and as listed below.

b. Humidity requirements. The equipment shall meet its required performance and accuracy requirements under humidity requirements for class 3 equipment as specified in MIL-T-28800.

c. Altitude requirements. The equipment shall meet its required performance and accuracy requirements under the altitude requirements for class 3 equipment as specified in MIL-T-28800.

d. Vibration requirements. The equipment shall meet the class 3 vibration requirements as specified in MIL-T-28800.

e. Mechanical shock requirements.

(1) Shock, functional. The equipment shall meet the class 3 shock, pulse requirement as specified in MIL-T-28800.

(2) Transit drop. The equipment shall meet transit drop requirement as specified in MIL-T-28800.

(3) Bench handling. The equipment shall meet the requirements as specified in MIL-T-28800.

f. Electromagnetic interference (EMI). The equipment shall comply with MIL-T-28800 requirements for class 3 equipment.

g. Magnetic environment. The equipment shall comply with the magnetic environment requirements of MIL-T-28800 for class 3 equipment.

9. Reliability. Reliability verification testing, shall be in accordance with the type III, class 3 environmental conditions of MIL-T-28800.

a. Mean time between failures (MTBF). The equipment mean time between failures (MTBF) shall be 2,000 hours. The lower test MTBF shall be 2,000 and the upper test MTBF shall be 4,000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

b. Pre-conditioning requirement. Each deliverable equipment shall be capable of being subjected to the environmental screening effects of burn in and thermal cycling, with thermal cycling being accomplished in the sample testing phase.

(1) Burn-in. Burn-in shall expose the equipment to extended periods of elevated temperatures, (40°C for a minimum of 100 hours). Each equipment which fails during burn-in shall be repaired and fully retested, until failure free. Failures which occur during the burn-in test shall be noted and reported but shall not count toward the establishment of MTBF. Prior to and following burn-in, a satisfactory operation test (SOT) shall be performed. A satisfactory operation check (SOC) shall be conducted at selected times during the burn-in test.

(2) Thermal cycling. Thermal cycling shall expose the equipment to hot and cold cycles for class 3 equipment per MIL-T-28800. Each equipment which fails during thermal cycling shall be repaired and full cycling test shall be noted and reported but shall not count toward the cycling, a satisfactory operation check (SOC) shall be conducted during the last two upper and lower temperature limits.

10. Calibration and maintenance adjustments. The design of the system shall provide for readily accessible calibration adjustments and maintenance adjustments. These adjustments shall be provided by variable value components which are adjustable by the use of simple means. The calibration by substitution of selected components or parts is unacceptable unless specifically approved. The calibration adjustments, wherever possible, shall be accessible without removal of the instrument case or modules.

a. Maintainability. The equipment shall meet the type III maintainability requirements specified in MIL-T-28800.

11. Interchangeability. The equipment shall meet the type III interchangeability requirements specified in MIL-T-28800.

12. Digital interface. The equipment shall meet the digital interface requirements per MIL-T-28800 if applicable.

13. Performance characteristics.

a. The TCTS shall consist of the following components:

(1) Signal amplifier

(2) Probe, pencil type

(3) Receiver, headset type

(4) Carrying case

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

b. The amplifier shall include the following features:

(1) A frequency response range of 500 to 1000 Hz.

(2) An adjustable volume control.

(3) A 310 type output jack for the receiver.

(4) A 310 type input jack for use with a probe or coil.

(5) A selector switch to allow the amplifier to function with a probe input or a coil input.

(6) An internal battery power source.

c. The TCTS shall be capable of performing the receiver function during the following tasks:

(1) Exploring coil and cable identification test.

(2) Locating grounds, crossed wires, wet spots, shorts and split pairs.

14. Calibration interval. After calibration, the equipment shall meet each performance requirement within the tolerances specified for a period of at least 9 months, based on an operating time of 1500 hours.

Packaging, packing, and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with national motor freight classification and uniform freight classification. Shipping container shall be marked as specified in the contract or order.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. Small businesses that cannot offer products with established commercial market acceptability, may compete by submission of bid samples. (The Government reserves the rights to require proof of such conformance before first delivery and thereafter as may be otherwise provided for under the provisions of the contract).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

Known acceptable products: The following product(s) are known to have previously met the requirements of this CID and need not resubmit bid samples or certification. All other manufacturers must meet the requirements of this CID and submit to bid testing and certification as required.

Manufacturer	Model	NSN
AT&T	91A	6625-00-752-7662

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project 6625-0702)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.