COMMERCIAL ITEM DESCRIPTION

MODULATOR, PULSE

The General Services Administration has authorized the use of this Commercial Item Description

Scope This pulse modulator is a high performance microwave pulse modulator covering the range of 2 to 18 GHz. It can be used to increase the modulation capabilities of many microwave sources (sweepers or signal generators).

Applicable documents The following specifications form a part of this commercial item description to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation

SPECIFICATIONS

MIL-T-28800	Test Equipment for use with Electrical and Electronic Equipment General Specification for.
MIL-C-39012	Connectors, Coaxial, Radio Frequency

(Copies of specifications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Salient characteristics

1. Frequency range 2 to 18 GHz
2. On/off ratio > 60 dB
3. Rise and fall times < 10 ns
4. Insertion loss < 6 dB, 2 to 12.4 GHz, < 10 db, 2 to 18 GHz
5. Maximum RF input power +20 dBm
6. Maximum repetition rate > 5 Mhz
   Minimum RF pulse width < 50 ns
8. Video feed through < 60 mV peak-to-peak
9. Pulse input
   a. Normal mode > 3 V (on), < 0.5 V (off)
   b. Complement mode < 0.5 V (on) > 3 V (off)

AMSC N/A FSC 6625

Distribution STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

c. Impedance: 50 ohms nominal.

10 Operating temperature: 0°C to +55°C.

11 Power: 100, 120, 220, 240 V +5, -10%; 48-400 Hz.

12 Design MIL-T-28800, type II, class 5, style E, color R. Connector shall be in accordance with MIL-C-39012 (N type for input/output and BNC for video/pulse input)

System safety: Shall be in accordance with MIL-T-28800, paragraph titled Safety.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. Small businesses that cannot offer products with established commercial market acceptability, may compete by submission of bid samples. (The Government reserves the rights to require proof of such conformance before first delivery and thereafter as may be otherwise provided for under the provision of the contract).

Packaging, packing and marking The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping container shall be in compliance with national motor freight classification and uniform freight classification Shipping container shall be marked as specified in the contract or order.

Known acceptable product

Manufacturer	Model	NSN
Hewlett-Packard MFC 28480	11720A	6625-01-048-6815

Custodian
Air force - 99
Navy - EC
DLA -ES

Preparing activity
Air Force - 82

Reviewing activity
Army - CR

(Project 6625-F845)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.