COMMERCIAL ITEM DESCRIPTION

SIGNAL GENERATOR

The General Services Administration has authorized the use of this commercial item description.

Scope This is a 10HZ to 10MHZ, output 3 16 volt into 50 ohm signal generator for general purpose use.

Applicable documents MIL-T-28800

Salient characteristics.

Frequency range: 10Hz to 10 MHz, 6 bands, dial calibration, 1 to 10.

Dial Accuracy: ±2%, 100 Hz to 1 MHz; ±3%, to 10 Hz to 100 Hz and 1 MHz to 10 MHz (including warm up, drift and ±10% line variation).

Frequency Stability. + 10 ppm/minute at 5MHz (at ambient temperatures), ±0 02% at 5MHz for 24-hour period

Output: 200 mw (3.16 V into 50-ohms).

100 Mw (3 16 V into 100-ohms)

Amplitude Stability: ±0.1% at mid-band frequencies for at least 15 hours.

Distortion less than 1.0%, 10 Hz to 5MHz less than 2 0% at 10 MHz

Hum and Noise Less than 0.05% of maximum rated output

Output Monitor: Voltmeter to monitor level at input to attenuator in volts or dbm: bottom scale calibrated in volts, top scale calibrated in dbm/100-ohm, accuracy ±2% at full scale: flatness: ±1% at full scale, 20 Hz to 4MHz, ±2% at full scale, 10Hz to 20MHz, and 4MHz to 10MHz.

Frequency response flat within ±2%, 100 Hz to 1MHz ±3%, 10 Hz to 100 Hz: ±4%, 1MHz to 10MHz.

Amplitude Control: 20db; coarse and fine.

Attenuator: range 90db in 10 db steps overall accuracy, ±0.1 db, 0.3mV through 3V ranges; ±0.2 db, 0.1 mV range Zo = 50 - ohms and 100 - ohms.

Temperature range: 0°C to + 50°C.

FSC 6625

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Power: 115 or 230 V ±10%, 50 to 1000 Hz

Certification: Bid samples from bidders will be tested in accordance with the salient characteristics of this commercial item description at San Antonio ALC, Kelly AFB, TX 78241.

Packaging, packing and marking. The preservation, packaging, labeling and marking shall be as specified in the contract or order.

Design: MIL-T-28800, type III, class 5, style E, color R.

Intended use. This will be used on military end items.

Construction: System safety per MIL-T-28800, paragraph 3.2.

Known acceptable products.

Manufacturer	Model	NSN
Hewlett-Packard (no longer made)	C04-6515	6625 00 944 7820

Custodians:
Air Force - 99
Navy - EC

Preparing activity:
Air Force - 82

(Project 6625-0655)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.