A-A-50764
14 APRIL 1986

COMMERCIAL ITEM DESCRIPTION

QUAD-OUTPUT SWITCHING POWER SUPPLY

The General Services Administration has authorized the use of this Commercial Item Description.

SCOPE. This Commercial Item Description (CID) specifies a Quad-Output, 95 watt switching power supply which features regulated +5 VDC and + 15 VDC output for driving the CRT display in the Fire Control Radar Track and System Control Test Station. This system shall be known as Quad-Output Switching Power Supply.

APPLICABLE DOCUMENTS.

MIL-T-28800 - Test Equipment for Use with Electrical and Electronic Equipment, General Specification for

MIL-M-38797 - Manuals Technical: Operation Instructions and Maintenance Instructions

MIL-M-7298 - Manuals, Technical: Commercial Equipment

SALIENT CHARACTERISTICS.

1. Performance Requirements.

a. Quad-Output Switching Power Supply: The power supply has four output modules consisting of 95 watts switching. Output voltage is protected against overload and short circuit by an electronic current limiting fold back circuit with automatic reset upon removal of the short circuit or overload. The power supply shall be capable of providing a constant voltage output which can be set at an input of 105-132 volts AC with 47-420 Hz frequency range. The current ratings available for each nominal voltage are as follows:

Output #1	Output #2	Output #3	Output #4
5VDC@3.5A	15VDC@2.0A	-15VDC@2.0A	-5VDC@3.5A

The power supply shall have the complete facility for calibrating at the above ranges of power.

b. Voltage Accuracy. The Input Line Regulation and the Regulation Load shall be accurate to within 0.1 percent or 10mV for rated line change.

FSC 6130

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

c. Voltage Stability. The ripple and noise of the output voltage shall not vary more than 1mVRMS with 10mV P-P to 10MHz periodic and random deviation.

d. Temperature Coefficient. The power supply temperature coefficient should be 0.03 percent per degree C.

e. Operating Temperature. The operation temperature of the power supply is -20°C to +50°C rated current to 60°C derated 10% to 71°C derated 25%.

f. Storage Temperature: The storage temperature of the power supply is -55°C to +85°C.

g. Collateral Power Output Indicator: A collateral power output indicator shall be provided for monitoring the output voltage and current. This output power indicator shall be required to provide a relative, convenient, monitor to directly track the output power within an accuracy of ±10 percent.

h. Recovery Time: The recover time for the power supply to go from no-load to within 50. mV of full-load is a maximum of 50 microseconds.

i. Remote Sense: The power supply has terminal sensing to provide correction of up to 0.5 volt load lead drop.

2. Type and Size.

a. Design and Construction. Unless otherwise specified herein, the equipment shall comply with the Type II design and construction requirements specified in MIL-T-28800.

b. Solid State Construction. The equipment shall be of solid-state modular miniaturized construction. Electron tubes shall not be used, except that high power RF signal production may necessitate the use of electronic vacuum tubes in the output states.

c. Receptacle and Connector Mounting. The connections are provided on barrier strip for jumper wire assembly. The connectors shall comply with MIL-T-28800 3.4.1.5.2.

d. Voltage Adjustment. All output voltage shall be externally adjustable ± 10 percent. The ± 15 VDC and the ± 5 VDC shall have a single tracking adjustment for each.

e. Accessibility. The equipment shall be constructed so subassemblies and chassis components can be removed without removing any other hardware subassembly, printed circuit card or component.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

f. Input Power Switch. The input power switch shall comply with Type III input switch requirements of MIL-T-28800, except that the switch shall break both sides of the power source, but not break the earth ground conductor circuit.

g. Fuses or Circuit Breakers. Fuses or circuit breakers shall comply with Type III requirements of MIL-T-28800, except that both sides of the input power line shall be equipped with fuses or circuit breakers.

3. Dimensions, Weight and Mechanical Stability.

a. Weight. The unpacked weight of the power supply, including all accessories, shall not exceed 18 pounds.

b. Dimensions. The maximum dimensions of the power supply, including all accessories, installed in the Style E enclosure as referenced in MIL-T-28800 shall not exceed 7 1/2 inches in width, 4 25/32 inches in height and 9 3/8 inches in depth.

CERTIFICATION. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. Bid samples from bidders will be tested in accordance with the salient characteristics of this Commercial Item Description at San Antonio ALC, Kelly AFB, Texas 78241.

OPERATIONAL INSTRUCTIONS/MAINTENANCE MANUAL. The contractor shall prepare an operator's manual according to the provisions of MIL-M-38797 for all equipment delivered under terms of this contract.

COMMERCIAL PUBLICATIONS. Commercial publications may be submitted to fulfill Air Force documentation requirements. These publications require technical order numbering and must be referenced in the system level publication. Such commercial data must be prepared in accordance with MIL-M-7298C. Two copies of each commercial manual proposed shall be submitted for Air Force evaluation and approval. Commercial publications shall be reviewed by the Technical Order Management Office (TOMO) before final acceptance by the Air Force. If modifications are performed on Air Force equipment, the contractor shall provide updating manual changes to meet Air Force standards. All applicable reproduction rights for government use must accompany submittals.

REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

PACKAGING, PACKING AND MARKING. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with national motor freight classification and uniform freight classification. Shipping containers shall be marked as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.

INTENDED USE. The equipment shall be designed for use at Air Force Base Depot Precision Measuring Equipment Laboratories.

KNOWN ACCEPTABLE PRODUCTS:

Manufacturer	Model	NSN
Todd Products Corp.	P/N Q5A-15A-5A0V	6130-01-122-8713DQ

"Product no longer available".

Custodian:
Air Force - 99
Army - ER

Preparing Activity:
Air Force - 82

Reviewer:
Navy - SH
DLA - GS

Project 6130-0258

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:46Z
Check the source to verify that this is the current version before use.