COMMERCIAL ITEM DESCRIPTION

SPOTLIGHTS, AUTOMOTIVE, ROOF-MOUNTED

The General Services Administration has authorized the use of this Commercial Item Description in preference to MIL-S-4510, Type I, Class A, Size 2.

Scope. This commercial item description covers 12 volt roof-mounted spotlights that use PAR 46 sealed beam lamps. They are used on trucks, utility service vehicles, construction equipment, wreckers/tow trucks and snow plows.

Applicable documents. The following documents are referenced in this commercial item description.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE J575 - Tests for Motor Vehicle Lighting Devices and Components.
SAE J591 - Spot Lamps.
SAE J760 - Dimensional Specifications for General Service Sealed Lighting Units.

(Copies of publications may be obtained from the Society of Automotive Engineers, Inc, 400 Commonwealth Drive, Warrendale, Pennsylvannia 15096.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B 456 - Electrodeposited Coatings of Copper Plus Nickel Plus Chromium and Nickel Plus Chromium.

(Copies of publication may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvannia 19103.)

Salient characteristics. The spotlight shall be designed to meet SAE J591 and perform under specified tests cited in SAE J575.

1. Components. The spotlight shall consist of lamp housing, support arm and roof sealing gasket, control arm and handle, switch and electric wiring, and PAR 46 sealed beam screw terminal lamp per SAE J760. The lamp housing shall position PAR 46 lamp horizontal centerline 6½ inches above the face of the mounting flange on the support arm. The control handle shall be 6 inches below the surface of the mounting flange on the control arm to provide the movement of the lamp in an azimuth thru an arc of not less than 270 degrees and in elevation from vertical to not less than 35 degrees below horizontal. The switch on or near the control handle and electric wiring shall be capable of meeting load demands of 20 amperes in a 12 volt circuit.

2. Mounting instructions and hardware. Mounting instructions, including required templates, mounting screws or bolts of sufficient length to fasten mounting flange to panel 1/8 inch thick, and self-locking nuts and lock-washers, shall be furnished and packed with each light.

3. Finish. All parts shall be copper/nickel/chrome plated per ASTM B456 with a bright finish of service condition 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:47Z
Check the source to verify that this is the current version before use.

4. Marking. A nameplate shall be permanently fastened to the lamp housing, approximately 180 degrees from the mounting, containing the following information:

a. Sealed Beam Lamp Trade Number (see Table I)

b. Voltage and Power Rating

c. Manufacturer's Part Number

d. Manufacturer's Name

5. Style. The style will be designated per sealed beam lamp trade number from Table I. The basic number with no designation will be supplied with the 4435 lamp.

TABLE I. Sealed beam trade numbers and operating characteristics.

Trade number	Design volts	Watts	Nominal C.P.	Beam spread (degrees)		Rated life* (hours)
				horiz	vert	
4435	12.8	30	75,000	5°	5°	100
4537-2	13	100	200,000	11°	6°	25
H7635	12.8	50	160,000	6¼°	4°	100
4436R	12.8	35	9,000	10°	4°	300

*At design volts.

Known acceptable product(s).

The following product(s) are known to meet the requirements of this CID.

Manufacturer	Part number
Unity Manufacturing Company 1260 N. Clybourn Ave. Chicago IL 60610 Phone 312/943-5300	275

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to initial delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Packing, packaging and marking. The items shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Shipping containers shall be marked as specified in the contract or order.

Custodians:
Air Force - 99
Navy - YD
Army - ME

Preparing activity:
Air Force - 82

(Project: 6220-0278)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:47Z
Check the source to verify that this is the current version before use.