[METRIC]
A-A-843E
June 17, 1993
SUPERSEDING
A-A-843D
January 21, 1993

COMMERCIAL ITEM DESCRIPTION

T-SQUARE(WOOD, WOOD AND PLASTIC, STEEL AND PLASTIC)

The General Services Administration has authorized the use of this commercial item description as a replacement for Federal Specification GG-T-711F.

This description covers fixed head T-squares for general drafting practice, type, size and class as specified:

Type I - Fixed head.
Type II - Double head. (fixed and adjustable).

Class B - Opaque blade. With transparent edges, the blade shall be one continuous piece of hardwood or opaque plastic with continuous transparent working edges between 6 and 12 millimeters wide.

Class C - Transparent blade. One continuous piece of plastic with a flat black metal slat permanently bonded to both surfaces. Available in 75 centimeter lengths or greater.

Salient characteristics.

Dimensions. Sizes and dimensions of the T-squares shall be as shown on table I. The size of the T-square shall be determined by the length of the blade, and shall be exclusive of the portion of the blade attached to the head.

Blade			Head		
Length (cm)	Width (cm)	Thickness (mm)	Length (cm)	Width (cm)	Thickness (mm)
45.7	5.4	3	25.0	5.6	9.5
61.0	5.7	3	30.5	5.7	9.5
76.2	5.7	3	33.0	6.4	9.5
91.4	6.4	3	35.5	6.4	9.5
106.7	6.8	3	38.0	6.4	9.5
122.0	6.8	4	40.5	6.9	9.5
152.4	6.8	4	40.5	6.9	9.5

Table I - Blade and Head Dimensions

Tolerances.

Blade length -	± 2.5 cm	Head length -	± 2.5 cm
Blade width -	± 0.6 mm	Head width -	± 6.0 mm
Blade thickness -	± 1.0 mm	Head thickness -	± 2.0 mm

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

Configuration. The Type I head shall be one piece and shall be rigidly secured at right angles to the blade. The maximum perpendicularity between the head and the blade shall be 90 degrees ± 15 minutes. Type II shall be provided with the fixed head and an adjustable head attached to opposite sides of the end of the blade. Both types shall conform to the design used in commercial practice.

Wood. The wood shall be of a hardwood species most suitable for the respective parts and shall be thoroughly seasoned, straight grained, free from blemishes, knots and other defects.

Plastic. Plastic material shall be methacrylate, vinyl chloride, or cellulose acetate butyrate.

Metal. Metal parts shall be fabricated of corrosion-resistant material or be treated to resist corrosion.

Surfaces. All surfaces shall have a smooth and uniform finish; plastic shall be polished; wood surfaces shall have a suitable protective coating with a dull finish.

The hole, 12.7 ± 2 millimeters in diameter, shall be placed in the blade near the free end.

The free ends of hardwood blades shall be reinforced by inserted strips or bridges.

Workmanship. The T-square shall have no defects which may impair its durability, appearance or serviceability.

QUALITY ASSURANCE PROVISIONS.

Responsibility for inspection and tests. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Sampling. Sampling for visual inspection and testing shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified, Inspection Level II with AQL 2.5 percent defective for visual inspection and level S-2, AQL 1.5 percent defective for testing shall apply.

Inspection. Samples selected in accordance with the requirements herein shall be visually inspected to verify conformance to dimensional and workmanship requirements of the CID. Any departure from specified requirements may be grounds for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

physical degradation such as corrosion of metal parts or distortion of plastic

Tests. Samples for the straightness test shall be equal to the number taken for the inspection. Samples for the temperature test shall be not less than three samples.

Temperature Test. (Class B, methacrylate only). The T-squares shall be placed in a heating chamber and subjected to a temperature of plus 70 ±2 degrees C. for a period of 4 hours. They shall then be removed and allowed to return to room temperature and examined. If the adhesive between the blade and the transparent edge is affected in any way, the entire lot of T-squares shall be rejected.

Straightness test. Securely fasten a good grade of drawing paper on a drawing board. Drive two identical pins vertically into the drawing board, about 6 mm deep, and spaced approximately 12 mm less than the length of the blade. Place the ruling edge against the pins and draw a line along the ruling edge with a sharp pencil. Rotate the T-square 180 degrees, place the same ruling edge against the other side of the pins and draw another line along the ruling edge. Measure the distance between the two lines at increments not exceeding 0.25 mm multiplied by the length (in mm) of the T-square.

Regulatory requirements. In accordance with section 23.403 of the Federal Acqusition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversly affecting performance requirements or exposing supplier's employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Packaging and marking (DoD). Export packaging shall be specified when shipments are to overseas Department of Defense (DoD) consignees. Commercial packaging may be specified for shipments to DoD consignees within the Continental United States. When a supplier's normal packaging will satisfy the requirements for military packaging, it may be used.

Military packing. Each T-square shall be preserved and packed to protect against physical damage and deterioration in a logistic environment characterized by the following:

1. Multiple handling during transportation and intransit storage.
2. Shock, vibration, and static loading forces during worldwide shipment by all transport modes.
3. Uncontrolled warehouse storage for extended periods.
4. Weather exposure during shipment and intransit transfers.
5. Stacking loads during shipment and storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.

The transducer shall be tested in accordance with [illegible] / 8.17 Vibration

Quantities of T-square of like description destined to a single addressee may be unitized into one or more unit loads.

Copies of MIL-STD-105 can be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

NOTE: Purchaser shall specify:

NSN	6675-00-183-6487	Type I, Class B, 106.7 cm
	6675-00-183-6488	Type I, Class C, 152.4 cm
	6675-00-190-5272	Type I, Class B, 76.2 cm
	6675-00-514-3527	Type I, Class B, 122.0 cm
	6675-00-526-5938	Type I, Class B, 91.4 cm
	6675-00-191-1504	Type II, Class B, 45.7 cm
	6675-00-526-5936	Type II, Class B, 61.0 cm
	6675-00-191-1502	Type II, Class B, 91.4 cm

MILITARY INTERESTS:

Military Coordinating Activity:

Army - ME

Custodian

Army - ME

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:10Z
Check the source to verify that this is the current version before use.