MILITARY SPECIFICATION

ANTENNA AS-1425( )/GRC

This amendment forms a part of Military Specification MIL-A-55671A(EL), dated 29 September 1970.

PAGE 3

2.1 DRAWINGS: Change "SC-DL-561639" to "DL-SM-B-561639" and add "GL-SM-B-323315A, GAGES for AS-1425/GRC ANTENNA.

3.2 CONSTRUCTION, Line 2; Change "SC-DL-561639" to "DL-SM-B-561639".

3.3.1.1 SIMULATED WINDLOAD and VELOCITY: Delete

3.3.1.2 SIMULATED ICE LOAD: Delete

PAGE 4

3.3.1.11 TEMPERATURE, Line 5; Change last sentence to read: "At the conclusion of these tests the Antenna shall have no physical degradation which prevents it from meeting operational service or maintenance requirements and shall meet Tilt and VSWR requirements (See 3.3.1.6 and 3.3.1.7)."

3.3.1.12 HUMIDITY, Line 2; Change last sentence to read: "At the conclusion of this test, the Antenna shall not exhibit corrosion or physical degradation which prevents it from meeting operational service or maintenance requirements and shall meet Tilt and VSWR requirements (See 3.3.1.6, 3.3.1.7 and 4.17)".

3.3.1.13 DUST, Line 2; Change last sentence to read: "At the conclusion of this test, there shall be no dust penetration of the Antenna Assembly which prevents the proper electrical and mechanical operation of the Antenna and it shall meet Tilt and VSWR requirements (See 3.3.1.6, 3.3.1.7 and 4.18)".

3.7 INTERCHANGEABILITY: Add the following to the end of the sentence: "and GAGES GL-SM-B-323315".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:51Z
Check the source to verify that this is the current version before use.

PAGE 9

4.6 SIMULATED WIND LOAD and VELOCITY: Delete

4.7 SIMULATED ICE LOAD TEST: Delete

PAGE 12

4.15 HIGH TEMPERATURE TEST, Line 3; Change last sentence to read: "At the conclusion of the test, the Antenna shall have no physical degradation which prevents it from meeting operational service or maintenance requirements and shall meet Tilt and VSWR requirements (See 3.3.1.11, 4.10 and 4.11)".

4.16 LOW TEMPERATURE TEST, Line 4; Change last sentence to read: "At the conclusion of this test, the Antenna shall have no physical degradation which prevents it from meeting operational service or maintenance requirements and shall meet Tilt and VSWR requirements (See 3.3.1.11, 4.10 and 4.11)".

4.17 HUMIDITY TEST, Line 3; Change last sentence to read: "At the conclusion of this test, the Antenna shall not exhibit corrosion or physical degradation which prevents it from meeting operational service or maintenance requirements and shall meet Tilt and VSWR requirements (See 3.3.1.12, 4.10 and 4.11)".

4.18 DUST TEST, Line 2; Change last sentence to read: "At the conclusion of this test, there shall be no dust penetration of the Antenna Assembly which prevents the proper electrical and mechanical operation of the Antenna and it shall meet Tilt and VSWR requirements (See 3.3.1.13, 4.10 and 4.11)".

4.20 INTERCHANGEABILITY TEST, Delete "DESIGN" from last sentence. Add new sentence: "Unit(s) which fail to meet Gage Limits specified in GL-SM-B-323315 shall be considered not acceptable, and to have failed interchangeability requirements.

Custodian
ARMY-EL

Preparing Activity:
ARMY-EL
Project No. (5985-A368)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:51Z
Check the source to verify that this is the current version before use.