MIL-C-81446(AS)
AMENDMENT 1
1 JULY 1969

MILITARY SPECIFICATION

COUPLER, ATTITUDE INDICATOR CU-1466A/ASN

This amendment forms a part of Military Specification MIL-C-81446(AS) dated 15 September 1966, and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 1, Title: Delete "Type CU1466*/ASN" and substitute "CU-1466A/ASN."

Page 4, paragraph 3.5.1: Delete "(7) Revert to all-attitude mode at Bomb release."

Page 7, paragraph 3.5.3.5.1: Delete and substitute

"3.5.3.5.1 Tone Generator - The power supply module shall provide an audio tone output signal when pull-up voltage or tone warning voltage is applied. The tone generator shall have the following characteristics:

Frequency - 1200 ±120 cycles per second(1200 ±200 at temperature extreme)

Load range - 40 ohms to 30,000 ohms

Voltage output - Adjustable from 0.5 max. to 3.5 min. into 3000 ohm load."

Output regulation - With output set at 3.0V into 3000 ohm, voltage output into 40 ohm load will not be less than 1.5V.

Page 7: Add

"3.5.3.9.1 Low Voltage Protection - A circuit shall be contained within this relay module to detect a low input supply voltage and clamp the outer roll servo signal at zero for values of input voltage less than 60V AC."

Page 7: Add

"3.5.3.10.2 Vertical Pointer - A relay contact shall be included which controls the signal to the vertical pointer of the associated Attitude Director Indicator. The output of the Yaw-Roll module shall appear at the output to the vertical pointer upon application of pickle voltage and shall remain until either the pickle voltage is removed or yaw-cancel occurs. At other times a voltage is to be provided to hide the pointer."

Page 13, paragraph 4.4.3.3: Delete and substitute: "The Test Level used shall be in accordance with Test Level E of MIL-STD-781."

Page 13, paragraph 4.4.3.3.1: Delete.

Page 13, paragraph 4.4.3.4: Delete "Following the initial hot and cold tests of the one temperature cycle (see 4.4.3.3.1), the tests shall continue at the test level of paragraph 4.4.3.3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:25Z
Check the source to verify that this is the current version before use.