MILITARY SPECIFICATION
COMPUTER SET, NAVIGATION
AN/ASN-66(*)

This amendment forms a part of Military Specification MIL-C-81448(AS) dated 15 August 1966 and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 1, paragraph 2.1, under SPECIFICATIONS, Military: Delete

"MIL-C-172 Cases, Bases, Mounting and Mounts, Vibration (for use with Electronic Equipment in aircraft)"

Page 6, paragraph 3.3.9: Delete "Room ambient (25°C±5°C)" and substitute

"Room ambient +25°C (+15°C - 5°C)"

Page 6, paragraph 3.3.10.1, line 2: Delete

"Curve II"

Page 6, paragraph 3.3.12: Add

"(3) AC Power Variable 0-5V for panel lighting 800 ma"

Page 6, paragraph 3.3.12.1: Delete

"or provide from source within equipment itself"

Page 6, paragraph 3.3.12.1(1): Add, after "Category B"

"1 amp"

Page 9, Table 1, under "Scale Factor": Delete "400 cycles 28V" and substitute

"400 cycles 0-6V"

Page 9, Table 1, under "Maximum Rate of Change": Delete "7°/min" and "6048 ± 360 kts" and substitute respectively

"7°/sec" and "6989 ± 360 kts"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:25Z
Check the source to verify that this is the current version before use.

Page 11, Table 3, line 8, under "Synchro Type": Delete and substitute

"Two Bendix AY-503F-21 positioned to true bearing and two AY-533-25 positioned to true heading."

Page 11, Table 3, under "Accuracy": Delete "± 4%" and substitute

"± 0.4%"

Page 12, Table 3, under "Scale Factor": Delete "2nm/1°" and substitute

"2nm/Rev"

Page 13, Table 4: Add

"Note 1. The specified accuracies are based on two sigma values."

Page 14, paragraph 3.5.1.4(1): Delete and substitute

"(1) Chassis Assembly - This subassembly shall include the unit's main frame, the main wiring harness, lighting panel, destination switch servoed target relays, function switch, and an elapsed time indicator."

Page 15, paragraph 3.5.1.4(6): Delete and substitute

"(6) Null Detector - This module shall include the circuitry required to verify target memory insertion."

Page 17, paragraph 3.5.1.6: Add

"(5) Wait Light - This light shall indicate when any servoed target coordinate (latitude and longitude) has not reached its servoed null."

Page 17, paragraph 3.5.2.3: Delete and substitute

"3.5.2.3 Weight - This unit shall not exceed 23.25 pounds."

Page 18, paragraph 3.5.2.4: Add

"(10) Servo Amplifiers - Servo amplifiers shall provide the necessary amplification for the wind velocity and direction servos. The remaining system servo amplifiers are located on each electro-mechanical module where required."

Figure 2: Delete computer amplifier number "18740-1A"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:25Z
Check the source to verify that this is the current version before use.