MIL-F-60043A (AR)
Amendment 1
27 Dec 1978

MILITARY SPECIFICATION

FUZE, BASE, DETONATION, M62A2
METAL PARTS FOR

This amendment forms a part of Military Specification MIL-F-60043A (MU) dated 2 May 1968

Page 2

Paragraph 3.3, Delete this paragraph in its entirety and substitute the following:

"3.3 Position of firing pin.-The peripheral edge of the firing pin point shall not wobble or rotate beyond the limits of a 26 degree maximum cone whose diameter, at a location corresponding to the greatest length of the percussion plunger assembly, is .075 inch maximum, when tested as specified in 4.4.1".

Page 10

Paragraph 4.3.2.9, Delete Major 106 and substitute the following:

"106 Position of charge cavity to datums A and B.....gage 09006"

Add Major 108 as follows:

"108 Length of Shoulder, min.....gage 09021"

Add Major 109 as follows:

"109 Incorrect Angle of Charge Cavity.....gage 09020"

Page 11

Paragraph 4.3.2.10 - Add Minor 204 as follows:

"Minor 204 Reduced diameter both end incorrect.....Gage 10007"

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:06Z
Check the source to verify that this is the current version before use.

Page 13

Paragraph 4.3.2.13 - Major 106 - Delete "min" and substitute "max."

Page 14

Delete Major 115 and substitute the following:

"Major 115 Position of head pitch diameter to datums A and C.....Gage 10315"

Delete Major 116 and substitute the following:

"Major 116 Position of head pitch diameter to datum D.....Gage 13016"

Delete Major 117 and substitute the following:

"Major 117 Position of detonator holder to datums A and E.....Gage 13017"

Delete Major 120 and substitute the following:

"Major 120 Runout booster cup threads to datum A.....Gage 13020".

Add Major 126 as follows:

"Major 126 Position of retaining screw threads to slider shoulder cavity.....Gage 13042"

Add Major 127 as follows:

"Major 127 Slider Cavity centerline angle incorrect.....Gage 13043"

Page 15

Minor 213 Delete "Depth of booster cavity" and substitute "Depth of Booster Cavity to Datum Diameter.....Gage 13038"

Add Minor 217 as follows:

Minor 217 Runout of Booster Cavity to Datum Diameter.....gage 13043"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.

Page 16

Paragraph 4.3.3.1, last sentence delete "4.4.1" and substitute "4.4.2".

Paragraph 4.3.3.2, last sentence Delete "4.4.2" and substitute "4.4.1".

Page 17

Paragraph 4.4.1, Delete the last two sentences of this paragraph and substitute the following:

"Arming shall be evidenced by rotation of the firing pin on the falcrum to the armed (ready-to-fire) position. The peripheral edge of the firing pin point shall not wobble or rotate beyond the limits of a 26 degree maximum cone whose diameter, at a location corresponding to the greatest length of the percussion plunger assembly, is .075 inch maximum. Check manually to see that the firing pin functions."

Paragraph 4.4.3, Delete the second sentence and substitute:

"Test equipment specified in 4.3.4 shall be used."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1390-A211

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:06Z
Check the source to verify that this is the current version before use.