MILITARY SPECIFICATION

INTERROGATOR SET AN/APX-76B(V)

This amendment forms a part of Military Specification MIL-I-81453A(AS) dated 10 June 1977 and has been approved by the Naval Air Systems Command, Department of the Navy.

Title: Delete "Interrogator Set AN/APX-76A(V) and substitute "Interrogation Set AN/APX-76B(V)"

Page 1, paragraph 1.2, Classification: Delete "RT-868A/APX-76(V) and substitute "RT-868B/APX-76(V)". Delete "RT-988/A" and substitute "RT-988A/A". Make this same change throughout the specification.

Page 5: Delete "MIL-STD-781" and substitute "MIL-STD-781B"

Page 7: Add new paragraph:

"3.2.4 Electron Tubes - Electron tubes shall not be used except for the single tube amplifier in the switch-amplifier SA-1568A/APX-76(V)".

Page 7, paragraph 3.3.3.1 Operational Stability: Delete "225" and substitute "400".

Page 8, paragraph 3.3.3.3 Equipment Reliability in Mean Time Between Failures (MTBF): Delete "225" and substitute "400". Add: "The specified MTBF of the RT-988A/A is 560 Hours"

Page 8, paragraph 3.3.3.3.1, Delete and Substitute: "3.3.3.3.1 Reliability of Individual Items - Items for system calculations of 400 hours MTBF:

C-7383/APX-76(V)	47,600 hours
RT-868B/APX-76(V)	560 hours
SA-1568A/APX-76(V)	2,370 hours
SN-416A/APX-76(V)	3,680 hours

Page 25, paragraph 3.5.2.3.2, Delete and substitute:

"3.5.2.3.2 Transmitter Power Output - The transmitter shall be capable of delivering not less than 1500 watts, peak rf power (as averaged over an rf pulse) to the antenna front panel jack of the RT-868B/APX-76(V) over the entire range of environmental conditions specified herein at a frequency of 1030 ±0.2 MHz and at any duty cycle up to a maximum of 0.6 percent. At the extreme temperatures under specified environmental con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:26Z
Check the source to verify that this is the current version before use.

ditions a 1dB drop in output power will be acceptable. Under standard conditions (para 3.3.11) the specified operation at a duty cycle up to a maximum of 1 percent shall be provided. Operating tests for demonstration of equipment life and reliability shall be carried out at a maximum duty cycle of 0.6 percent. An adjustment shall be provided capable of reducing the transmitter power output by 3 ±1 dB in order to be able to suit the needs of a specific installation. This reduction in transmitter power shall be accomplished without degradation of receiver sensitivity. The transmitter performance shall not be affected by hot switching of an associated rf switch."

Page 27, paragraph 3.5.2.6.2(1), line 4: Delete "switch" and substitute "adjustment."

Page 29, paragraph 3.5.2.9 Controls, line 4: Delete "Shall reduce the power output in two steps of 2 ±1 dB each" and substitute, "Not Used. Maintained in highest power position".

Preparing Activity
NAVY-AS

Project No. 5895-N273

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:26Z
Check the source to verify that this is the current version before use.