MILITARY SPECIFICATION

NET, HELICOPTER CARGO CARRYING EXTERNAL 5,000 and 10,000 CAPACITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This performance specification establishes the design, test manufacture and acceptance requirements for the 5,000 (5K) and the 10,000 (10K) pound capacity external cargo net.

1.2 Classification.

5,000 lb capacity net P/N 6018-5
10,000 lb capacity net P/N 6018-10

2. APPLICABLE DOCUMENTS

2.1 The following documents shall form a part of this specification to the extent specified herein, Unless listed by date as of a particular issue, the latest issue in effect on the date of the contract shall be applicable. In event of conflict between documents referenced herein, and the contents of this specification, the contents of this specification shall be considered a superseding requirement.

SPECIFICATIONS

FEDERAL

QQ-P-416	Plating, Cadmium (Electrodeposited)
PPP-B-601	Box, Wood, Cleated-Plywood
PPP-B-636	Box, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Aviation Research and Development Command, ATTN: DRDAV-ERS, 4300 Goodfellow Boulevard, St. Louis, MO 63120, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

V-T-295	Thread, Nylon
DDD-L-20	Label for Clothing Equipage and Tentage (General Use)

MILITARY

MIL-C-7515	Cord, Nylon, Coreless
MIL-I-6868	Magnetic Particle Inspection
MIL-S-5000	Steel, Chrome-Nickel-Molybdenum (E4340) Bars and Reforging Stock
MIL-W-27265	Webbing, Textile Woven Nylon, Impregnated
MIL-P-116	Preservation, Methods of

STANDARDS

FEDERAL

FED-STD-595	Colors
FED-STD-751	Stitches, Seams, and Stitching

MILITARY

MIL-STD-1O5	Sampling Procedures and Table for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-1188	Commercial Packaging of Supplies and Equipment

DRAWINGS

USAAVRADCOM 6018	Net, Helicopter Cargo
USAAVRADCOM 6022	Net Repair Test Criteria, 5K and 1OK Helicopter Cargo

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2,2 OTHER PUBLICATIONS

AA-STD-l (TSARCOM)	Quality Acceptance Criteria for Magnetic Particle Inspection

(Application for copies should be addressed to the contracting officer, US Army Troop Support and Aviation Materiel Readiness Command, 4300 Goodfellow Boulevard, St. Louis, MO 63120).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Item Description. The net is a gridwork of elastomer material which gathers at its comers to envelop a cargo load. Through lifting legs, the gathered comers join to a single attachment apex fitting to be placed onto a helicopter external cargo hook.

3.1.2 Interface Definition. Interface of the net with the helicopter external cargo hook is accomplished by the design of the apex fitting.

3.1.3 Major Component List. No major components are involved in the net design.

3.1.4 Government Furnished Property. Bag, Aviator's Kit NSN 8460-00-606-8366, one for each 5,000 lb capacity production net. Case, Screen, Woodland, Radar Scattering NSN 1080-00-108-1155 or Case, Screen, Woodland, Radar Transparent NSN 1080-00-107-$563, one for each 10,000 lb capacity.

3.2 Characteristics.

3.2.1 Performance. The net assembly is designed for a minimum of 100 operations consisting of carrying cargo beneath helicopters under world-wide environmental conditions. Net P/N 6018-5 is capable of carrying 5,000 pounds and net P/N 6018-10 is capable of carrying 10$000 pounds.

3.2.2.2 Physical Characteristics.

3.2.2.1 Weights. The 5,000 lb capacity net assembly maximum empty weight shall not exceed 58 pounds. The 10,000 lb capacity net assembly maximum empty weight shall not exceed pounds. These weights de not include stowage containers.

3.2.2.2 Strengths. Metal parts, net mesh, and total net assembly strength requirements are given in Table I.

3.2.2.3 Common Parts. Both capacity net shall use the same apex fitting and the same lifting leg hooks. The retaining strap shall be made of the same material as the lifting legs.

3.2.3 Reliability. The net has been designed with a life based on condition rather than a finite service life based on time.

3.2.4 Maintainability. Each capacity net assembly, including the mesh cord, border cord, and lifting legs shall be manufactured capable o being repaired to full net performance capacity, if damaged in the field. The criteria for nets repairability is contained an drawing 6022.

3.2.5 Environmental conditions. The net has been designed to withstand climatic temperature and humidity extremes world-wide.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.

3.2.6 Stowage. Each net will be stowed in containers per para 3.1.4, as part of the delivered assembly. Cargo nets shall be clean and free of contaminants and folded neatly when placed into the Government furnished stowage Containers.

TABLE I

HELICOPTER EXTERNAL CARGO NET COMPONENT & ASSEMBLY STRENGTHS

ITEM	NET CAPACITY (LBS)	PROOF LOAD (LBS)	MINIMUM ULTIMATE BREAKING STRENGTH (LBS)
NET MESH & LIFTING LEG ASSY (HOOKS AND APEX EXCLUDED]	5,000		50,000 MIN
	10,000		90,000 MIN
NET ASSY DWG NO. 6018	5,000	14,500	
	10,000	29,000	
APEX FITTING DWG NO. 6019	5,000	29,000	50,000
	10,000	29,000	50,000
HOOK DWG NO. 6020	5,000	11,000	20,000
	10,000	11,000	20,000

3.3 Design and Construction. The design and consruction of the net shall conform to the following criteria.

3.3.1 Materials, Processes, and Parts.

3.3.1.1 Net Mesh/Border Cord Body. Net body shall be made of nylon cord per Table II. Intersection design shall not contain knots or additional materials added to the cord, such as weldments, patches or swages, not shall sewing be the primary means of holding the intersection together. The centerlines of the intersecting cords shall remain coplanar. Intersection strength shall be compatible with Table I.

3.3.1.2 Lifting Legs. The lifting leg straps shall be made of nylon webbing per Drawing 6018. Strengths must be compatible with requirements of Table 1.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.

3.3.1.3 Thread and Whipping Cord. Appropriate threads and whipping cord made in accordance with V-T-295 shall be selected to insure satisfactory performance, as specified herein. Thread, nylon, soft finish, Ticket #5, 3 ply Type I, Class I, Sub-Class A, shall be utilized.

3.3.1.4 Stitches. Stitches shall be Class 300 and accomplished in accordance with Fed Std 751 to insure satisfactory performance, as specified herein.

3.3.1.5 Nylon Webbing. Ends of all nylon webbing shall be seared.

3.3.1.6 Anti-Abrasive Treatment. The net body and border shall be given one coat of anti-abrasive treatment per Drawing 6018. Mesh and border cord furnished on reels for the net shall be uncoated. Lifting Legs, Part No. 6018-30 shall be treated per MIL-W-27265, Class R, prior to sewing and assembly onto net mesh border.

3.3.1.7 Load Zone. The net load zone shall be marked with a hollow-braided nylon cord, 1400 lb tensile strength, 142 feet per pound weight, color of yellow-orange, No. 33538 per Fed-Std-595. The marker cord shall be applied to the net mesh with a half hitch selvedging knot at each mesh intersection and the two free ends shall be secured with a double half hitch knot with a 5 to 6 inch back splice to eliminate fraying. The load zone outline shall be circumscribed by a 5 foot radius circle for the 5,000 lb capacity net and a 6 foot radius circle for the 10,000 lb capacity net. The load zone outline shall be centered on the net mesh planform within 10 inches of true net center.

3.3.1.8 Color. The 10,000 lb capacity net shall be lusterless black, No. 37038 per Fed-Std 595. The 5,000 lb capacity net shall be olive drabs No, X34087, per Fed-Std-595. Exceptions are the Apex Tether Cord, Part No. 6018-45, Cotton Buffer, Part No. 6018-25, and Thread, Part No. 6018-40 may be either black or olive drab per the above colors. The protective coating colors of metalware is acceptable.

3.3.1.9 Production Repair. No repair procedures shall be applied to production quantities to correct production defects.

3.3.2 Identification and Marking. The net shall be permanently marked with a label per Federal Specification DDD-L-20, Type VI, Class II, with identification part numbers, load capacity, manufacturer code and date of manufacture (month and year). The label shall be sewn to one of the four retaining straps. Nominal size shall be 1 3/4 inch wide by 5 inches long. Title and NSNs are NET, HELICOPTER CARGO EXTERNAL, 5,000 LBS, NSN 1670-01-058-3811; NET, HELICOPTER CARGO EXTERNAL, 10,000 LBS, NSN 1670-01-058-3810.

3.3.3 Workmanship. The nets shall conform to the quality established by this specification and documents referenced herein. The occurance of defects shall not exceed the acceptance criteria established herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

3.3.4 Safety. The net design has been safety engineered.

3.3.5 Human Performance/Human Engineering. The net design has undergone human performance/human engineering,

3.3.6 Standard of Manufacture. The standard of manufacture are specified by reference to Government and Commercial specifications,

3.4 Major Component Characteristics. The design does not lend itself to major component characteristics.

3.5 First Article Test. A first article test shall be conducted per Section 4 on components and assemblies as given in the following.

3.5.1 Net Assy, Part Numbers 6018-5 and 6018-10. One each size net assembly shall be strength tested, In addition, one 10,000 lb capacity net shall demonstrate original strength repairs that have been accomplished. One each size net shall be provided and used as a manufacturing standard per repair criteria given in drawing 6022.

3.5.2 Metalware. Apex fittings and hooks shall be tested in net assemblies and separately, as required. Parts supplied under contract as end items shall be tested only as separate items,

3.5.3 Mesh Cord and Border Cord. Cord furnished as bulk material shall be strength tested. Type XX cord, per Table II shall be evaluated by fabricating one complete 5,000 lb mesh/lifting leg assembly and testing. Type XXII cord per Table 11 shall be evaluated by fabricating into one complete 10,000 lb mesh/lifting leg assembly and testing. Also, the cord shall be fabricated into a complete mesh/lifting leg assembly to demonstrate ease of repair and original strength. If both Type XX and Type XXII cord per Table 11 is procured, only the 10,000 lb mesh/lifting leg assembly need be tested to demonstrate ease of repair aid original strength.

TABLE II

CORD, NYLON CORELESS

The nylon braided cord construction used to construct the net shall be per MIL-C-7515, cut with the following special criteria.

NET SIZE	COMPONENT	CORD TYPE
5,000	Net Body	TYPE XX with COL A exceptions
5,000	Net Border	TYPE XXII with COL B exceptions
10,000	Net Body	TYPE XXII with COL B exceptions
10,000	Net Border (used double)	TYPE XXII with COL B exceptions

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.

SPECIAL CRITERIA

CHARACTERISTIC	COL A	COL B
Breaking strength nominal (lbs)	4,500	7,000
Carrier	16	24
Yarn denier per carrier	20,160	20,160
Yam Ply	2-8	2-8
Ends per carrier	2-8	2-8
Picks per inch	3-5	4-6
Ft per pound minimum	30	14
Elongation minimum (%)	20	20
Nylon Type	6-6	6-6
Yarn Twist	See Note Below	See Note Below

NOTE: “S” twist yarns shall be used in the carriers that form “Z” twist picks in the braid. "Z” twist yarns shall be used in the carriers that form the “S” twist picks.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure suppliers and services conform to prescribed requirements.

4.1.1 Centificate of Compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of certification.

4.2 Classification of Inspection. The inspection requirements specified herein are classified as follows:

a. First Article (See 4.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

b. Quality Conformance (See 4.4)

c. Packaging (See 4.9)

4.3 First Article Inspection. The first article shall be subject to the inspections in 4.4.1, 4.5, and the tests in 4.6 and 4.8.

4.4 Quality Conformance Inspection. The inspections and tests comprising quality conformance inspection are identified in paragraphs 4.4.1, 4.5, and 4.6.1.

4.4.1 Magnetic Particle Inspection. Each hook and apex shall be magnetic particle inspected using methods of MIL-I-6868 and accepted or rejected using criteria of AA-STD-1.

4.4.2 Sampling

4.4.2.1 Inspection Lot. A lot shall consist of all nets made of the same materials, components and essentially under the same conditions and offered for acceptance and delivery at one time.

4.4.2.2 Test. For testing per para 4.6.1, a random sample of nets shall be selected from each lot in accordance with MIL-STD-105, inspection level S-2. The acceptance quality level (AQL) shall be 4.0.

4.5 Inspection. The net shall be visually and dimensionally inspected for the defects listed below.

4.5.1 Completed Net Assembly. Materials and components shall be visually and dimensionally inspected in accordance with all the requirements of referenced specifications, standards, and drawings. Inspection shall be in accordance with MIL-STD-l05, inspection level II. AQL. shall be 1.0 for major defects and 6.5 total defects per hundred units. Characteristics and classification of defects shall be as follows:

Examine	Defect	Classification Major	Minor
Cord (Table II)	Any cut.	x	
	Abrasion or chafed area.	x	
	Kinks, Knots or unevenly braided resulting in open places, breaks in continuity of braid, or soft spots, broken, or missing ends or picks.	x	
	Other type than specified.		
	Other color than specified.		

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T00:01Z
Check the source to verify that this is the current version before use.

Examine	Defect	classification Major	Minor
Webbing (Para 3.3.1)	Not specified type or class.	x	
	Not specified color.	x	
	Any hole, cut or tear.	x	
	Ends not seared.		x
Thread (Para 3.3.1)	Not specified type or size	x	
Hardware Dwgs : 6019 6020	Any missing.	x	
	Burrs or sharp edge.	x	
	Any area of rust or corrosion.	x	
	Malformed.	x	
Body intersections	Not as specified in pare 3.3.1.1.	x	
Construction and Workmanship	Any component missing.	x	
	Grease, Oil, pitch, resin, dirt and other foreign matter in or on surfaces of the cord or webbing.	x	
	Lumps and sharp edges on seared ends of webbing.		x
Marking	Omitted, incorrect, illegible, wrong location or otherwise not as specified		x
Net Weight	Not as specified in para 3.2.2.1,	x	
Net Dimensions	Not as specified in Dwg 6018.	x	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

4.5.2 Material and Component Inspection. Sample in accordance with para 4.5.1. Requirements of Table II shall be met and stitches shall be examined during manufacture, as specified below:

Examine	Defect	classification Major	Minor
Stitches	Wrong class.	x	
	Missing or incomplete row of stitches.	x	
	Needle chews or bunched stitches.	x	
	Thread breaks, bobbin runouts, skipped stitches and runoffs not overstitched, restitched or back-stitched.	x	
	Ends of stitches not backstitched or secured as specified.		x
	Tension loose, resulting in 8 loose top or bobbin thread, or tight tension puckering of material at stitch line.	x	

4.5.3 Embrittlement Relief Testing. The hooks and apex fitting drawings which require heat treatment to tensile strengths in the range of 170,000 - 190,000 psi also require cadmium plating per QQ-P-416. In accordance with paragraphs 3.2.8, 4.4.3.4, 4.4.4.3, and 4.5.4 of QQ-P-416, embrittlement testing shall be performed on four test samples or test specimens prepared per paragraph 4.494.3 and representative of each cadmium plating lot. The load specified shall be applied for 200 hours and lots accepted if there is no evidence of cracks or fracture at the conclusion.. If actual hooks and apex fittings are used in this tests such hooks and apex fittings shall not be counted in the deliverable quantity. These test samples or specimens together with the certified reports shall be available for review by the Government inspector.

4.6 Tests. The nets shall be capable of reaching proof and ultimate loads without repairs being made during the test. Tests shall be as follows:

4.6.2 Proof load. Proof loads requirement are given in Table I, Section 3. No failures are permitted.

4.6.1.1 Metalware. The apex fitting and hook shall be loaded to proof loads and held for 30 seconds minimum. Load application shall be per Drawings 6019 and 6020. The same parts may be used in the Net Assy proof load test specified in the following paragraph.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.

4.6.1.2 Net Assy, Part No's. 6018-5 and 6018-10. Application of the proof loads shall be by placing appropriately dense weights within the net load zone as defined in Section 3, Cotton duck cloth (6-12 oz) or equivalent, may be placed between the weights and net mesh to aid in equalizing load pressure and reduce sharp edge abrasion from the weights. The load shall be lifted slowly and held free of ground for 5 minutes.

4.6.1.3 Mesh Cord and Border Cord. The cord shall be tested as mesh/lifting leg assemblies per Section 3. Load application shall be as in paragraph 4.6.2.2.

4.6.2 Ultimate Load. Ultimate load requirements are given in Table 1, Section 3. No failures are permitted.

4.6.2.1 Metalware. The apex fitting and hook shall be loaded until destruction occurs. The metalware shall be tested separate from the mesh/lifting leg assembly. Load application shall be per Drawings 6019 and 6020.

4.6.2.2 Mesh/Lifting Leg Assembly. The net metalware shall not be included in the mesh assembly ultimate load strength test. Suitable metalware shall be substituted. Load application shall be per paragraph 4.6.1.2 and in accordance with the following schedule:

	LOAD INCREMENT	
	5,000 lb Net Capacity (lb)	10,000 lb Net Capacity (lb)
Start	14,500	29,000
2nd Lift	30,000	70,000
3rd Lift	40,000	80,000
4th Lift (Ultimate Loads)	50,000	90,000

The load shall be held free of ground for 5 minutes at each load level. At ultimate load, there shall be no loss of load through the net. The mesh border and lifting leg shall not fail. Individual mesh cords may fail, but no cascade of adjacent mesh cord failures shall occur. Loads at failure shall be recorded. Loading in excess of ultimate loads to destruction is not required.

4.6.3 Net Repairability Test. One each capacity net, after proof load testing per paragraph 4.6.1, shall be subjected to destruct damage to the fabric parts (i.e., torn, complete severance, abrasion to the mesh intersection, border cord and lifting legs) prior to testing for repairability.

4.6.3.1 The repairability of the damaged net shall be demonstrated during First Article evaluation by using the Net Repair criteria of Drawing 6022 and para 3.5.

4.6.3.2 Each capacity net shall be strength tested in accordance with paragraphs 4.6.1 and 4.6.2 (see note 6.1.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

4.7 Failures. Failure of any net part or component during the tests except as specified herein shall be cause for rejection. Apart or component is considered to have failed, if after once having functioned properly, it no longer functions properly or is defective. All failures will be recorded.

4.8 Design Demonstration. The nets shall be demonstrated to verify that a typical intersection lies in one plane per Section 3.

4.9 Examination of Packaging. An examination shall be made to determine compliance with the applicable packaging, packing, and marking requirements. The sample unit shall be one container fully prepared for delivery, except that it need not be sealed. Examination for closure defects shall be made of containers fully prepared for delivery. Characteristics to be examined and the defects applicable thereto shall be specified below:

Examine	Defects
Marking (interior and exterior container)	Missing, incomplete, incorrect, illegible; or improper size, location, sequence or method of application,
Contents	Component missing, damaged, defective or otherwise not as specified.
Workmanship	Contents not snug fit in container; incomplete or improper application of tape; loose strapping or inadequate stapling; incomplete closure of containers; bulging or distortion of containers.

5. PACKAGING

5.1 Packaging. Packaging shall be Level A, B, at Commercial, as specified (see 6.1.6).

5.1.1 Level A. Each net assembly stowed as specified in para 3.2.5 shall be packaged per Method III of MIL-P-116, in a close-fitting box conforming to PPP-B-601, overseas type, style 1.

5.1.2 Level B.

5.1.2.1 Cargo net 5,000 pound capacity. Each net assembly stowed as specified in para 3.2.5 shall be packaged per Method III of MIL-P-116, in a close-fitting box conforming to PPP-B-636, W5s or W5c. Closure shall be in accordance with Method V of the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

5.1.2.2 Cargo net 10,000 pound capacity. Each net assembly stowed as specified in para 3.2.5 shall be packaged per Method III of MIL-P-116, in a close-fitting box conforming to PPP-B-636, VIIc. Closure shall be in accordance with Method V of the appendix to the box specification.

5.1.3 Commercial. Each net assembly stowed as specified in para 3.2.5 shall be packaged in accordance with MIL-STD-1188.

5.2 Packing. Not required. The unit container shall serve as the shipping container. For marking purposes the level of pack shall be the same as the level of packaging.

5.3 Marking. Military levels of protection shall be marked in accordance with MIL-STD-129. Commercial packaging shall be marked in accordance with MIL-STD-1188.

6. NOTES

6.1 Ordering Data. Procurement documents shall specify:

6.1.1 Title, number and date of this specification.

6.1.2 Quantities and identity of components or total assemblies being procured.

6.1.3 Time frame required for production deliveries.

6.1.4 Whether or not a pre-production First Article Test is required for any component or assembly.

6.1.5 Time frame required for pre-production models,

6.1.6 Level of packaging and packing required.

6.1.7 See Section 3.1.4 for Government Furnished Material.

6.1.8 The net repairability test of 4.6.3 may be waived at the discretion of the procuring activity in instances of follow-on procurement from the same supplier.

Custodians:

Army - AV
Navy - AS

Review Activities:

Navy - MC

Preparing Activity:

Army - AV

Project No. 1670-0661

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-N-58106

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

HQ, US Army Aviation Research and
Development Command
ATTN: DRDAV-ERS
4300 Goodfellow Boulevard
St. Louis, Missouri 63120

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:01Z
Check the source to verify that this is the current version before use.