MIL-R-81443 (AS)
Amendment 2
28 March 1968

Superseding
Amendment 1
28 September 1967

MILITARY SPECIFICATION

RECEIVER-TRANSMITTER, RADIO RT-793/ASQ and RT-793A/ASQ

This amendment forms a part of Military Specification MIL-R-81443(AS) dated 15 Aug. 1966 and has been approved by the Naval Air Systems Command, Department of the Navy.

Page 1, Specification Title: Delete and substitute the title of this amendment

Page 1, Paragraph 1.1: Add

"(5) Communication by means of AM radio telephone (A-3) when used in conjunction with Juliet-28 equipment."

Page 1; Paragraph 1.2: Add

"Juliet-28 equipment"
"Control, Radio Set C-8057/ARC"

Page 6, Paragraph 3.4.3: Add

"When an RF input of 4 microvolts, (open-circuit) modulated 30% at 1000 cps is applied, the signal plus noise-to-noise ratio of the auxiliary audio and the auxiliary guard audio shall be 6 db or greater."

Page 6, Paragraph 3.4.5: Add

"The overall selectivity of the RT-793A/ASQ for use with Juliet-28 shall be:

6 db	80 kc min.
60 db	150 kc max."

Page 7, Paragraph 3.4.8.1: Add

"The auxiliary guard audio shall have an output of 0.15 to 0.45 volts when terminated with a 600 ohm load for any input level between 10 and 10,000 microvolts modulated 30% at 1000 cps."

Page 7, Paragraph 3.4.8.3: Delete and substitute

"Auxiliary Circuit - The auxiliary circuit shall deliver only signals detected by the variable frequency receiver. When a 1000-microvolt signal modulated 30% at 1000 cps is applied, the output shall be at least 0.25 volt for a 20,000 ohm resistive load, and when the modulation frequency is varied from 70 to 7000 cps, the output for any frequency in the range shall be within $\pm$ 3 db of the output obtained at 1000 cps. The response of the RT-793A/ASQ, for use with Juliet-28, shall not vary more than +4

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:25Z
Check the source to verify that this is the current version before use.

Page 7, Paragraph 3.4.8.3: Delete and substitute (Continued)

to -4 db from that obtained at 1000 cps, when the input is varied from 70 cps to 20,000 cps."

Page 7, paragraph 3.4.9: Change the third sentence "3 db" to "5 db".

Page 8, Paragraph 3.4.11.1: Change fourth paragraph "the transmitter" to "the RT-793/ASQ." Add last sentence.

"Modulator response for the RT-793A/ASQ for use with Juliet - 28.

Frequency cps	Relative Output in db
100	-5 or lower
300	+4 to -4
600	+4 to -4
1000	0 (Ref. level)
3000	+2 to -2
6000	+3 to -3
10,000	+4 to -4
20,000	+4 to -4"

Page 9, Paragraph 3.4.14: Add

"The auxiliary audio, and the auxiliary guard audio shall have a signal plus noise-to-noise ratio of at least 20 db when a 1000 microvolt signal modulated 30% at 1000 cps is applied."

*Page 9, Paragraph 3.4.17: Delete "100 milliseconds" and substitute "200 milliseconds".

Page 14, Paragraph 3.5.1.10.3: Add

"The auxiliary guard output shall be terminated in a 600 ohm nonreactive load which shall include means for measuring the audio output voltage."

Page 14, Paragraph 3.5.1.10.4, under "Carbon Microphone Input" and under "Dynamic Mike Input": Delete "150 - 10,000 cps" and substitute "150 - 20,000 cps".

Page 14, Paragraph 3.5.1.10.4: Add

"1.0 VRMS open circuit must be supplied when the RT-793A/ASQ is used with Juliet equipment."

*An asterisk preceding a page number denotes a change to be made to the specification which did not appear in the preceding amendment.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1968-301-519/3966

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:25Z
Check the source to verify that this is the current version before use.