MIL-T-52062D
14 August 1987
SUPERSEDING
MIL-T-52062C
25 October 1983

MILITARY SPECIFICATION

TRAP, MOSQUITO, LIGHT

This specification is approved for use by all Departments and Agencies of the Department of Defense (DoD).

1* SCOPE

1.1 Scope. This specification covers a mosquito light trap for attracting and collecting mosquitoes.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Defense (DoDISS) specified in the solicitation form a part of this specification to extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Biomedical Research and Development Laboratory, ATTN: SGRD-UBE-D, Fort Detrick, MD 21701-5010, by using the self-addressed Standard Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3740

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:06Z
Check the source to verify that this is the current version before use.

2.1.1 (cent'd)

SPECIFICATIONS

FEDERAL

QQ-S-781	Strapping, Steel, and Seals.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-636	Boxes, Shipping, Fiberboard.
PPP-B-640	Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-C-5541	Chemical Conversion Coating on Aluminum and Aluminum Alloys.
MIL-P-15024/6	Plates, Identification, Equipment.
MIL-G-20241	Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-P-23377	Primer Coating: Epoxy-Polyamide, Chemical and Solvent Resistant.
MIL-C-81706	Chemical Conversion Materials for Coating Aluminum and Aluminum Alloys.
MIL-S-81733	Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of U.S. Military Property.
MIL-STD-889	Dissimilar Metals.

2.1*2 Other Government drawings. The following Government drawings form a part of this specification to the extent specified herein.

DRAWINGS

U.S. Army Biomedical Research and Development Laboratory (USABRDL), MD

60075FD - Trap, Mosquito, Light.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the document which is DoD adopted shall be listed in the issue of the DoDISS specified in the solicitation.

ASTM D 3951 Commercial Packaging

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of the specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The mosquito light trap shall be in accordance with 60075FD (see 2.1.2) and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fit, the contractor shall provide tolerances within those prescribed on the drawings to ensure correct fit, assembly, and operation of the mosquito light trap. Unless otherwise specified in the contract or purchase order, any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available for inspection by the contracting officer or his designated representative (see 6.2).

3.2 First article When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Material. The material shall be as specified herein and on the applicable drawings (see 6.5).

3.3.1 Material deterioration and control The mosquito light trap shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environments to which the item may be exposed. The aluminum and aluminum alloy parts of the trap shall be treated with a

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3.3.1 (cent'd)

corrosion resistant coating in accordance with MIL-C-5541C, Class 1A and included in the Qualified Products List of Products Qualified under Military Specification MIL-C-81706, Class 1A, Form I (Liquids), Method C (Immersion).

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a coat of epoxy primer conforming to MIL-P-23377, or corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against galvanic corrosion could also be obtained by exclusion of the electrolyte, if feasible.

3.4 Performance. When connected to a 3-wire, 115-volt, alternating current (AC), 60-Hertz power source, the mosquito light trap shall operate without failure; and the light bulb shall cut on and off with the activation and deactivation of the photocell (see 4.5.2.1).

3.5 Identification markings. The mosquito light trap shall be identified in accordance with MIL-STD-1301 The marking shall be applied to the mosquito light trap on plates conforming to MIL-P-15024/6, type B, style III.

3.6 Workmanship. The mosquito light trap shall be clean and free from sand, dirt, fins, sharp edges, pits, flux, cracks, or harmful extraneous material. Welds and bolted connections shall be sound.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance and all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other Tactilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.1.2 Disassembly Inspection Failure of any examination or test by the first article trap shall be cause for disassembly, in the presence of a Government representative, of the first article to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined . in detail for compliance with. this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship Parts not

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:06Z
Check the source to verify that this is the current version before use.

4.1.2 (cent'd)

complying with such requirements shall be rejected and shall be cause for rejection of the first article, Reassembly with replacement parts and retesting shall be the responsibility of the contractor.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article mosquito light trap shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article mosquito light trap shall be tested as specified in 4.5.2. Failure of the test shall be cause for rejection or for performance of the disassembly inspection specified in 4.1.2.

4.4 Quality conformance inspection

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105, inspection level II for examination, and inspection level II for tests.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. The acceptable quality level (AQL) shall-be 2.5 percent defective for major defects and 6.5 percent for minor defects.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. The AQL shall be 4.0 percent defective.

4.5 Inspection procedure

4.5.1 Examination The mosquito light trap shall be examined as specified herein for the following defects:

Major

101. Material not as specified.
102. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operating environments.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

4.5.1 (cent'd)

103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
104. Contractor does not have documentation available for identification of material, material finishes, or treatment.
105. Dimensions not as specified.
106. Components missing, damaged, defective, or not as shown on the drawings.
107. Any design characteristics not as specified.
108. Workmanship not as specified.

Minor

201. Identification marking missing, incomplete, or illegible.
202. Treatment and painting not as specified.

4.5.2. Test.

4.5.2.1 Operation. Connect the mosquito light trap to a 115-volt AC 60-Hertz power source. "During continuous operation of not less than 120 hours, subject the trap to a cycle of 20 minutes light and and 20 minutes dark. Inability of the mosquito light trap to perform as follows shall constitute failure of this test:

a. Inability of the light to illuminate.

b. Inability of the fan to rotate at 1,650 revolutions per minute and produce a down draft.

c. Inability of the photocell to respond to changing light conditions.

4.5.2.2 Assembly and disassembly The mosquito light trap shall be assembled for operation, to include extension of the body, lid support rods, legs, attachment of the collection assembly, connection of the power cord, and disassembled 25 times. At the end of each test, all components shall be examined for fatigue and failure. Component failure or fatigue, to include welds, solder points, screws, bolted connections, sewn seams, and nylon mesh fabric shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a complete pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with hfIL-STD-105, inspection level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:06Z
Check the source to verify that this is the current version before use.

4.6.1.3 Examination Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. The AQL shall be 2.5 percent defective.

109.	Materials and containers not as specified for level A or B. Each incorrect material or container shall constitute one defect.
110.	Mosquito light traps not disassembled for level A.
111.	Components not cushioned or blocked as required for level A or
112.	Box not closed and sealed as specified for level A.
113.	Gross weight exceeds the weight limitations of the box specifications, for level A or B.
114.	Strapping not as specified for level A.
115.	Marking missing, illegible, incorrect, or incomplete for level A, B, or commercial.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2.1).

5.1.1 Level A. Each disassembled mosquito light shall be placed in a close-fitting box conforming to PPP-B-636, W6c, or W5c, style optional. The components shall be arranged within the box in a manner to secure the minimum cube and shall be cushioned or blocked, as required, to prevent free movement or damage to the components. The box shall be closed and sealed as specified for method V in the appendix to the box specification.

5.1.2 Commercial. Each disassembled mosquito light trap shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2.1).

5.2.1 Level A. Mosquito light traps, preserved as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. The strapping shall conform to QQ-S-781, class 1, type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2.1), strapping shall be finish A.

5.2.2 Level B. Mosquito light traps, preserved as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, V3c, V1c, V13, or V15c, style optional or PPP-B-640, class, style optional. The gross weight or size shall not exceed the limitations of the applicable box specification.

5.2.3 Commercial. Mosquito light traps, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

5.3.1 Military. Marking for military levels of production (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with ASTM D 3951,

6. NOTES

6.1 intended use. The mosquito light trap is a sampling device used to determine density of mosquito populations and the species of mosquitoes. These data are for establishing mosquito control measures and determining the effectiveness of the control measures.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Required data will be made available unless otherwise specified (see 3.1.1).

c. When a first article is required for inspection and approval and number of units required (see 3.2).

d. Degree of preservation and degree of packing required (see 5.1 and 5.2).

e. When other than finish B strapping is required (see 5.2.1).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraph:

Paragraph Number	Data Requirement Title	Applicable DID Number	Options
6.4	Commercial Manuals	DI-M-4022C	

(Copies of Data Item Descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publication and Forms Center, or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it will be tested and approved under the appropriate provisions of paragraph 7-104.55 of the DAR. The first article may be a standard production item from the contractor's current inventory as specified in 4.3. The first article should consist of the number of units specified (see 6.2). The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations tests, and approval of the first article.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts list, and contractor's maintenance and operation manual to be furnished with each mosquito light trap.

6.5 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.3).

6.6 Subject term (keyword) listing.

Blower
Fan
Light
Mosquito
Mosquito light trap
Photocell
Trap
115-volt alternating current

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - MD
Navy - YD
Air Force - 99

Review activities:
Army - MD
Navy - MS
Air Force - 84
DLA- CS

User activity:
Navy - MC

Preparing activity:
Army - MD

(Project 3740-0126)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

TRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in mitting comments and suggestions for improvements. All users of military standardization documents are invited to provide gestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and led. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the blems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an nowledgement will be mailed to you within 30 days to let you know that your comments were received and are being sidered.

TE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of cification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

ARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

ICIAL BUSINESS
ALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

HQDA (DASG-HCL)
Washington,DC 20310-2300

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.