MILITARY SPECIFICATION

WELDING MACHINES, ARC, DC, TRANSFORMER-RECTIFIER, ADJUSTABLE CONSTANT VOLTAGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers single operator, direct current, transformer-rectifier type, constant voltage 100 percent duty cycle welding machines.

1.2 Classification. This specification covers welding machines of the following sizes. The size supplied shall be as specified (see 6.2.1).

Size	Capacity
250	250 amperes
300	300 amperes
400	400 amperes
500	500 amperes
600	600 amperes
750	750 amperes
1000	1000 amperes
1200	1200 amperes
1500	1500 amperes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5297, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appering at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-W-45562 - Welding and Soldering Equipment, Supplies and Accessories, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

, FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing office, Washington> DC 20402.)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE

ANSI/NEMA EW 1 - Electric Arc-Welding Apparatus.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Commercial Packaging, Standard Practice for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First Article. When specified (see 6.2.1), a sample shall be subjected to first article inspection (see 4.3 and 6.2).

3.2 Design. The welding machine shall be new and one of the manufacturer's current models capable of welding by the consumable electrode, metal arc, gas shielded welding process, and the submerged arc welding process in accordance with the requirements herein. The machine shall be rated at 100 percent duty cycle and comply with NEMA Standard EW-1. The machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the machine. When only one system of measurements is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.2 Reclaimed materials. The machine may contain reclaimed materials provided such materials will not jeopardize the machine's intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.2.3 Energy efficiency. The welding machine and all its applicable components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

3.2.4 Safety and health requirements. Covers , guards, or other safety devices shall be provided for all parts of the welding machine that present safety hazards. The safety devices shall not interfere with the operation of the machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance and repair of the parts. All machine parts, components, mechanisms, and assemblies furnished on the machine, whether or not specifically required herein, shall comply with all of the requirements of OSHA 2206 that are applicable to the machine itself. Additional safety and health requirements shall be as specified (see 6.2.1).

3.2.5 Mercury restriction. The machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.6 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the machine.

3.2.7 Environmental protection. The machine shall be designed and constructed such that, under the operating, service, transportation and storage conditions described herein, the machine shall not emit materials hazardous to the ecological system as prescribed by Federal, state or local statutes in effect at the point of installation.

3.2.8 Interchangeability. To provide for replacement of worn or damaged parts, all parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification to the part or the machine.

3.2.9 Portability. The welding machines shall be portable, and shall be base mounted. Running gear, if required (see 6.2.1), shall be as specified by the procuring activity. The welding machines shall be provided with a lifting device attached directly to the framework of the machine. The device shall be conveniently located for handling by crane or hoist, and shall be capable of supporting 2-1/2 times the weight of the machine. The center of gravity of the entire unit shall be as low as is consistent with economical design.

3.2.10 Open circuit voltage. The open circuit voltage shall be within the range of from 20 volts or less to 50 volts or more for all sizes except size 1200 and size 1500. The range for size 1200 and 1500 shall be from 25 volts or less to 50 volts or more.

3.2.11 Temperature rise. The maximum allowable temperature rise of various parts of the machines for the given class of insulation used shall be in accordance with NEMA EW-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.2.12 Overtemperature protection device. An overtemperature protection device shall be provided that will interrupt the input power to the welding machine in event of overtemperature for the class of insulation used. Allowable temperatures shall conform with NEMA EW-1 for the given class of insulation used.

3.3 Construction. The machine shall be constructed of parts which are new, without defects and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects such as scale and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins , sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer’s commercial practice.

3.3.5 Painting. All surfaces to be painted shall be cleaned of all foreign matter. Unless otherwise specified (see 6.2.1), the machine shall be painted in accordance with manufacturer’s standard commercial practice.

3.3.6 Threads. All threaded parts used on the machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable “Detailed Standard” section referenced therein.

3.4 Components. The welding machines shall consist of, but not be limited to, the following components: Enclosure, transformer, rectifier, controls, and ventilation system.

3.4.1 Enclosure. The sheet metal enclosure shall be dripproof, so designed and constructed that liquid or solid particles falling on the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

enclosure from above, at angles up to 15 degrees from the vertical, shall not "interfere with the satisfactory operation of the equipment. Surfaces of all parts of the enclosure shall be free from sand, dirt, fins, sprues, scale, flux, or other harmful or extraneous materials. External surfaces shall be smooth, and all protruding edges shall be rounded or beveled and all other edges shall be free of burrs. Inlet and outlet electrical connections shall be clearly and permanently marked. All intake and exhaust openings shall be screened or shall be small enough to prevent entrance of trash or vermin. Ventilation openings shall be louvered or so designed to prevent vertical water spray that would interfere with the satisfactory operation of the machine from entering the enclosure.

3.4.2 Transformer. The transformer shall be of laminated core or shell type. The secondary circuit shall be thoroughly insulated from the primary. Insulation of transformer coils shall be a class B, F, or H insulation system in accordance with the requirements of NEMA EW-1. The temperature rise of the windings shall not exceed the limits for the applicable class as specified in NEMA EW-1. Insulation distances and clearances shall be as liberal as is economically practical in order to minimize the need for frequent cleaning. The transformer shall be rigidly mounted within the enclosure

3.4.3 Rectifier. The rectifiers shall be of the full wave type. Rectification shall be accomplished by means of silicon diodes of suitable size and design for the intended service. The rectifier shall be of a type which has had a satisfactory history of field service on general industrial arc welding. Temperature rise of the silicon diodes shall not exceed 110° C above 40° C ambient temperature when operated at rated output and duty cycle.

3.4.3.1 Solid state components. Solid state design shall be used throughout for electronic components. The use of selenium or other similar ageing devices is permitted only for voltage surge protection to other solid state components.

3.4.4 Controls.

3.4.4.1 Control panel. The control panel shall include contact-making devices, rheostats, switches, or other equipment necessary to provide adjustments to control the welding power. All welding controls shall be mounted on a recessed panel of the enclosure. All current-carrying parts, except welding terminals, shall be contained within the welding enclosure. The welding output terminals shall be located on the front of the welding machine. Terminals shall be not less than l/2-inch (12.7 mm)diameter studs, or receptacles with equivalent current carrying capacity. If receptacles are used, a pair of matching plugs suitable for attachment to the welding leads, shall be included. All adjusting devices of the control panel shall be provided with marked scales to designate a setting for repeat performances. Operation of adjustment controls shall be free from binding, and shall be so constructed of such materials and of such design that a fixed

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

setting will remain after extended exposure to adverse atmospheric conditions. Subject to ±10 percent for fluctuations in the primary power supply, voltage shall remain constant as set and not require continual readjustment to hold over a period of operation.

3.4.4.2 Voltage adjustment. The output voltage shall be adjustable in not more than five ranges. When accomplished in more than one range, the design shall be such that any voltage within the capacity of the machine can be obtained. Voltage control and adjustment may be any method yielding the desired results and not adversely affecting welding performance at any setting.

3.4.4.3 Adjustable slope. When specified (see 6.2.1), the welding machines shall have an adjustable slope control. The slope control shall be adjustable from a relatively flat to a relatively steep volt/ampere curve.

3.4.4.4 Current rise and violent start control. When specified (see 6.2.1), means shall be provided to control the rate of current rise and eliminate violent starts. This may be accomplished by use of inductance or other built-in circuitry.

3.4.4.5 Remote controls. When specified (see 6.2.1), the welding machines shall be equipped with a remote voltage control. The remote voltage control shall be a module of the control panel or a separate control box, and perform the voltage adjustment functions. The remote control shall be supplied with a multi-conductor cord that can be readily connected to the welding machine at a terminal strip or plugged into a suitable receptacle. The remote control shall have interconnecting cables with connections for extensions. The interconnecting cable shall be not less than 20 feet (6 m) long. The control panel shall have a multiple-conductor cord, keyed or polarized receptacle for connection of the remote voltage control cable.

3.4.4.6 Auxiliary power supply. The welding machines shall have an auxiliary power supply, with a parallel grounding receptacle outlet or terminal strip located in the control panel. The auxiliary power supply shall be 115 volt, 60 Hz, single phase, with not less than 1/2 KW rating for 250 and 400 sizes, and not less than 1 KW for larger sizes. The current and voltage rating of the auxiliary power supply shall be marked at the receptable location.

3.4.4.7 Voltmeter and ammeter. When specified (see 6.2.1), a voltmeter and ammeter shall be furnished. Indication of welding variables shall be provided by means of a panel-mounted voltmeter and ammeter. The voltmeter shall have a minimum range of O to 50 volts for machines of 1000 amperes or less, and O - 80 volts for 1200 and 1500 amperes size machine. The ammeter shall have a minimum range of O to 125 percent of current rating, with suitable shunt. The voltmeter and ammeter shall be not less than 2-1/2 inch size commercial type instruments.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.4.4.8 Spot welding control. When specified (see 6.2.1), the welding machines shall be furnished with a gas spot gun welding panel with an adjustable timer capable of automatically controlling the weld time for gas spotgun welding and other similar welding processes. The spot welding control may be a separate module from the power source.

3.4.5 Ventilation system. Adequate ventilation and cooling of all component parts to meet the duty cycle specified herein shall be provided by forced air. When specified (see 6.2.1), the ventilation shall be down-draft type. The cooling fan or fans shall have totally enclosed motors with permanently-lubricated bearings. The fan assembly shall be securely fastened to a rigid mount in such a manner to withstand vibration encountered in this type of equipment. Fan blades shall be of a material and design to prevent fatigue failure.

3.4.6 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to the requirements of this paragraph. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit. Each machine shall have fused safety disconnect switch or circuit breaker. The machine shall be initially wired for operation on 460 volts. An identified terminal for grounding the machine when it is installed shall be mounted in or near the disconnect switch.

3.5 ‘Performance. The welding machines shall be designed for welding by the consumable electrode, metal arc, gas shielded welding process, and the submerged arc welding process. Characteristics of the machine shall be such that a welder may easily strike and maintain a stable arc, using electrode wire of any size and type within the volt/ampere limits of the machine, without loss of arc more than once per minute.

3.6 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each welding machine. The nameplate shall contain the information listed below. If the welding machine is a special model, the model designation shall include the model of the basic standard welding machine and a suffix identified in the manufacturer’s permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer’s name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.7 Technical data. When technical data is required it shall be furnished in accordance with the requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. Workmanship of the welding machines and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.5 and all tests in 4.6. Failure of the item to pass the first article tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1) quality conformance inspection shall consist of at least the examination in 4.5 and the tests in 4.6. Failure of the item to pass the examination or tests shall be cause for rejection.

4.5 Examination. The machine and equipment shall be examined to determine compliance with the requirements specified herein.

4.6 Tests. Except as otherwise specified (see 6.2.1), all tests shall follow the procedures of NEMA EW-1.

4.6.1 High potential test. The welding machine shall be subjected to a high potential test as described in Testing Standards of NEMA EW-1. When the first article inspection is required, this test shall be performed after the rough handling test in 4.6.2.

4.6.2 Rough handling test. A chain or cable shall be attached to the lifting device of the welding machine. The welding machines shall be raised and then dropped to fall freely a distance between six inches (15.2 cm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

minimum and ten inches (25.4 cm) maximum upon a solid concrete slab. The drop shall be repeated so that the impact is made on each of the three lower edges of the machine. There shall be no damage to the welding machine as a result of these tests other than minor denting of the cited lower edges.

4.6.3 Open circuit voltage. When the welding machine is connected to the proper primary power supply, the open circuit voltage test shall be in accordance with 3.2.10.

4.6.4 Temperature rise test. With machine at room temperature, the temperature of the primary and secondary windings of the transformer shall be recorded. The welding machine shall be operated at rated load at 100 percent duty cycle until stable temperatures are obtained. The load tests are to be run with resistance loading. Temperature rise shall be in accordance with requirements of 3.2.11. The temperature rise of the rectifiers shall be recorded to determine compliance with requirements of 3.4.3.

4.6.5 Overtemperature protection device test. The transformer winding resistance and temperature shall be recorded. A variable load bank shall be connected to the output terminals of the welding machine and the machine energized. The load bank shall be adjusted to draw a load that will not damage the machine, but will cause overheating of the transformer windings thereby tripping of the overtemperature protection device is activated the test shall be immediately terminated and winding resistance shall be recorded within one minute from activation of overtemperature protection device. The temperatures shall be calculated from the recorder data. The calculated temperature at which the overtemperature protection device activated shall conform to requirements of 3.2.12.

4.6.6 Performance tests. The output leads of the welding machine shall be connected to a resistance load bank that is rated in excess of the maximum potential of the welding machine. The welding machine shall be operated through successive periods of ten minutes each in increments of 25, 50, 75 and 100 percent of rated output to determine the output performance of the machine. Disconnect the load bank and make two six-inch (15.2 mm) fillet welds using the Gas Metal Arc Welding (GMAW) process to demonstrate the arc stability of the machine. Evidence of difficulty in establishing or maintaining an arc during the welding shall constitute failure of test and rejection of welding machine.

4.7 Packaging inspection. Packaging shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Packaging, packing and marking. Unless otherwise specified, packaging, packing, and marking shall be in accordance with ASTM-D-3951. When specified (see 6.2.1), packaging, packing and special marking shall be accomplished in accordance with MIL-W-45562.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The constant voltage welding machines covered by this specification are intended for use in gas shielded metal arc welding process. The welding machines vary from the basic model for economy and simplicity, to the more sophisticated models with controls for slope, voltage, and prevention of current rise and violent starts.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification.

b. Size and capacity required (see 1.2).

c. When first article is required for inspection and approval (see 3.1).

d. If machine is required to be configured in a specific measurement system (US or SI), state required system) (see 3.2.1).

e. Additional safety and health requirements, if required (see 3.2.4).

f. Running gear, if required (see 3.2.9).

g. Painting, if different (see 3.3.5).

h. Adjustable slope, if required (see 3.4.4.3).

i. Current rise and violent start control, if required (see 3.4,4.4).

j. Remote controls, if required (see 3.4.4.5).

k. Voltmeter and ammeter, if required (see 3.4.4.7).

l. Spot welding control, if required (see 3.4.4.8).

m. Ventilation, down draft, if required (see 3.4.5).

n. Electrical system and input power supply if different (see 3.4.6).

0. Nameplate, if different (see 3.6).

P. First article inspection, if different (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026t0-23T04:35Z
Check the source to verify that this is the currentversion before use.

q. Quality conformance inspection, if different (see 4.4).

r. Tests, if different (see 4.6).

s. Level of packaging, packing and marking, if different (see 5.1).

6.2.2 Contract data requirements. All data requirements such as, parts lists, wiring diagrams, operating manuals, maintenance manuals, alignment and test results shall be requested on a DD Form 1423, Contract Data Requirements List, and shall be furnished in accordance with each specified DD Form 1664, Data Item Description as shown on the DD Form 1423.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test and approval of the first article.

6.4 Safety and health requirements. Paragraph 3.2.4 requires compliance only with those OSHA requirements that concern the machine itself. It does not require compliance with those OSHA requirements that concern "the machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, and heat. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual machines in the environment) the procuring activity is advised to analyze the existing machine requirements that will integrate the new machine into its future operating environment . The above, and any other additional safety and health requirements should be specified in detail under 6.2.1.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review Activities:
Army - AL
Navy - SH
Air Force - 84

User Activities:
Army - CE
Navy - YD, MC, AS

Preparing Activity:
DLA-IP

Project Number:
3431-0168

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEFENSE LOGISTICS AGENCY
Headquarters
Defense Industrial Plant Equipment Center
Memphis, Tennessee 38114-5297

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEFENSE LOGISTICS AGENCY

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-SSM
Memphis, Tennessee 38114-5297

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-80062C	Welding Machines, Arc, DC, Transformer-Rectifier, Adjustable Constant Voltage

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:35Z
Check the source to verify that this is the current version before use.