NOTICE OF
CHANGE

DOD-STD-35-133(MI)
NOTICE 1
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING DOCUMENT PREPARATION SYSTEM

SHIELDING, RFI, EMI

TO ALL HOLDERS OF DOD-STD-35-133(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-133(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	22 SEPTEMBER 1978	(Reprinted without change)	
2	18 SEPTEMBER 1992	2	22 SEPTEMBER 1978
3	18 SEPTEMBER 1992	3	22 SEPTEMBER 1978
4	22 SEPTEMBER 1978	(Reprinted without change)	
27	22 SEPTEMBER 1978	(Reprinted without change)	
28	18 SEPTEMBER 1992	28	22 SEPTEMBER 1978
29	18 SEPTEMBER 1992	29	22 SEPTEMBER 1978
30	18 SEPTEMBER 1992	30	22 SEPTEMBER 1978
31	18 SEPTEMBER 1992	31	22 SEPTEMBER 1978
32	22 SEPTEMBER 1978	(Reprinted without change)	
35	18 SEPTEMBER 1992	35	22 SEPTEMBER 1978
36	18 SEPTEMBER 1992	36	22 SEPTEMBER 1978
37	18 SEPTEMBER 1992	37	22 SEPTEMBER 1978
38	18 SEPTEMBER 1992	38	22 SEPTEMBER 1978
39	18 SEPTEMBER 1992	39	22 SEPTEMBER 1978
40	18 SEPTEMBER 1992	40	22 SEPTEMBER 1978
41	18 SEPTEMBER 1992	41	22 SEPTEMBER 1978
42	18 SEPTEMBER 1992	42	22 SEPTEMBER 1978
43	18 SEPTEMBER 1992	43	22 SEPTEMBER 1978
44	18 SEPTEMBER 1992	44	22 SEPTEMBER 1978
45	18 SEPTEMBER 1992	45	22 SEPTEMBER 1978
46	18 SEPTEMBER 1992	46	22 SEPTEMBER 1978
47	18 SEPTEMBER 1992	47	22 SEPTEMBER 1978
48	18 SEPTEMBER 1992	48	22 SEPTEMBER 1978

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-133(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A464)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for RFI and EMI Shielding.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found usefule in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
SHIELD, EMI	817001	MIL-G-47197	PRESSURE SEAL

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-G-47197	Gasket, Shielding, Electronic Oriented Wires Embedded in Silicone Rubber, Pressure Seal

STANDARDS

MILITARY

DOD-STD-35	Automated Engineering Document Preparation System
MIL-STD-1285	Marking of Electrical and Electronic Parts
MIL-STD-130	Identification Marking of U.S. Military Property

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM A 342	Permeability of Feebly Magnetic Materials
ASTM A 712	Electrical Resistivity of Soft Magnetic Alloys

Source: https://assist.dla.mil - Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

ASTM C 177	Thermal Conductivity of Materials by Means of the Guarded Hot Plate
ASTM D 412	Tension Testing of Vulcanized Rubber
ASTM D 991	Volume Resistivity of Electrically Conductive and Antistatic Elastomers
ASTM D 2240	Indentation Hardness of Rubber and Plastics by Means of a Durometer
ASTM E 10	Method of Test for Brinell Hardness of Metallic Materials
ASTM E 18	Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials
ASTM E 380	Metric Practice Guide

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, Pa. 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
7050	MAXIMUM WEIGHT PER FOOT. THE WEIGHT PER FOOT SHALL BE NOT GREATER THAN 7050 OUNCE(S).
7051	MAXIMUM WEIGHT PER FOOT. THE WEIGHT PER FOOT SHALL BE NOT GREATER THAN 7051 POUND(S).
7056	MAXIMUM WEIGHT PER 100 FEET. THE WEIGHT PER 100 FEET SHALL BE NOT GREATER THAN 7056 POUND(S).
7347	MAXIMUM WEIGHT PER 1000 FEET. THE WEIGHT PER 1000 FEET SHALL BE NOT GREATER THAN 7347 POUND(S).
7400	MAXIMUM WEIGHT PER METER. THE WEIGHT PER METER SHALL BE NOT GREATER THAN 7400 GRAM(S).
7401	MAXIMUM WEIGHT PER METER. THE WEIGHT PER METER SHALL BE NOT GREATER THAN 7401 KILOGRAM(S).
7407	MAXIMUM WEIGHT PER KILOMETER. THE WEIGHT PER KILOMETER SHALL BE NOT GREATER THAN 7407 KILOGRAM(S).

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
WEIGHT (CONT)	
MINIMUM WEIGHT PER UNIT (SELECT ONE)	
U.S. (SELECT ONE)	
(OUNCES)	6943
(POUNDS)	6944
SI (SELECT ONE)	
(GRAMS)	6945
(KILOGRAMS)	6946
ATTENUATION RATIO	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1700
AS FOLLOWS:	1702
MINIMUM ATTENUATION (RATIO)	1706
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1708
PER (DOC DES)	1710

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the currentversion before use.

CHAR CODE	STANDARD PARAGRAPH
6943	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6943 OUNCE(S).
6944	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6944 POUND(S).
6945	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6945 GRAM(S).
6946	MINIMUM WEIGHT PER UNIT. THE WEIGHT PER UNIT SHALL BE NOT LESS THAN 6946 KILOGRAM(S).
1700	ATTENUATION RATIO. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1700.
1702	ATTENUATION RATIO. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1706	THE ATTENUATION RATIO SHALL BE NOT LESS THAN 1706.
1708	ATTENUATION RATIO. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1708.
1710	ATTENUATION RATIO. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1710.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ATTENUATION RATIO (CONT)	
PER MIL-S-47235. (CONT)	
FLUX FIELD (SELECT ONE):	
(HERTZ)	1712
(KILOHERTZ)	1714
BREAKING STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1716
AS FOLLOWS:	1718
MINIMUM BREAKING STRENGTH (SELECT ONE)	
(POUNDS)	1720
(KILOGRAMS)	1722
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1724
PER (DOC DES)	1726
ELECTRICAL CONDUCTIVITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1728

Source: http://assist.daps.dla.mil - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1712	THE FLUX FIELD SHALL BE 1712 HERTZ.
1714	THE FLUX FIELD SHALL BE 1714 KILOHERTZ.
1716	BREAKING STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1716.
1718	BREAKING STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1720	THE BREAKING STRENGTH SHALL BE NOT LESS THAN 1720 POUND(S).
1722	THE BREAKING STRENGTH SHALL BE NOT LESS THAN 1722 KILOGRAM(S).
1724	BREAKING STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1724.
1726	BREAKING STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1726.
1728	ELECTRICAL CONDUCTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1728.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ELECTRICAL CONDUCTIVITY (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	1730
MINIMUM CONDUCTIVITY (SELECT ONE)	
U.S. (OHMS PER SQUARE INCH)	1732
SI (SELECT ONE)	
(SIEMENS PER SQUARE METER)	1734
(SIEMENS PER SQUARE MILLIMETER)	1736
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1738
PER MIL-G-47197.	1740
NUMBER OF TEST SPECIMENS (QUANTITY)	1742
SPECIMEN LENGTH (SELECT ONE)	
(INCHES)	1744
(MILLIMETERS)	1746
LOAD (SELECT ONE)	
(POUNDS)	1748
(KILOGRAMS)	1750

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1662	ELECTRICAL RESISTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1662.
1657	ELECTRICAL RESISTIVITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1658	THE ELECTRICAL RESISTIVITY SHALL BE NOT GREATER THAN 1658 OHMS PER CIRCULAR MIL PER FOOT OF LENGTH.
1660	THE ELECTRICAL RESISTIVITY SHALL BE NOT GREATER THAN 1660 OHMS PER SQUARE MILLIMETER PER METER.
1659	ELECTRICAL RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1659.
1661	ELECTRICAL RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM A 712.
1752	ELONGATION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1752.
1754	ELONGATION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1756	THE ELONGATION SHALL BE NOT LESS THAN 1756 PERCENT.

Source: https://assist.dla.mil - Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ELONGATION (CONT)	
AS FOLLOWS: (CONT)	
NECKING (PERCENT)	1758
LOAD (SELECT ONE)	
(POUNDS)	1760
(KILOGRAMS)	1762
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1764
PER (DOC DES)	1766
PER ASTM D 412.	1768
FLEXIBILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1800
AS FOLLOWS:	1802
NO EVIDENCE OF PHYSICAL DAMAGE.	1804
TENSILE STRENGTH SHALL NOT BE ADVERSELY AFFECTED.	1806

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1758	THE NECKING SHALL BE NOT LESS THAN 1758 PERCENT.
1760	THE LOAD SHALL BE 1760 POUND(S).
1762	THE LOAD SHALL BE 1762 KILOGRAM(S).
1764	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1764.
1766	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1766.
1768	ELONGATION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 412.
1800	FLEXIBILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1800.
1802	FLEXIBILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1804	THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
1806	THE TENSILE STRENGTH SHALL NOT BE ADVERSELY AFFECTED.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FLEXIBILITY (CONT)	
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1808
PER (DOC DES)	1810
MINIMUM BENDS THROUGH AN ANGLE OF 180 DEGREES OVER SPECIFIED RADIUS (QUANTITY)	1812
RADIUS (SELECT ONE)	
(INCHES)	1814
(MILLIMETERS)	1816
MAXIMUM BEND RATE (BENDS PER MINUTE)	1818
HARDNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1820
AS FOLLOWS:	1822

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1808	FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1808.
1810	FLEXIBILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1810.
1812	THE NUMBER OF BENDS THROUGH AN ANGLE OF 180 DEGREES OVER SPECIFIED RADIUS SHALL BE NOT LESS THAN 1812.
1814	THE RADIUS SHALL BE 1814 INCH(S).
1816	THE RADIUS SHALL BE 1816 MILLIMETER(S).
1818	THE BEND RATE SHALL BE NOT GREATER THAN 1818 BENDS PER MINUTE.
1820	HARDNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1820.
1822	HARDNESS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:

Supersedes page 39 of 22 SEPTEMBER 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
HARDNESS (CONT)	
AS FOLLOWS: (CONT)	
ANNEALED CONDITION (SELECT ONE)	
DUROMETER (VALUE)	1824
ROCKWELL (VALUE)	1826
*SCALE (LETTER)	1828
BRINELL (VALUE)	1830
MILL CONDITION (SELECT ONE)	
DUROMETER (VALUE)	1832
ROCKWELL (VALUE)	1834
*SCALE (LETTER)	1836
BRINELL (VALUE)	1838
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1840
ASTM E 10, BRINELL.	1842
ASTM E 18, ROCKWELL.	1844
ASTM D 2240, DUROMETER.	1846

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1824	THE ANNEALED CONDITION DUROMETER SHALL BE 1824.
1826 1828	THE ANNEALED CONDITION ROCKWELL HARDNESS SHALL BE 1826 OF THE 1828 SCALE.
1830	THE ANNEALED CONDITION BRINELL HARDNESS SHALL BE 1830.
1832	THE MILL CONDITION DUROMETER SHALL BE 1832.
1834 1836	THE MILL CONDITION ROCKWELL HARDNESS SHALL BE 1834 ON THE 1836 SCALE.
1838	THE MILL CONDITION BRINELL HARDNESS SHALL BE 1838.
1840	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1840.
1842	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM E 10.
1844	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM E 18.
1846	HARDNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 2240.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
INSERTION LOSS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2000
AS FOLLOWS:	2001
MINIMUM INSERTION LOSS (DECIBELS)	2003
MAXIMUM INSERTION LOSS (DECIBELS)	2005
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2007
PER (DOC DES)	2010
FIRST FREQUENCY (SELECT ONE)	
(MEGAHERTZ)	2012
(KILOHERTZ)	2014
SECOND FREQUENCY (SELECT ONE)	
(MEGAHERTZ)	2016
(KILOHERTZ)	2018
THIRD FREQUENCY (SELECT ONE)	
(MEGAHERTZ)	2020
(KILOHERTZ)	2022

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2000	INSERTION LOSS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2000.
2001	INSERTION LOSS. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2003	THE INSERTION LOSS SHALL BE NOT LESS THAN 2003 DECIBEL(S).
2005	THE INSERTION LOSS SHALL BE NOT GREATER THAN 2005 DECIBEL(S).
2007	INSERTION LOSS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2007.
2010	INSERTION LOSS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2010.
2012	THE FIRST FREQUENCY SHALL BE 2012 MEGAHERTZ.
2014	THE FIRST FREQUENCY SHALL BE 2014 KILOHERTZ.
2016	THE SECOND FREQUENCY SHALL BE 2016 MEGAHERTZ.
2018	THE SECOND FREQUENCY SHALL BE 2018 KILOHERTZ.
2020	THE THIRD FREQUENCY SHALL BE 2020 MEGAHERTZ.
2022	THE THIRD FREQUENCY SHALL BE 2022 KILOHERTZ.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
PERMEABILITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1848
AS FOLLOWS:	1850
MAXIMUM PERMEABILITY (GAUSS/OERSTED)	1852
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1854
PER ASTM A 342.	1856
SALT SPRAY/FOG	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6356
NO EVIDENCE OF CORROSION, PHYSICAL DAMAGE OR DEGRADATION OF PERFORMANCE.	6357
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6353
PER ASTM B 117.	6354
EXPOSURE PERIOD (HOURS)	4783

Source: http://assist.mil - Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1848	PERMEABILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1848.
1850	PERMEABILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1852	THE PERMEABILITY SHALL BE NOT GREATER THAN 1852 GAUSS PER OERSTED.
1854	PERMEABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1854.
1856	PERMEABILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM A 342.
6356	SALT SPRAY/FOG. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6356.
6357	SALT SPRAY/FOG. THERE SHALL BE NO EVIDENCE OF CORROSION, PHYSICAL DAMAGE OR DEGRADATION OF PERFORMANCE.
6353	SALT SPRAY/FOG. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 6353.
6354	SALT SPRAY/FOG. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM B 117.
4783	DURATION OF TEST SHALL BE 4783 HOUR(S).

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TENSILE STRENGTH	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1900
AS FOLLOWS:	1902
MINIMUM TENSILE STRENGTH (SELECT ONE)	
(POUNDS PER SQUARE INCH)	1904
(KILOPASCALS)	1906
MINIMUM PULL STRENGTH (SELECT ONE)	
(POUNDS)	1908
(NEWTONS)	1910
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1912
PER (DOC DES)	1914
PER ASTM D 412.	1916
THERMAL CONDUCTIVITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1641

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:05Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1900	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1900.
1902	TENSILE STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1904	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 1904 POUND(S) PER SQUARE INCH.
1906	THE TENSILE STRENGTH SHALL BE NOT LESS THAN 1906 KILOPASCAL(S).
1908	THE PULL STRENGTH SHALL BE NOT LESS THAN 1908 POUND(S).
1910	THE PULL STRENGTH SHALL BE NOT LESS THAN 1910 NEWTON(S).
1912	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1912.
1914	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1914.
1916	TENSILE STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 412.
1641	THERMAL CONDUCTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1641.

Source: https://assist.dla.mil/ - Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
THERMAL CONDUCTIVITY (CONT)	
REQUIREMENTS (CONT)	
AS FOLLOWS:	1649
MAXIMUM THERMAL CONDUCTIVITY (SELECT ONE)	
(BRITISH THERMAL UNITS PER HOUR PER SQUARE FOOT PER DEGREE FAHRENHEIT PER INCH)	1650
(WATTS PER METER KELVIN)	1652
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1651
PER ASTM C 177.	1653
VOLUME RESISTIVITY	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1918
AS FOLLOWS:	1920

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:05Z
Check the source to verify that this is the current version before use.