MILITARY STANDARD

AUTOMATED ENGINEERING

DOCUMENT PREPARATION SYSTEM

CONNECTORS, ELECTRICAL,

RECTANGULAR

TO ALL HOLDERS OF DOD-STD-35-69A(MI)

1. THE FOLLOWING PAGES OF DOD-STD-35-69A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	15 December 1978	(REPRINTED WITHOUT CHANGE)	
2	15 April 1983	2	15 December 1978
3	15 December 1978	(REPRINTED WITHOUT CHANGE)	
4	15 April 1983	4	15 December 1978
11	15 December 1978	(REPRINTED WITHOUT CHANGE)	
12	15 April 1983	12	15 December 1978
37	15 December 1978	(REPRINTED WITHOUT CHANGE)	
38	15 April 1983	38	15 December 1978
39	15 April 1983	39	15 December 1978
39A	15 April 1983	NEW PAGE	
39B	15 April 1983	NEW PAGE	
40	15 December 1978	(REPRINTED WITHOUT CHANGE)	
189	15 December 1978	189	15 April 1983
190	15 April 1983	190	15 December 1978
191	15 April 1983	191	15 December 1978
192	15 April 1983	192	15 December 1978
193	15 April 1983	193	15 December 1978
195	15 April 1983	195	15 December 1978
196	15 December 1978	(REPRINTED WITHOUT CHANGE)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

2 RETAIN THIS NOTICE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-69A(MI) will verify that page changes and additions indicated above have been entered. These notice pages will be retained as check sheets. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodian:
Army - MI

Review activities:
Army - AT
Army - AV
Army - ER
Army - ME
Army - MR
Army - CR

User activity:
Army - AR

Preparing activity:
Army - MI

(Project EDS-A326)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for rectangular connectors.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate an MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
F. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for an MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSE's for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for an MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in Cataloging Handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

TABLE I. TITLE INDEX.

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONNECTOR, ELECTRICAL, RECTANGULAR	072001	MIL-C-21617	POLARIZED SHELL SOLDER, ENVIRON AND NON-ENVIRON
		MIL-C-81659	POLARIZED SHELL CRIMP, ENVIRON
		MIL-C-83513	POLARIZED SHELL MICROMINIATURE
CONNECTOR, ELECTRICAL, RECTANGULAR, COAXIAL CONTACT	072005	MIL-C-28748	SHIELDED
		MS27741	SHIELD TERM.
CONNECTOR, ELECTRICAL RECTANGULAR, MINIATURE,	072002	MIL-C-24308	KEYSTONE SHELL CRIMP AND SOLDR NON-ENVIRONMTL
		MS14058	PC SOCKETS
		MS14059	PC PINS
		MS18268	PLUG, SOLDR PIN
		MS18269	RCPT, SOLDR SKT
		MS18270	RCPT, CRIMP SKT
		MS18271	PLUG, CRIMP PIN
		MS18272	PLUG, HERM PIN
		MIL-C-28731	CENTER SCREW-LOCK, CRIMP, NON-ENVIRONMTL
		MIL-C-83733	POLARIZED SHELL ENVIRONMENTAL, CRIMP
CONNECTOR, ELECTRICAL RECTANGULAR, MODULE AND BASE PLATE	072004	MIL-C-28754	MODULAR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX. (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONNECTOR, ELECTRICAL, RECTANGULAR, RACK AND PANEL	072003	MIL-C-28748	SCREW POLARIZED CRIMP AND SOLDR NON-ENVIRONMTL
			SOLDER SIZE 22
		MS14012	4 PIN
		MS14013	4 SOCKET
		MS14014	7 PIN
		MS14015	7 SOCKET
		MS14016	14 PIN
		MS14017	14 SOCKET
		MS14018	20 PIN
		MS14019	20 SOCKET
		MS14020	26 PIN
		MS14021	26 SOCKET
		MS14022	34 PIN
		MS14023	34 SOCKET
		MS14024	44 PIN
		MS14025	44 SOCKET
		MS14026	50 PIN
		MS14027	50 SOCKET
			SOLDER SIZE 16
		MS18239	9 SOCKET
		MS18240	14 PIN
		MS18241	14 SOCKET
		MS18242	20 PIN
		MS18243	20 SOCKET
		MS18244	34 PIN
		MS18245	34 SOCKET
		MS18246	42 PIN
		MS18247	42 SOCKET
		MS18248	50 PIN
		MS18249	50 SOCKET
		MS18250	66 PIN
		MS18251	66 SOCKET
		MS18252	75 PIN
		MS18253	75 SOCKET
		MS18254	104 PIN
		MS18255	104 SOCKET

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
CONNECTOR, ELECTRICAL, RECTANGULAR, RACK AND PANEL	072003 (CONT)		SOLDER SIZE 20
		MS18256	9 SOCKET
		MS18257	9 PIN
		MS18258	42 PIN
		MS18259	75 SOCKET
		MS18260	42 SOCKET
		MS18261	75 PIN
		MS18262	104 SOCKET
		MS18263	104 PIN
		MS18264	9 PIN
		MS24003	7 SOCKET
		MS24004	7 PIN
		MS24009	14 SOCKET
		MS24010	14 PIN
		MS24013	20 SOCKET
		MS24014	20 PIN
		MS24019	26 SOCKET
		MS24020	26 PIN
		MS24021	34 SOCKET
		MS24022	34 PIN
		MS24025	50 SOCKET
		MS24026	50 PIN
		MIL-C-28804	POLARIZED SCREW LOCK, CRIMP AND SOLDER ENVIRON AND NON-ENVIRON
		MIL-C-85028	POLARIZED CTR JACKSCREW, CRIMP, ENVIRON
CONNECTOR, ELECTRICAL SUBMINIATURE	072006	MIL-C-28804	POLARIZED CTR JACKSCREW, HIGH DENSITY
		MIL-C-24308	POLARIZED SHELL RACK & PANEL

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table II provides codes for column headings which may be used for rectangular connector characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

Reprinted without change

TABLE II. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1568	CONTACT SPEC AND DETAIL SHT	1570	CONTACT MS NUMBER	1609	HARDWARE
1612	SHELL SIZE	1616	CONTACT RATING MAX AMPERES	1618	CONTACT RATING NOM AMPERES
1678	NUMBER OF CONTACTS	1682	CONTACT TYPE	1686	WIRE SIZE (AWG)
1688	WIRE SIZE MILLIMTR	1690	TERMINATE TYPE	1788	PLZN
1790	SHELL DOC DES	1796	BACKSHELL PART NO.	1800	INSERT ARR ILL NO.
1802	CONTACT ILL NO.	1824	MATING CONNECTOR PART NO.	1827	ASSY ILL. NUMBER
1830	DC OR RMS RATED WKG VOLTAGE	1916	SHELL PART NO.	2002	MAXIMUM CONTACT RESISTANCE
3401	CONTACT SIZE	7021	MAX WEIGHT GRAMS	7022	MAX WEIGHT OUNCES
7023	MAX WEIGHT POUNDS	7024	MAX WEIGHT KILOGRAMS		

Source: https://assist.dla.mil - Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1806	GROMMET (WIRE SEAL). THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1844	THE GROMMET SHALL BE DESIGNED TO ACCOMMODATE A WIRE SIZE NOT GREATER THAN 1844 INCH OUTSIDE DIAMETER.
1810	THE GROMMET SHALL BE DESIGNED TO ACCOMMODATE A WIRE SIZE NOT GREATER THAN 1810 MILLIMETER(S) OUTSIDE DIAMETER.
1846	THE GROMMET SHALL BE DESIGNED TO PROVIDE SEALING ON A WIRE SIZE NOT LESS THAN 1846 INCH OUTSIDE DIAMETER.
1812	THE GROMMET SHALL BE SESIGNED TO PROVIDE SEALING ON A WIRE SIZE NOT LESS THAN 1812 MILLIMETER(S) OUTSIDE DIAMETER.
1814	GROMMET SEALING PLUGS. GROMMET SEALING PLUGS SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1814.
1816	GROMMET SEALING PLUGS. GROMMET SEALING PLUGS SHALL BE IN ACCORDANCE WITH 1816.
1818	1818 PERCENT OF THE NUMBER OF CONTACTS, BUT NOT LESS THAN 1, SHALL BE INCLUDED IN THE UNIT PACKAGE.
1820	CONNECTORS MAY BE SUPPLIED WITHOUT GROMMET SEALING PLUGS.

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
LUBRICATION	
COMPONENT LUBRICATED (NAME)	1600
LUBRICANT (DOC DES)	1601
MATING CONNECTOR	
(DOC DES)	1822
(PART NUMBER)	1824
(VENDOR FSCM)	1826
CONNECTOR ASSEMBLY (ILLUSTRATION NUMBER)	1827
ALTITUDE	
OPERATING (SELECT ONE)	
SEA LEVEL TO (FEET)	6790
SEA LEVEL TO (METERS)	6791
NONOPERATING (SELECT ONE)	
SEA LEVEL TO (FEET)	6972
SEA LEVEL TO (METERS)	6793

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1600	LUBRICATION. THE 1600 OF THE CONNECTOR SHALL BE LUBRICATED.
1601	LUBRICANT IN ACCORDANCE WITH 1601 SHALL BE USED.
	MATING CONNECTOR.
1822	THE MATING CONNECTOR SHALL BE IN ACCORDANCE WITH 1822.
1824	THE MATING CONNECTOR PART NUMBER SHALL BE 1824.
1826	THE MATING CONNECTOR VENDOR FSCM SHALL BE 1826.
1827	CONNECTOR ASSEMBLY. THE CONNECTOR ASSEMBLY SHALL BE IN ACCORDANCE WITH ILLUSTRATION 1827.
6790	OPERATING ALTITUDE. THE OPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6970 FEET.
6791	OPERATING ALTITUDE. THE OPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6791 METERS.
6792	NONOPERATING ALTITUDE. THE NONOPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6792 FEET.
6793	NONOPERATING ALTITUDE. THE NONOPERATING ALTITUDE SHALL BE FROM SEA LEVEL TO 6793 METERS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE	
MAXIMUM OPERATING (DEGREES CELSIUS)	6794

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
6794	MAXIMUM OPERATING TEMPERATURE. THE OPERATING TEMPERATURE SHALL BE NOT GREATER THAN 6794 DEGREES CELSIUS.

New page

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DESIGN AND CONSTRUCTION (CONT)	
TEMPERATURE (CONT)	
MAXIMUM NONOPERATING (DEGREES CELSIUS)	6795
MAXIMUM STORAGE (DEGREES CELSIUS)	6796
MAXIMUM AMBIENT OPERATING (DEGREES CELSIUS)	6798
MINIMUM OPERATING (DEGREES CELSIUS)	6799
MINIMUM STORAGE (DEGREES CELSIUS)	6801
MINIMUM AMBIENT OPERATING (DEGREES CELSIUS)	6803
WEIGHT	
MAXIMUM WEIGHT PER UNIT (SELECT ONE)	
U.S. (SELECT ONE)	
(OUNCES)	7022
(POUNDS)	7023
SI (SELECT ONE)	
(GRAMS)	7021
(KILOGRAMS)	7024

Reprinted without change
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
0101	14	1505	146	1640	112	1761	96
0102	14	1508	134	1646	110	1764	96
0103	14	1509	134	1648	110	1768	94
0104	14	1520	108	1652	118	1770	96
0105	14	1529	152	1658	116	1776	92
0107	16	1545	146	1660	116	1778	92
0108	16	1546	146	1662	116	1779	92
0700	14	1568	30	1663	116	1782	90
0800	14	1570	30	1670	26	1786	34
1003	14	1571	30	1672	26	1788	34
1004	14	1572	30	1674	28	1790	34
1005	14	1581	30	1676	28	1792	34
1006	14	1582	30	1678	28	1794	34
1008	14	1586	30	1680	28	1796	34
1009	24	1590	32	1682	28	1798	34
1371	106	1591	32	1684	30	1800	26
1372	108	1592	32	1686	30	1802	30
1373	106	1593	34	1688	30	1806	36
1374	146	1594	34	1690	30	1810	36
1376	106	1595	34	1694	124	1812	36
1377	108	1596	34	1696	124	1814	36
1380	104	1600	38	1700	122	1816	36
1381	108	1601	38	1702	122	1818	36
1383	108	1602	22	1705	58	1820	36
1384	106	1604	22	1712	58	1822	38
1386	106	1606	22	1716	58	1824	38
1387	106	1607	22	1720	102	1826	38
1407	106	1608	22	1722	104	1827	38
1451	132	1609	22	1724	104	1828	20
1468	132	1610	22	1725	104	1829	20
1471	134	1612	22	1727	104	1830	20
1477	98	1614	22	1732	102	1831	20
1478	132	1615	22	1734	102	1832	20
1482	132	1616	22	1738	64	1833	20
1486	132	1618	22	1740	66	1834	20
1488	132	1624	88	1746	64	1835	20
1494	130	1626	88	1748	64	1842	34
1495	132	1628	88	1750	64	1844	36
1502	134	1632	86	1752	64	1846	36
1504	136	1634	88	1756	96	1852	32

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
1854	32	2297	68	3105	76	3180	56
1858	32	2300	66	3108	48	3182	56
1860	32	2304	66	3110	48	3184	56
1862	32	3002	72	3116	48	3186	56
1904	32	3004	72	3118	48	3188	56
1906	32	3006	72	3120	42	3190	56
1910	32	3010	126	3121	42	3192	56
1916	34	3012	126	3122	42	3194	56
1980	70	3018	126	3123	42	3196	56
1990	70	3020	126	3124	42	3198	58
1994	70	3021	126	3125	44	3200	58
2000	68	3024	124	3126	44	3202	58
2002	70	3026	124	3127	50	3204	58
2052	110	3030	46	3128	50	3206	58
2054	110	3031	46	3130	50	3208	58
2060	108	3033	46	3131	42	3210	60
2062	110	3034	46	3132	50	3212	60
2066	114	3035	46	3134	50	3214	60
2068	114	3036	46	3136	50	3216	60
2070	114	3037	46	3138	52	3218	60
2078	112	3039	46	3140	52	3220	60
2082	112	3040	46	3142	52	3222	60
2088	72	3042	46	3144	52	3224	60
2090	74	3044	46	3146	52	3226	60
2094	74	3048	44	3148	52	3228	60
2099	74	3049	44	3150	52	3230	62
2100	48	3050	44	3152	52	3232	62
2102	48	3052	44	3154	52	3234	62
2104	48	3054	44	3156	52	3236	62
2106	48	3058	144	3158	54	3238	62
2108	48	3060	144	3160	54	3240	62
2110	50	3064	144	3162	54	3242	62
2112	50	3066	144	3164	54	3244	62
2258	120	3076	144	3166	54	3246	62
2259	120	3082	142	3168	54	3248	62
2262	122	3094	76	3170	54	3250	42
2264	120	3096	76	3172	54	3252	64
2266	120	3098	76	3174	54	3254	64
2294	68	3102	76	3176	54	3256	64
2295	68	3104	76	3178	54	3258	66

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
3260	66	3338	78	3414	29	3496	104
3261	66	3340	80	3415	29	3498	104
3262	66	3342	82	3416	29	3500	106
3264	66	3344	82	3417	29	3502	108
3268	66	3346	82	3418	29	3504	108
3270	66	3348	82	3430	90	3506	108
3272	66	3350	82	3432	90	3508	108
3274	68	3352	82	3434	92	3510	110
3276	68	3354	82	3436	92	3512	110
3278	68	3356	82	3438	92	3514	110
3280	68	3358	82	3440	92	3516	112
3282	70	3360	84	3442	92	3518	112
3284	70	3362	86	3444	92	3520	112
3286	70	3364	86	3446	92	3522	112
3288	70	3366	88	3448	92	3524	112
3289	70	3368	88	3450	92	3526	112
3290	72	3370	88	3452	96	3528	114
3292	72	3372	88	3454	96	3530	114
3294	72	3374	88	3456	96	3532	114
3296	72	3376	90	3458	96	3534	114
3298	74	3378	90	3460	96	3536	114
3300	74	3380	90	3462	96	3538	114
3302	74	3382	90	3464	100	3540	114
3304	74	3384	90	3466	100	3542	114
3306	74	3386	90	3468	100	3544	114
3308	74	3388	90	3470	100	3546	116
3310	74	3390	90	3472	100	3548	116
3312	74	3401	29	3474	100	3550	116
3314	74	3402	29	3476	100	3552	116
3316	76	3403	29	3478	100	3554	118
3318	76	3404	29	3480	100	3556	118
3320	76	3405	29	3482	100	3558	118
3322	76	3406	29	3484	100	3560	118
3324	78	3407	29	3486	100	3562	118
3326	78	3408	29	3487	102	3564	118
3328	78	3409	29	3488	102	3566	118
3330	78	3410	29	3489	102	3568	118
3332	78	3411	29	3490	102	3570	120
3334	78	3412	29	3492	102	3571	120
3336	78	3413	29	3494	104	3572	120

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
3574	120	3644	136	3726	148	4756	94
3576	120	3646	136	3728	148	4760	94
3578	122	3648	136	3730	148	4761	94
3580	122	3650	136	3732	148	4762	94
3582	122	3652	138	3733	150	4765	128
3584	122	3654	140	3734	150	4766	128
3586	122	3656	140	3736	150	4770	128
3588	122	3658	140	3738	150	4772	128
3590	122	3660	140	3740	150	4773	128
3592	122	3662	140	3742	150	4788	98
3594	124	3664	140	3744	150	4790	100
3596	124	3666	140	3746	150	4793	100
3598	124	3668	140	3748	150	4795	98
3600	124	3670	140	3750	150	4798	98
3602	124	3672	142	3752	150	4799	98
3604	124	3674	142	3754	150	4803	98
3606	124	3676	142	3756	152	4805	98
3608	126	3678	142	3758	152	4813	98
3610	126	3680	142	3760	152	4815	98
3611	126	3682	142	3762	152	4849	80
3612	128	3684	142	3764	152	4850	84
3613	128	3686	142	4662	138	4854	84
3614	128	3688	144	4663	138	4855	84
3616	130	3690	144	4664	138	4856	84
3618	130	3692	146	4665	138	4859	80
3620	130	3694	146	4666	138	4861	84
3622	130	3696	146	4667	138	4867	84
3624	130	3698	146	4672	136	4869	86
3626	130	3700	146	4674	136	4870	86
3628	130	3702	146	4675	136	4874	84
3630	130	3704	146	4681	144	4875	84
3632	130	3706	148	4682	146	4878	126
3634	132	3708	148	4683	138	4884	80
3635	132	3710	148	4684	136	4885	80
3636	134	3714	148	4685	136	4891	80
3637	134	3716	148	4686	136	4894	80
3638	134	3718	148	4715	140	7	86
3639	134	3720	148	4717	86	4900	82
3640	134	3722	148	4754	94	4902	82
3642	134	3724	148	4755	94	4906	80

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC CODE INDEX

CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.	CHAR CODE	PAGE NO.
4908	78	6803	40				
4942	152	6870	154				
4943	152	6873	14				
4944	152	6874	16				
4950	24	6941	16				
5000	86	6942	16				
5052	20	6991	156				
5054	18	6992	156				
5060	18	6993	156				
5061	18	6994	156				
5062	18	6995	156				
5063	18	7001	154				
5068	18	7002	154				
5069	18	7003	154				
5070	18	7004	154				
5071	18	7005	154				
5209	152	7021	40				
6205	138	7022	40				
6263	44	7023	40				
6264	44	7024	40				
6265	44	7301	18				
6267	86	7302	18				
6272	42	7345	42				
6273	42	7572	24				
6280	80	7577	24				
6308	80	7580	26				
6310	82	7629	154				
6359	106	7630	154				
6369	14						
6372	154						
6790	38						
6791	38						
6792	38						
6793	38						
6794	39A						
6795	40						
6796	40						
6798	40						
6799	40						
6801	40						

Source: https://assist.dla.mil - Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

INDEX

	Page
Acceleration	42
Additional Part Marking	156
Additional Requirements	154
Altitude	38
Altitude Immersion	44
Altitude-Low Temperature	48
Altitude Rating	18
Aperture Cards Required	16
Applicable Documents	156
Backshell Accessories	34
Base Document	14
Cable Pull-Out	50
Cable Seal Flexing	52
City, State Zip	14
Classification	22
Company Name/Command	14
Configuration	-24,30
Connector Assembly	38
Contact Axial Concentricity	56
Contact Current Rating	22
Contact Engagement and Separation Force	58
Contact Insertion and Removal Force	64
Contact Pin Strength	66
Contact Resistance	68
Contact Retention	72
Contacts	28
Contract Number/Office Symbol	14
Control, Source	14
Control, Specification	16
Crimp Tensile Strength	76
Crush	76
Date	14
Design and Construction	26
Dielectric Withstanding Voltage at Reduced Barometric Pressure	78
Dielectric Withstanding Voltage at Sea Level	84
Durability	86
Finishes	26
Flammability	88
Fluid Immersion	90
Format	14
Fungus	94

Source: https://assist.dla.mil - Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.

INDEX (CONT)

	Page
Gage Location and Retention	94
Government Design Activity FSCM	14
Grommet Sealing Plugs	36
Grommet (Wire Seal)	34
Humidity	98
Identification	30
Illustrations	24
Insert	26
Insertion	32
Insert Retention	102
Insulation Resistance	104
Low-Signal Level Contact Resistance	108
Lubrication	38
Magnetic Permeability	110
Maintenance Aging	112
Materials	26
Mating Connector	38
Mating and Unmating Forces	116
Metals	26
Mounting Hardware	154
Nomenclature	156
Notes	156
Oversize Pin Exclusion	120
Ozone Exposure	122
Packaging	156
Part Marking	154
Part Number	16
Part Number Cross-Reference	156
Phone Number	14
Polarization	32
Probe Damage (Contacts)	124
Quality Assurance Provisions	156
Rated Working Voltage	20
Removal	32
Requester FSCM	14
Requester's Name	14

Reprinted without change

☆U.S. GOVERNMENT PRINTING OFFICE: 1983 — 805-034/3978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:58Z
Check the source to verify that this is the current version before use.