INCH-POUND

NOTICE OF CHANGE

MIL-STD-1247C
NOTICE 3
25 May 1994

MILITARY STANDARD

MARKINGS, FUNCTIONS AND HAZARD DESIGNATIONS OF HOSE, PIPE, AND TUBE LINES FOR AIRCRAFT MILLES AND SPACE SYSTEMS

~~TO ALL HOLDERS OF MIL-STD-1247C:~~

1. THE FOLLOWING PAGES OF MIL-STD-1247C HAVE BEEN CORRECTED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
1	13 October 1989	1	REPRINTED WITHOUT CHANGE
2	10 May 1994	2	13 October 1989
2A	10 May 1994	2	13 October 1989
7	21 October 1991	7	24 March 1993
~~7A~~	~~21 October 1991~~	~~7~~	~~24 March 1993~~
8	24 March 1993	8	REPRINTED WITHOUT CHANGE
8A	24 March 1993	8	REPRINTED WITHOUT CHANGE

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-1247 will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the military standard is completely revised or canceled.

AMSC N/A AREA SAFT

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

Custodians:
Army - MI
Navy - AS
Air Force - 16

Review activities:
Army - AR, AV
Navy - OS
Air Force - 10, 11, 19, 68
DLA - GS

International interest: (para 6.4)

Preparing activity:
Army - MI

(Project SAFT-A035)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard establishes material labeling requirements for identification, function, subfunction, pressures, hazards, and direction of flow for pipes, hoses, and tube lines used in aircraft, missiles, space systems, and support equipment. The use of colors, words, and symbols to identify the functions of such items (to include approved abbreviations), and the dimensions of labeling items such as tags, tapes, and bands, are specifically prescribed (see 4.1.1).

1.2 Applicability. The criteria for marking functions upon, and designating hazardous pipes, hoses, and tube lines are designed to result in rapid servicing of functional systems to return them to full operation and are an integral part of the complete system. Lines, pipes, and hoses external to these systems should be coded in accordance with MIL-STD-101.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

QQ-A-250/1	-	Aluminum 1100, Plate and Sheet

MILITARY

MIL-S-5059	-	Steel, Corrosion-Resistant (18-8), Plate, Sheet and Strip
MIL-T-9906	-	Tape, Identification, Aerospace Vehicle Tubing Marker

STANDARDS

FEDERAL

FED-STD-595	-	Colors

MILITARY

MIL-STD-101	-	Color Code for Pipelines and for Compressed Gas Cylinders
MS21045	-	Nut, Self Locking, Hexagon-Regular Height, 450 Degrees F, 125 KSI FTU
MS21919	-	Clamp, Loop Type, Cushioned Support
MS33739	-	Aircraft Markings, Servicing and Precautioning
MS51958	-	Screw, Machine Pan-Head, Cross-Recessed, Corrosion Resisting Steel, UNF-2A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Function.

5.1.1 Colors. Colors conforming to FED-STD-595 as indicated below shall be used to denote function as specified in 5.1.1.1.

Color	FED-STD-595 Code No.
Blue	15102
Green	14187
Yellow	13655
Orange	12197
Red	11136
Brown	10049
Gray	16473
Black	17038

5.1.1.1 Application of colors. Color coding shall be based upon function as indicated below. Where more than one color is required to identify a single function the order of colors is from left to right, and the colored area shall be composed of vertical stripes, of equal width, of the required colors (see figures 2 and 4).

Function	Color
Fuel	Red
Rocket Oxidizer	Green, Gray
Rocket Fuel	Red, Gray
Water Injection	Red, Gray, Red
Lubrication	Yellow
Hydraulic	Blue, Yellow
Solvent	Blue, Brown
Pneumatic Air	Orange, Blue
Instrument Air	Orange, Gray
Coolant	Blue
Breathing Oxygen	Green
Air Conditioning	Brown, Gray
Monopropellant	Yellow, Orange
Battery Activator	Yellow, Gray
Rain Repellants	Blue, Gray
Vacuum	Gray, Orange, Gray
Fire Protection	Brown
De-Icing	Gray
Rocket Catalyst	Yellow, Green
Compressed Gas	Orange
Electrical Conduit	Brown, Orange
Inerting Fluid	Orange, Green

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

Function	Color
Fire Protection	Brown
De-Icing	Gray
Rocket Catalyst	Yellow, Green
Compressed Gas	Orange
Electrical Conduit	Brown, Orange
Inerting Fluid	Orange, Green

Supersedes page 7 of Notice 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

5.1.1.2 Colors on tapes. Tapes used to identify function shall be 1 inch minimum width. The left-hand side shall be colored, and 1/4 inch of the right-hand side shall be reserved for geometric symbols.

5.1.1.3 Colors on painted bands. Paints used for color coding lines in accordance with 4.2.3 shall conform to the color requirements of 5.1.1 and the coding requirements of 5.1.1.1. The entire painted identification group shall completely encircle the line, and shall be of sufficient length to allow a clearance of one-half the letter height (see 5.1.3.3) between lettering and color coding on one end and between lettering and unlettered surfaces on the other end. The color coding shall appear on the left hand side of the identification group as depicted in figure 1, and shall be 2 ± 1/4 inches wide for lines 4 to 13 inches in diameter, 6 ± 3/4 inches for lines larger than 13 inches in diameter. The word group shall be applied as required to enable viewing from the normal point of operation or viewing.

5.1.2 Symbols. Solid black or, as an option, black outlined geometric symbols shall be printed on the tapes to denote functions as indicated i table I. Background shall be white or metallic (silvery or chrome). These symbols shall appear in a repeated pattern, as indicated in figure 2, for the entire length of the tapes. Symbols shall appear on the right-hand side of tapes and shall be approximately 3/16 inches wide and confined to the right of the tape within 1/4 inch from the edge. Symbols may be omitted on bands, tags, or in painted identification.

5.1.3 Wording. Wording denoting function shall be the wording specified under function in table I, or as otherwise approved by the procuring activity

5.1.3.1 Wording on tapes. Letters shall be 3/32 inch high, and shall be printed as shown in figures 1,2, and 4. There shall be a 1/32 inch vertical space between words when more than one written line is required to complete a statement of function. Such statements shall normally recur at 1/4 inch interval throughout the length of the tape. Lettering shall be black. regardless of the background color.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.

5.1.3.2 Wording on tags. Words indicating functions shall be the first word appearing at the top of the tag. Wording on tags shall be of such size as to be clearly legible and compatible to the diameter of the line.

5.1.3.3 Painted words. ~~Letters shall be painted black on a~~ white background, or they may be stenciled. Letters shall be of such size as to be clearly legible and compatible with the size of the lines. Words denoting function shall be the first words appearing in the identification.

Reprinted without change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:34Z
Check the source to verify that this is the current version before use.