





TYPE A - CABLE CLAMP, STRAIN RELIEF

DASH NO. (a)	CONNECTOR SHELL SIZE (REF) (b)	A THREAD	B MAX	C	D	E ±.031 DIA	F ±.031	G ±.031	BUSHING (REF) (c)
-3A	8S AND 10S	.500-28 UNEF-2B	.250	.047	.406	.688	.812	.812	MS3420-3
-4A	10SL. 12S AND 12	.625-24 UNEF-2B	.312	.062		.812	875		MS3420-4
-6A	14S AND 14	.750-20 UNEF-2B	.438	.078		.969	1.062	.875	MS3420-6
-8A	16S AND 16	.875-20 UNEF-2B	.562	.109		1.094	1.156		MS3420-8
-10A	18	1.000-20 UNEF-2B	.625	.125		1.188	1.250	.938	MS3420-10
-12A	20 AND 22	1.188-18 UNEF-2B	.750	.156		1.375	1.469		MS3420-12
-16A	24 AND 28	1.438-18 UNEF-2B	.938	.188		1.656	1.688	1.031	MS3420-16
-20A	32	1.750-18 UNS-2B	1.250	.250	.469	2.031	2.031	1.094	MS3420-20
-24A	36	2.000-18 UNS-2B	1.375	.297	.531	2.219	2.281	1.156	MS3420-24
-28A	40	2.250-16 UN-2B	1.625	.328		2.500	2.688	1.688	MS3420-28
-32A	44	2.500-16 UN-2B	1.875	.375	.594	2.781	2.938	1.750	MS3420-32
-40A	48	3.000-16 UN-2B	2.375	.453	.656	3.281	3.500		MS3420-40

(a) PART NUMBERS MS3057-3A THROUGH -40A ARE INTERCHANGEABLE WITH PART NUMBERS AN3057-3A THROUGH 40A.
(b) CLAMP MATES WITH CONNECTOR SHELL SIZE LISTED IN THIS COLUMN.
(c) BUSHINGS FOR REFERENCE ONLY AND NOT SUPPLIED AS PART OF CLAMP.
FOR ADDITIONAL CLOSE DOWN OF THE B DIMENSION, BUSHINGS MS3420-3 THROUGH MS3420-40 MAY BE USED.
ONE BUSHING AS REQUIRED FOR MS3057-3A THROUGH MS3057-12A, CORRESPONDING TO MS3420-3 THROUGH MS3420-12.
TWO BUSHINGS AS REQUIRED FOR MS3057-16A THROUGH MS3057-24A, ONE EACH CORRESPONDING TO MS3420-16 THROUGH MS3420-24, AND MS3420-12 THROUGH MS3420-20. (EXAMPLES: MS3057-16A REQUIRES ONE MS3420-16 AND ONE MS3420-12.)
THREE BUSHINGS AS REQUIRED FOR MS3057-28A THROUGH MS3057-40A, ONE EACH CORRESPONDING TO MS3420-28 THROUGH MS3420-40, AND MS3420-24 THROUGH MS3420-32, AND MS3420-20 THROUGH MS3420-28. (EXAMPLES: MS3057-40A REQUIRES ONE MS3420-40, ONE MS3420-32, AND ONE MS3420-28.)

NOTES:
1. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.016. ANGLES ±2°. DIMENSIONS AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5-1973.
2. MATERIAL: ALUMINUM ALLOY, QQ-A-591. ALLOY NO. 13.
3. FINISH: IN ACCORDANCE WITH MIL-C-5015.
4. THREADS IN ACCORDANCE WITH MIL-S-7742.
5. REMOVE ALL BURRS AND SHARP EDGES.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

(E) INACTIVE FOR DESIGN AFTER 1 JULY 1982. DOCUMENT WILL BE CANCELLED AFTER 1 JULY 1984, USE MIL-C-85049/1,/2,/41,/42

(E) DENOTES CHANGES

P.A Navy - AS Other Cust Army - EL USAF - 85	International interest	TITLE CLAMPS, CABLE, ELECTRICAL CONNECTOR	MILITARY STANDARD MS 3057
Procurement Specification MIL-C-5015		SUPERSEDES: AN3057	PAGE 1 OF 8

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NO. 5935-3297-01

APPROVED 17 Dec 58 REVISED (A) 10 Jan 63 (B) 27 Feb 70 (C) 5 Nov 70 (D) 13 Oct 76 (E) 10 May 1982

User activities: Army - AT, AV, ME; Navy - MC, SH, OS; Air Force -

Review activities: Army - MU, MI; Navy - EC, OS; Air Force -

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - MU, MI
Navy - EC, OS
Air Force -

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

P.A	International interest
NAVY - AS Other Cust Army - EL USAF - 85	

Procurement Specification: MIL-C-5015


SUPERSEDES: AN3057

TITLE: CLAMPS, CABLE, ELECTRICAL CONNECTOR

MILITARY STANDARD

MS3057

PAGE 2 OF 8




TYPE B CABLE SEAL, GROUNDING

(d) FOR ADDITIONAL CLOSEDOWN OF THE Z DIMENSION, BUSHINGS MS3420-3A THROUGH MS3420-40A MAY BE USED. DIAMETER Z SHALL BE FREE OF OBSTRUCTIONS.
(e) APPLY LUBRICANT, VV-P-236 TO THREADS AND SURFACES OF SLEEVE.
(f) RETAINING RING TO BE BONDED IN RUBBER GLAND.
(g) SERRATIONS AT BASE OF RETAINING RING MAY BE COVERED WITH A MAXIMUM OF .013 RUBBER FOR SIZES 3B THROUGH 10B, IF COVERED, THE RUBBER SHALL BE MOLDED TO THE CONTOUR OF THE SERRATIONS.

NOTES:

6. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.016. ANGLES ±2°. DIMENSIONS AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5-1973. SEE SHEET 3 FOR TABULATED DIMENSIONS.
7. MATERIAL: BODY, ALUMINUM ALLOY, QQ-A-225/5, TEMPER T4; QQ-A-601 OR QQ-A-591, ALLOY NO. 13, 218, 380, OR SC114A. SLEEVE, ALUMINUM, AMS4025 OR QQ-A-225. GLAND, RUBBER, AMS3209, DUROMETER "A" 70 ± 5. RETAINING RING, BRASS, SAE 70, HARD TEMPER ONLY.
8. FINISH: BODY, SCREWS AND WASHERS - CADMIUM PLATE, SPECIFICATION QQ-P-416, TYPE II, CLASS 3; COLOR, DULL OLIVE DRAB, ELECTRICALLY CONDUCTIVE. SLEEVE - SPECIFICATION MIL-C-5541. THE PORTION OF THE SLEEVE IN CONTACT WITH THE BODY SHALL BE COATED WITH POLYTETRAFLUOROETHYLENE RESIN FOR SIZES 3B THRU 10B.
9. THREADS IN ACCORDANCE WITH MIL-S-7742.
10. REMOVE ALL BURRS AND SHARP EDGES.



SIDE VIEW OF SERRATIONS ON RETAINING RING (20 SERRATIONS PER INCH)

FED. SUP CLASS 5935

APPROVED 17 Dec 58 REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - MU, MI
Navy - EC, OS
Air Force -

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

P.A Navy - AS
Other Cust Army - EL
USAF - 85
International interest

Procurement Specification MIL-C-5015

SUPERSEDES: AN3057

TITLE
CLAMPS, CABLE, ELECTRICAL CONNECTOR

MILITARY STANDARD
MS3057

PAGE 3 OF 8

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

FED. SUP CLASS 5935

TYPE B CABLE SEAL, GROUNDING

DASH NO. (h)	CONNECTOR SHELL SIZE (REF) (i)	A +.031 -.016	C MAX	D +.000 -.020 DIA GLAND	F +.020 -.000 DIA	H +.000 -.020 DIA	K MAX	L MIN	M ±.031	N	P ±2°	R MIN
-3B	8S AND 10S	.188	.812	.389	.231	.441	1.031	.156	.473	.254	20°	.531
-4B	10SL, 12S AND 12		.937	.510	.315	.560						
-6B	14S AND 14		1.062	.627	.440	.676					30°	
-8B	16S AND 16		1.188	.744	.515	.800						
-10B	18		1.312	.870	.614	.926	1.094		.537	.281		
-12B	20 AND 22	.250	1.562	1.037	.738	1.107	1.219		.625	.320		
-16B	24 AND 28		1.750	1.286	.926	1.357			.662	.344		
-20B	32	.312	2.250	1.590	1.200	1.670	1.344			.406	35°	.562
-24B	36		2.375	1.844	1.363	1.920	1.547		.940			.781
-28B	40		2.625	2.083	1.611	2.162						
-32B	44	.375	2.812	2.332	1.865	2.412	1.734	.188	1.047	.500		
-40B	48		3.312	2.832	2.365	2.912	1.781					

DASH NO. (h)	S	T	U THREAD	V THREAD	W MIN	X	Z DIA APPROX (GLAND) FREE	Z DIA APPROX (GLAND) CLOSED	BUSHING (REF)	MAX CABLE DIA
-3B	.200	.641	6-32UNC-2A	.500-28 UNEF-2B	.281	.025 +.010 -.003	.219	.031	MS3420-3A	.219
-4B				.625-24 UNEF-2B			.312	.094	MS3420-4A	.312
-6B				.750-20 UNEF-2B			.438	.250	MS3420-6A	.438
-8B				.875-20 UNEF-2B			.531	.312	MS3420-8A	.515
-10B	.218	.672		1.000-20 UNEF-2B		.032 +.012 -.003	.625	.375	MS3420-10A	.614
-12B	.273	.719	8-32UNC-2A	1.188-18 UNEF-2B	.344		.750	.500	MS3420-12A	.738
-16B				1.438-18 UNEF-2B			.938	.594	MS3420-16A	.926
-20B	.431	.797	10-32UNF-2A	1.750-18 UNS-2B	.406	.051 ±.005	1.250	.938	MS3420-20A	1.200
-24B		1.016		2.000-18 UNS-2B			1.375	.969	MS3420-24A	1.363
-28B				2.250-16 UN-2B			1.625	1.188	MS3420-28A	1.611
-32B	.500	1.172		2.500-16 UN-2B		.064 ±.005	1.875	1.375	MS3420-32A	1.865
-40B		1.234		3.000-16 UN-2B			2.375	1.875	MS3420-40A	2.365

(h) PART NUMBERS MS3057-3B THROUGH -40B ARE INTERCHANGEABLE WITH PART NUMBERS AN3057-3B THROUGH -40B.

(i) CLAMP MATES WITH CONNECTOR SHELL SIZE LISTED IN THIS COLUMN.

APPROVED 17 Dec 58

REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - MU, MI; Navy - EC, OS; Air Force -

User activities: Army - AT, AV, ME; Navy - MC, SH, OS; Air Force -

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

P.A Navy - AS

Other Cust Army - EL USAF - 85

International interest

Procurement Specification MIL-C-5015

SUPERSEDES: AN3057

TITLE


CLAMPS, CABLE, ELECTRICAL CONNECTOR

MILITARY STANDARD

MS3057

PAGE 4 OF 8

FED. SUP CLASS 5935




TYPE C CABLE SEAL, STRAIN-RELIEF

(j) FOR ADDITIONAL CLOSE DOWN OF THE Z DIMENSION, BUSHINGS MS3420-3A THROUGH MS3420-40A MAY BE USED. DIAMETER Z SHALL BE FREE OF OBSTRUCTIONS.
(k) APPLY LUBRICANT, VV-P-236 TO THREADS AND SURFACES OF SLEEVE.
(l) SERRATIONS AT BASE OF RETAINING RING MAY BE COVERED WITH A MAXIMUM OF .013 RUBBER FOR SIZES 3C THROUGH 10C, IF COVERED, THE RUBBER SHALL BE MOLDED TO THE CONTOUR OF THE SERRATIONS.
(m) RETAINING RING TO BE BONDED IN RUBBER GLAND.
(n) "E" MIN WITH CLAMPING BARS FULLY OPENED SHALL BE NO LESS THAN "B" DIMENSION.

NOTES:

11. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ± .016. ANGLES ± 2°. DIMENSIONS AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5-1973. SEE SHEET 5 FOR TABULATED DIMENSIONS.
12. MATERIAL: BODY, ALUMINUM ALLOY, QQ-A-225/5, TEMPER T4; QQ-A-601 OR QQ-A-591. ALLOY NO. 13, 218, 380, OR SC114A.
SLEEVE, ALUMINUM, AMS4025 OR QQ-A-225
GLAND, RUBBER, AMS3209, DUROMETER "A" 70 ± 5.
RETAINING RING, BRASS, SAE70, HARD TEMPER ONLY.
CLAMPING BARS, ALUMINUM QQ-A-250/8 TEMPER H32.
13. FINISH: BODY, SCREWS AND WASHERS - CADMIUM PLATE, SPECIFICATION QQ-P-416, TYPE II, CLASS 3; COLOR, DULL OLIVE DRAB, ELECTRICALLY CONDUCTIVE.
SLEEVE - SPECIFICATION MIL-C-5541. THE PORTION OF THE SLEEVE IN CONTACT WITH THE BODY SHALL BE COATED WITH POLYTETRAFLUOROETHYLENE RESIN FOR SIZES 3C THRU 10C.
14. THREADS IN ACCORDANCE WITH MIL-S-7742.
15. REMOVE ALL BURRS AND SHARP EDGES.



(l) SIDE VIEW OF SERRATIONS ON RETAINING RING (20 SERRATIONS PER INCH)

APPROVED 17 Dec 58 REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - MU, MI
Navy - EC, OS
Air Force -

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

P.A Navy - AS
Other Cust Army - EL USAF - 85
International interest
Procurement Specification MIL-C-5015
SUPERSEDES: AN3057
TITLE
CLAMPS, CABLE, ELECTRICAL CONNECTOR
MS3057
MILITARY STANDARD
PAGE 5 OF 8

FED. SUP CLASS 5935

TYPE C CABLE SEAL, STRAIN RELIEF

DASH NO.	CONNECTOR SHELL SIZE (REF) (o)	A +.031 -.016	B MIN CABLE CLEARANCE	C MAX	D +.000 -.020 DIA GLAND	E MAX CLOSED	F +.020 -.000 DIA	G ± .016	H +.000 -.020 DIA	J ±.020	K MAX	L MIN	M ±.031	N	P	R MIN
-3C	8S AND 10S	.188	.239	.812	.389	.217	.231	.125	.441	.875	1.375	.156	.473	.254	20°	.531
-4C	10SL, 12S AND 12		.317	.937	.510	.296	.315		.560							
-6C	14S AND 14		.443	1.062	.627	.390	.440		.676						30°	
-8C	16S AND 16		.551	1.188	.744	.434	.515		.800							
-10C	18		.630	1.312	.870		.614		.926	.927	1.437		.537	.281		
-12C	20 AND 22	.250	.771	1.562	1.037	.596	.738	.156	1.107	1.016	1.562		.625	.320		
-16C	24 AND 28		.959	1.750	1.286		.926		1.357	1.037	1.812		.662	.344		.562
-20C	32	.312	1.271	2.250	1.590	.858	1.200	.188	1.670	1.167	2.062		.940	.406	35°	.781
-24C	36		1.396	2.375	1.844		1.363		1.920	1.386						
-28C	40		1.646	2.625	2.083	1.107	1.611		2.162							
-32C	44	.375	1.896	2.812	2.332	1.421	1.865		2.412	1.480	2.188	.188	1.047	.500		

DASH NO.	S	T	U THREAD	V THREAD	W MIN	X	Z DIA APPROX (GLAND) FREE	Z DIA APPROX (GLAND) CLOSED	BUSHING (REF)	MAX CABLE DIA
-3C	.200	.641	6-32UNC-2A	.500-28 UNEF-2B	.469	.025 +.010 -.003	.219	.031	MS3420-3A	.219
-4C				.625-24 UNEF-2B	.594		.312	.094	MS3420-4A	.312
-6C				.750-20 UNEF-2B			.438	.250	MS3420-6A	.438
-8C				.875-20 UNEF-2B	.719		.531	.312	MS3420-8A	.515
-10C	.218	.672		1.000-20 UNEF-2B		.032 +.012 -.003	.625	.375	MS3420-10A	.614
-12C	.273	.719	8-32UNC-2A	1.188-18 UNEF-2B	.844		.750	.500	MS3420-12A	.738
-16C				1.438-18 UNEF-2B	1.062		.938	.594	MS3420-16A	.926
-20C	.431	.797	1/4-20UNC-2A	1.750-18 UNS-2B	1.187	.051 ±.005	1.250	.938	MS3420-20A	1.200
-24C		1.016		2.000-18 UNS-2B	1.312		1.375	.969	MS3420-24A	1.363
-28C				2.250-16 UN-2B			1.625	1.188	MS3420-28A	1.611
-32C	.500	1.172		2.500-16 UN-2B		.064 ±.005	1.875	1.375	MS3420-32A	1.865

(o) CLAMP MATES WITH CONNECTOR SHELL SIZE LISTED IN THIS COLUMN.

APPROVED 17 Dec 58 REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.


This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.


Review activities: Army - MU, MI
Navy - EC, OS
Air Force -

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

P.A Navy - AS
Other Cust Army - EL USAF - 85
International interest
Procurement Specification MIL-C-5015
SUPERSEDES: AN3057
TITLE CLAMPS, CABLE, ELECTRICAL CONNECTOR
MILITARY STANDARD MS3057
PAGE 6 OF 8





DESIGN OPTIONAL STAINLESS STEEL

DETAIL A

SCREW TELESCOPING, FIL. HD.

#4-40 UNC-2*, clamp size 4 thru 10
#6-32 UNC-2*, clamp size 12 and 16
#8-32 UNC-2*, clamp size 20 thru 32

Type D - Cable clamp, heavy duty, high shock

FED. SUP CLASS 5935

APPROVED 17 Dec 58 REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Review activities: Army - MU, MI
Navy - EC, OS
Air Force -

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

P.A Navy - AS
Other Cust Army - EL
USAF - 85

International interest

Procurement Specification MIL-C-5015

SUPERSEDES: AN3057

TITLE: CLAMPS, CABLE, ELECTRICAL CONNECTOR

MILITARY STANDARD MS3057

PAGE 7 OF 8

FED. SUP CLASS 5935

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Type D - Cable clamp, heavy duty, high shock.

Dash No.	A Thread Class 2A	B Dia Max	C ±.010	D ±.020	E +.000 -.007	F ±.010	G ±.020	H Clamp Range Min	H Clamp Range Max	J Dia ±.010	K ±.010	M ±.010	N ±.010	P ±.005	Test plug diameter (inches) Min	Test plug diameter (inches) Max	Pull-out load (pounds)	Clamp size range
-4D	.625-24 UNEF	.937	.637	.937	.250	.312	1.281	.125	.312	.218	.062	.156	.109	.166	.109	.125	25	1
-6D	.750-20 UNEF	1.031	.763	1.125	.250	.375	1.281	.250	.437	.281	.062	.175	.125	.166	.234	.250		
-8D	.875-20 UNEF	1.250	.942 ±.032	1.312	.250	.422 ±.026	1.281	.312	.562	.312	.062	.211 ±.018	.125	.166	.296	.312	50	
-10D	1.000-20 UNEF	1.250	.964	1.312	.250	.437	1.281	.350	.625	.312	.062	.218	.125	.166	.334	.350		
-12D	1.188-18 UNEF	1.437	1.130	1.531	.250	.437	1.312	.500	.750	.375	.062	.250	.156	.192	.484	.500		2
-16D	1.438-18 UNEF	1.688	1.375	1.750	.250	.531	1.406	.625	.937	.375	.062	.250	.188	.192	.609	.625	75	
-20D	1.750-18 UNS	2.000	1.703	2.093	.312	.531	1.593	.875	1.250	.475	.078	.312	.188	.217	.859	.875		
-24D	2.000-18 UNS	2.250	1.906	2.343	.312	.531	1.625	1.000	1.375	.500	.093	.312	.250	.217	.984	1.000		3
-28D	2.250-16 UN	2.500	2.218	2.750	.312	.812	1.900	1.250	1.625	.625	.093	.312	.375	.217	1.234	1.250	100	
-32D	2.500-16 UN	2.750	2.500	3.000	.312	.812	1.900	1.437	1.875	.675	.125	.312	.375	.217	1.421	1.437		

NOTE: Unless otherwise specified, tolerances shall be: .xx = ±.01; .xxx = ±.005; angular: x° = ±1°00'; x°xx' = ±0°30'.

APPROVED 17 Dec 58

REVISED (E) FOR CHANGES SEE SHEET 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.

Requirements:

A. Material: Clamp body and saddle - Aluminum alloy, per QQ-A-591, comp. 13,380 or A 380. clamp screws - AISI 300 series stainless steel.

B. Finish:

Designator	Finish	
A	Cadmium plate, per QQ-P-416, type II, class 3, over nickel: Color - Olive drab.	
C	Cadmium plate, per QQ-P-416, type II, class 3; Color - Olive drab.	
N	Electroless nickel, per MIL-C-26074, class 3 or 4, grade B.	
D	Nonmagnetic corrosion resisting steel, per QQ-S-763, 300 series classes	Cadmium plate, per QQ-P-416, type II, class 3, color - black.
S		Passivate

Performance: MS3188, MS3189, MS3437 or other suitable back shells shall be used as the test fixture when necessary.

C. Magnetic permeability -

The relative magnetic permeability shall be less than 2.0 when checked with an indicator conforming to MIL-I-17214.

D. Vibration -

The assembly shall be subjected to the vibration requirements of MIL-STD-167-1(Ships) paragraph 5.1.3.3.3 and Method 204, condition B of MIL-STD-202. There shall be no loosening of parts or evidence of damage due to vibration. No safety wires shall be used.

E. Shock -

The assembly shall be subjected to the requirements of MIL-S-901, grade A. The clamp is a subassembly, class I, lightweight test classification (250 lbs. or less) type C. There shall be no loosening of parts or evidence of damage due to shock. No safety wires shall be used.

F. Salt spray (corrosion) -

Salt spray test in accordance with Method 1001 of MIL-STD-1344 test condition B. There shall be no exposure of basis metal due to corrosion.

G. Cable Pull-Out -

Cables shall not pull out when specified loads in table are applied, nor shall the slippage exceed .125 inch.

H. Quality assurance:

A. Examination of product.

I. Military part number: See example.

MS3057 - 16D A

Basic No.
Dash No.
Finish designator
See requirement B

User activities: Army - AT, AV, ME
Navy - MC, SH, OS
Air Force -

Review activities: Army - MU, MI
Navy - FC, OS
Air Force -

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 17 Dec 58 REVISED (E) FOR CHANGES SEE SHEET 1

P.A Navy - AS Other Cust Army - EL USAF - 85	International interest	TITLE CLAMPS, CABLE, ELECTRICAL CONNECTOR	MILITARY STANDARD MS3057
Procurement Specification MIL-C-5015		SUPERSEDES: AN3057	PAGE 8 OF 8

DD FORM 1 MAY 73 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:57Z
Check the source to verify that this is the current version before use.