FEDERAL SPECIFICATION

DOMESTIC (HOUSEHOLD) COMPACTOR

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electrically operated household compactors capable of compacting refuse.

1.2 Classification.

Type I - Mobile
Type II - Stationary

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Underwriters' Laboratories, Inc. (UL)

UL 1086 - Standard for Household Waste Compactors.

(Application for copies should be addressed to the Underwriters' Laboratory, 207 East Ohio St, Chicago, Illinois, 60611).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

Association of Home Appliance Manufacturers (AHAM)

AHAM TC-1 - Performance Evaluation Procedure for Household Trash Compactors.

(Application for copies should be addressed to AHAM, 20 North Walker Dr, Chicago, Illinois 60606.)

Uniform Classification Committee Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tarriff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

3. REQUIREMENTS

3.1 Standard product. Trash compactors shall be the latest standard model of the manufacturer except as modified to meet the requirements of this specification.

3.1.1 Guarantee. The contractor shall be required to guarantee the equipment against defective material, workmanship and performance for a period of one year. The guarantee shall run from the date of acceptance of the equipment by the Government. The contractor shall agree to furnish and replace without cost to the Government all parts and materials which are found to be defective during the guarantee period.

3.2 Technical Industry Standard Association of Home Appliance Manufacturers. Trash compactors shall be tested in accordance with the parameters and procedures outlines in AHAM's Standard No. TC-1. Terms used in this specification to describe household trash compactors and their components shall be as defined in the above-mentioned standard.

Underwriters' Laboratories, Inc. (UL) Trash compactors shall conform to requirements of UL's standard 1086. Acceptable evidence of meeting this requirement shall be (a) UL label, (b) UL listing, or (c) a certified test report from a nationally recognized testing laboratory (acceptable to the Government) that has tested and certified that the trash compactor conforms to applicable requirements of UL's standard 1086.

3.4 Materials.

3.4.1 Cold rolled steel. Cold rolled steel shall be low carbon steel containing less than 0.15 percent carbon and 0.25-0.60 percent manganese.

3.4.2 Motors Electrical Components. Motors and electrical components shall meet the requirements outlined in UL 1086.

3.4.3 Design. The trash compactor shall be a totally enclosed mobile or stationary cabinet provided with a loading door. The cabinet shall be equipped with an electrically powered ram assembly designed to compact bulk waste into a disposable container placed within a compaction chamber. The compaction chamber shall be designed in such a fashon as to allow the deposit of fresh refuse into the chamber when the door is pulled open and allow the removal of the disposable container. The compactor must be designed as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

3.4.3.1 Deodorizing and disenfecting. The compactor shall be equipped with either an automatic or manual pushbutton type disenfecting system. The system must provide the opportunity to spray disenfectant prior to each compaction cycle.

3.4.3.2 Electrical requirements. The compactor shall use 115 volt AC, 15 amp, household current having 2 wire service plus ground wire. The cord shall meet the requirements outlined in UL 1086. For mobile compactors and stationary compactors intended for free standing use, the cord must be a minimum of five feet in usable length. For stationary compactors intended to be built into a kitchen counter installation, the cord must be no less than three feet and no greater than four feet in useable length.

3.4.4 Construction.

3.4.4.1 Cabinet. The cabinet shall be formed of corrosion resistant material and in a configuration to provide adequate strength and proper enclosure. The loading door should open far enough to provide easy access for trash deposit and container removal. Access which does not require the use of special tools, shall be provided for servicing the internal components of the machine.

3.4.4.2 Ram assembly. Ram assembly shall be placed in the upper part of the cabinet and rigidly supported by framing members to prevent vibration. The ram assembly shall consist of an electric motor operated power module of the electro-mechanical type and a vertically descending ram. The electro-mechanical unit shall be equipped with a screw type drive to activate the ram. The ram assemblies shall be capable of providing of the thrust specified in Table I.

3.4.4.3 Compaction chamber. The compaction chamber shall be capable of withstanding the compaction forces that will be exerted upon it. The chamber shall be reinforced and be lined with smooth pitt free walls. The chamber must provide a means for securing the disposable liner in place so that it does not slip down and be compacted with the refuse. The chamber must be so designed as to prevent refuse being compacted from seeping around the packing head.

3.4.4.4 Casters. Casters shall be provided with type I compactors and shall be 2 inches in diameter, swivel type. The front two casters must be locking type. Type II compactors shall be provided with screw type adjustable legs having a maximum of one-inch vertical travel.

3.4.4.5 Disposable containers. Disposable containers shall be leakproof and fabricated from polyethylene plastic, corrugated fiberboard, or impregnated or coated paper as specified (see 6.2). The quantity required shall be as specified (see 6.2) and closures for the container shall be provided.

3.4.4.5.1 Polyethylene bag. Polyethylene bag shall be not less than 3 mils thick and sized to the compaction chamber. If specified, a 2- or 3-piece metal liner that will protect the refuse container from sharp objects such as glass during the compaction cycle shall be provided. The insert shall be fabricated from corrosion resistant material. (see 6.2).

3.4.4.5.2 Corrugated box. Corrugated box shall be 175 pound test single wall, minimum. The interior of the box shall be coated with plastic, wax or other suitable waterproofing material.

3.4.4.5.3 Paper bag. Paper bag shall be 50-pound test minimum. The interior of the bag shall be coated with plastic, wax, or other suitable waterproofing material.

3.4.6 Performance. The compactor tested in accordance with AHAM standard TC-1 shall attain a compaction index falling within the range specified in Table I.

3.5 Safety. Compactors shall meet all safety requirements outlined in UL 1086.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

3.6 Equipment manual. Unless otherwise specified (see 6.2), the supplier shall furnish a copy of the manufacturer's equipment manual containing installation, operation and maintenance instructions and shall include pictures or illustrations with parts identified. The manual shall include electrical data, connection diagrams and contain a complete list of all parts showing part number, name and quantity required. In addition, a wiring diagram should be attached to each unit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.3 Inspection. An inspection shall be made to determine that the quality of the compactor is as specified by this specification. Examination of the end item shall be in accordance with the classification of defects shown in table II. The inspection level shall be S-2. The AQL for major defects shall be 2.5 and the AQL for minor defects, 6.5. The sample unit for this examination shall be one complete trash compactor. The lot shall be expressed in units of complete trash compactors.

TABLE II. Examination of Product Quality

Examine	Defect	Major	Minor
Welding	Not continuous and not free from defects	X	
Finish of metal	Not smooth or free from pitting or irregularities		X
Design	Not as specified in Table I	X	
Workmanship	All parts, components are not well made or free from defects which affect appearance or serviceability	X	
Safety	Not as specified in UL 1086	X	
Performance	Machine does not perform as specified in 3.4.5	X	
Electrical	Does not use household current	X	

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level C.

5.1.1 Level C. The compactors shall be packed in such a manner as to prevent any damage caused by shock and vibration in the course at transit, handling or storage.

5.2 Packing. Packing shall be level C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

5.2.1 Level C. The compactors shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the National Motor Freight Classification rules or the Uniform Freight Classification rules depending on mode of transportation.

5.3 Marking. In addition to markings required by the contract or order, the shipping container shall be marked in accordance with Federal Standard No. 123 for civil agencies or MIL-STD-129 for military agencies.

6. NOTES

6.1 Intended use. The compactors described in this specification are to be used to compact normal household refuse such as napkins, soft drink cans and bottles, coffee grounds, etc., into easily disposable dense sludge.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number and date of this specification.

b. Type of machine required.

c. Whether plastic bags, corrugated, or impregnated paper containers are required and quantity require.

d. Whether metal liner is required.

TABLE I BASIC DESIGN CRITERIA

OUTSIDE DIMENSIONS (inches)	CAPACITY (cu. ft.)		CLEAR TOP [1] OPENING (sq. in.)	COMPACTION INDEX [2]	
36 x 18 x 24	1.0	1.75	280 - 300	12 lb/cu ft	14 lb/cu ft
Max.	Min.	Max.		Min.	Max.

1. Top area of compaction chamber.
2. As defined by AHAM.

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.