GGG-C-1968
April 5, 1976
SUPERSEDING
MIL-C-19482C
June 8, 1970

FEDERAL SPECIFICATION

CARRIERS, STORAGE BATTERY, HAND

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal Agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers hand transported storage battery carriers.

1.2 Classification. The carriers shall be of the following types and sizes, as specified (see 6.2).

Type I - Strap (terminal gripping).

Size 12 - Short.
Size 20 - Long.

Type II - Jaw and handle (case gripping).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids ore request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

W-B-131 - Battery, Storage: Vehicular, Ignition, Lighting, and Starting.
PPP-P-40 - Packaging and Packing of Hand Tools.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.)

FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:43Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The carrier, storage battery, hand, hereinafter called the carrier shall consist of straps with battery post grips, or adjustable tong type brackets with handles and battery case gripping jaws.

3.2 Capacity. The carrier referred to in this specification shall carry class 1, 3, and 4 batteries of W-B-131.

3.3 Material. All materials shall be new and unused. All material shall be as specified shall be of the same quality used for the intended purpose in commercial practice. Materials shall be free from defects which would adversely affect the performance or maintainability of individual component or the overall assembly.

3.4 Standard commercial product. The storage battery carriers shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product, provided the carrier meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining carriers to be furnished under the contract. Additional or better features which are not specifically prohibited by this specification, but which are a part of the manufacturer's standard commerical product shall be included in the carriers being furnished.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:43Z
Check the source to verify that this is the currentversion before use.

3.5 Performance. When subjected to a lifting force not less than the weight of the battery with full charge of electrolyte for not less than 2 minutes, the type I carrier shall not slip on the battery terminals, bend or misaline the terminals, or leave scratches and grooves which result in improper fit and a poor electrical connection. The type II carrier, subjected to the weight of the battery with full charge of electrolyte for not less than 2 minutes, shall not slip and shall not collapse the battery case. All carriers when lifting and carrying the battery for which designed, shall transport the battery in level position and provide positive placement control. Twisting in a manner to rotate the battery clockwise and counterclockwise 45° to 60° during transport shall not break or distort the strap of type I carrier, or damage the pivot and the handle connection of type II carrier.

3.6 Design and construction. Metal parts used for type I and type II carrier construction shall be made of corrosion-resistant alloy or shall be treated or coated to be protected against corrosive effects. Cadmium coating is not acceptable.

3.6.1 Type I carrier. The type I carrier shall consist of a strap with a battery post grip permanently held in place on each end of the strap. The battery post grips shall be disk or ring type, designed to hold the battery posts securely when under lifting tension, and shall have adequate clearance to release easily when relaxed. Post grips shall be designed for working fit with posts of all vehicle style storage batteries conforming to W-B-131, class 1, 3, and 4. Straps shall be of synthetic rubber-impregnated fabric or webbing material, molded synthetic rubber with card insert, or plastic having manufacturer's designation as acid resistant. Synthetic rubber shall be a compound utilizing polymerized chloroprene as the basic material, with a width of not more than 1 inch and a thickness adequate for the performance. The manufacturer's designated acid-resistant plastic shall be a polyethylene material having an indefinite shelf life and maximum-minimum use temperature from +200° Fahrenheit to -70°. The overall length shall be of the manufacturer's nominal standard nearest 12 inches for size 12, and 20 inches for size 20 as applicable.

3.6.2 Type II carrier. The type II carrier shall consist of tongs with a carrying handle, and battery case gripping pads. The carrying handle shall be not less than 3/4 inch in diameter, and shall be parallel to the ground when lifting and carrying the battery. The tongs shall be designed with an action which will cause the gripping pads to close against the battery sides when lifting force is applied to the handle. The tongs shall be hinged with a pin or notched lever design to incorporate an adjustment range between gripping pads, with increments to provide for handling the automotive batteries specified (see 3.2). In proper carrying adjustment, the gripping pads shall bear evenly against the battery sides. Gripping pad surfaces shall be of metal or nonskid durable material, and shall not damage the battery case surface.

3.7 Identification marking. The carriers shall be clearly marked with the manufacturer's name or U.S. Registered Trademark so that the

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:43Z
Check the source to verify that this is the current version before use.

source of manufacture can be easily identified. Marking of items shall be accomplished in a manner which will not adversely affect the life and utility of the item.

3.8 Workmanship. The quality of workmanship shall be such as to produce carriers that meet the requirements of this specification and insure proper functioning of all parts of the unit.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Quality conformance inspection shall be performed on the sample carriers selected in accordance with 4.3. This inspection shall include the examination of 4.5 and the tests of 4.6.

4.3 Inspection lot. All carriers of the same type and size offered for delivery at one time shall be considered a lot for purposes of inspection.

4.4 Sampling. Random samples of the carrier shall be selected from each lot in accordance with MIL-STD-105. The inspection level shall be S-2 and Acceptable Quality Level 4.0 percent defective.

4.5 Examination. Each sample selected in accordance with 4.4 shall be examined for compliance with the requirements in section 3 of this specification. This element shall encompass all visual examination and dimensional measurements.

4.6 Tests. All sample carriers selected in accordance with 4.4 shall be tested in accordance with 4.6.1. Defective carriers, parts, and materials shall be replaced with nondefective items. Uncorrectable defects shall be cause for rejection. Dropping of the battery during pickup and hand transport, accidental release of either battery post, battery not level in transport position, damage to the posts and other parts of the battery when using type I carrier, and damage to the battery case when using type II carrier, shall be cause for rejection. Indentations from the metal grippers shall not be considered damage to the battery case.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:43Z
Check the source to verify that this is the current version before use.

4.6.1 Sample carrier tests. Materials and parts shall be tested in accordance with the manufacturer's standard production line quality control procedures. On completion of assembly, each sample carrier shall be used to lift the largest and heaviest acid filled battery conforming to W-B-131, class 1, 3, or 4 from bench to floor or floor to bench, to demonstrate proper function.

4.7 Packaging inspection. Examination of packaging shall be in accordance with the quality assurance section of PPP-P-40.

5. PREPARATION FOR DELIVERY

5.1 Preservation-packaging, packing and marking. Preservation-packaging, packing, and marking shall be in accordance with PPP-P-40. The levels of preservation-packaging and packing shall be as specified (see 6.2), and marking shall be for civil agencies, or military activities as specified (see 6.2).

6. NOTES

6.1 Intended use. Hand transported storage battery carriers are used in automotive and battery service stations to facilitate the safe handling of the storage batteries, and to prevent breakage and accidental contact by personnel with spilled acid. Type I, size 12 carriers are used with conventional type batteries having diagonally opposite terminal posts. Type I, size 20 carriers are used with batteries of end-to-end cell construction and diagonally opposite terminal posts. Type II carriers are used with all batteries so situated that access for lifting is not limited to the terminal posts, and where battery holders may be removed to provide clearance for the lifting jaws.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type and size of carrier required (see 1.2).
(c) Level of preservation-packaging and level of packing required (see 5.1).
(d) Type of marking required (see 5.1)

6.3 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Armed Services Procurement Regulation (ASPR), the data requirements will be developed as specified by an

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:43Z
Check the source to verify that this is the currentversion before use.

approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of ASPR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 Supersession data. This specification includes the requirements of MIL-C-19482 dated 8 June 1970.

MILITARY CUSTODIANS:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Army - ME

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

Navy - YD

Project No. 5120-0776

U. S. GOVERNMENT PRINTING OFFICE : 1976 - 210-814/1191

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Prices 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:43Z
Check the source to verify that this is the current version before use.